CUSTOM SCRM4590 DOUBLE-LIPPED STRIKE & RESCUE STOP COMBO 1-3/4" THICK DOOR 1/8" INSET DOOR SCHLAGE MORTISE LOCK W / DEAD BOLT 11-3/4" FRAME 11³ FRAME DOOR 45 45 STOP STOP IS SPRING LOADED ¹16 COVER MAKING PART NON-HANDED <u>13</u> 16 MIN-BUT INSTALLATION IS 3/32 STILL HANDED * $\frac{1}{16}$ ∦ INSET 16 STOP ABH DOOR STOP COVER DIMENSIONS ÇOF MAY NOT MATCH OTHER MANUFACTURERS * **TOP VIEW** DOOR ÇΟF € OF FRAME 3-7/16" -Ŕ DOOR 13 MIN. CLEARANCE FOR DOOR STOP € ⓓ COVER CENTERED $2\frac{7}{16}$ 4-29/32 2-5/16" -4<u>7</u> Ĵ₽ MIN. CLEARANCE FOR DOOR STRIKE CENTERED $4\frac{1}{4}$ 3/16 32 (2) REINFORCEMENT PLATES SUPPLIED (ŧ BY DOOR FRAME $\frac{5}{16}$ MANUFACTURER C'SINK FOR #8 FLAT HEAD SCREW **CUT-OUT FOR** (6 PLACES) **FRONT VIEW METAL JAMB**

NOTE:

1. HORIZONTAL CENTERLINE OF PLATE TO MATCH HORIZONTAL CENTERLINE OF CUTOUT.

2. SCREWS - 8-32 X 3/8" UNDERCUT F.H.M.S.

3. R.H. DOOR SHOWN, L.H. OPPOSITE (RESCUE STOP IS NON HANDED)

4. DO NOT SCALE DRAWING.

5. FOR CUSTOM RESCUE DOOR STOP CONSULT FACTORY.

REINFORCEMENT:

WHEN INSTALLING IN METAL FRAME, REINFORCEMENT IS **NEEDED** WITH THIS PRODUCT, CUSTOMER OR MANUFACTURER TO SUPPLY FRAME REINFORCEMENT WITH LATCH BOLT CLEARANCE.

★ = CRITICAL DIMENSION MUST BE FOLLOWED



www.abhmfg.com E-mail: abhinfo@abhmfg.com Architectural Builders Hardware Mfg., Inc. 1222 Ardmore Ave., Itasca, IL 60143 630.875.9900; FAX 800.9FAXABH (932.9224) SP-CR4624 11.750 x 4.875 SCHLAGE .DWG

SP-CR4624

©2016 ABH Mfg., Inc. printed in USA

ISSUED 12-27-16