

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

1000A Series Concealed Mount, Heavy Duty, Adjustable



Standard Features

- Concealed mount
- Heavy duty
- Stop, hold-open and friction functions available
- Single acting doors only
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Degree of opening is field-adjustable after installation from 85° to 110° (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- 1-3/4" minimum door thickness
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 6 lbs.

Options Available

(see page B-5 for details)

- **SEC** - Security fasteners
- **LL** - For lead-lined door applications
- **LS** - Less shock-absorbing spring for special applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- **HC** - Hold Closed
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

- **Stainless steel** is the standard base material for arm, channel and jamb bracket for all finishes.

Door Frame Opening	Model Number		
Hinges, Swing Clear or Offset Pivots	Hold Open	Stop	Friction
27" - 29-15/16"	1011A	1021A	1031A
30" - 35-15/16"	1012A	1022A	1032A
36" - 39-15/16"	1013A	1023A	1033A
40" - 43-15/16"	1014A	1024A	1034A
44" - 52"	1015A	1025A	1035A
ANSI Code	C01511	C01541	C01531

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable

