# **Overhead Holders & Stops**



### 1000RA Series Concealed Mount, Heavy Duty, Adjustable



#### **Standard Features**

- Concealed mount
- Heavy duty, adjustable
- Internal Channel Slide allows for field adj. degree of open
- Stop, hold-open and friction functions available
- Single or double acting doors
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- 1-3/4" minimum door thickness
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- average weight per unit = 6 lbs.

Door Frame Opening		Model Number		
Butt Hinges or 3/4" Offset Pivots	Center Hung	Hold Open	Stop	Friction
24" - 32"	-	1012RA*	1022RA*	1032RA*
31-1/16" - 40"	31-1/16" - 40"	1013RA	1023RA	1033RA
40-1/16" - 48"	40-1/16" - 48"	1014RA	1024RA	1034RA
ANSI Code		C01511	C01541	C01531

<sup>\*</sup> Butt Hinges and 3/4" Offset Pivots only

# Options Available

(see page B-5 for details)

- **SEC -** Security fasteners
- LL For lead-lined door
- applications
- LS Less shock-absorbing spring for special applications
- N- All stainless steel (non-ferrous) components for wet environments to prevent corrosion
- T Jamb bracket is repaced with a threaded pivot screw and nylon washer
- Special Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additinal hardware is being used at the top of the door.

  A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

#### **Material**

• Stainless steel is the standard base material for arm, channel, and jamb bracket for all finishes

### **Specify When Ordering**

- Model Number
- Finish
- Option(s), if applicable

