

Proprietary Verbal Exit Instructions with Alarm Tone and 3/4" Digital Countdown Display



STANDARD FEATURES INCLUDE: 12/24VDC voltage sensing input, delay electronics packaged on a 3-gang wall plate for recessed wall mounting or surface wall mounting with optional junction box. Features include: std. 15 or 30 second switchable exit delay (NA), 1 or 2 second nuisance delay. Keypad for violation reset, momentary bypass and on-off; Voice Annunciation and digital countdown display with door open indicator. Status and remote control inputs are standard.

12VDC / 24VDC @ 200 mA Max.

- Doors **WITH** latch assemblies are sensor activated and do not require power transfer or trigger switch in exit device. Where preferred a trigger switch may be added to the exit device for manual activation in lieu of door movement activation.
- Doors **WITHOUT** latches require a non-latching Request-to-Exit Bar PSB560 Sure Exit® or MSB550 Switch Bar (see pages 79 - 80). Also compatible with standard EMLocks (see page 7.)



## DELAYED EGRESS CONTROLLER (1 PER OPENING, SINGLE OR PAIRS)

LIST



101-DE

**101-DE** Wall mount controller with keypad control and reset, 200 mA @ 12/24 VDC - NA standard **881.00**

**101-KDE** Wall mount controller with both key switch and keypad control and reset, 200 mA @ 12/24 VDC **998.00**  
order with optional Mortise Cylinder



**CYL-6KDQ** 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 49.00**

**CYL-6KAQ** 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 49.00**

**Specify NA, NC, ND, NH, BC, BD, BH - see codes and description on page 18**

**Optional Add-On: If no Code is specified - NA is the SDC STANDARD OPERATIONS MODE for this product**

**RRX** Reset on REX - No Charge when ordered WITH a 101-DE/KDE.

Allows the REX input to reset after an unauthorized egress alarm. Not available for NC operation. Replacement Chip (if ordered separately from 101-DE/KDE unit)

**56.00**



101-KDE

## MAGNETIC LOCK WITH INTEGRATED ACTIVATION SENSOR

LIST

**Specify 2 for pair of doors**

**1511DEV** Single, 1650 lbs holding force, 670/350 mA @12/24 VDC **560.00**

**1571DEV** Single, 1200 lbs holding force Energy Saver, 250/125 mA @12/24 VDC **532.00**

**1581DEV** Single, 650 lbs holding force, 440/220 mA @12/24 VDC **444.00**

Outdoor Locks

**1575DEU** Single outdoor magnetic lock with magnetic bond sensor, 1200lbs **532.00**

**1576DEU** Single face drilled outdoor magnetic lock with magnetic bond sensor, 1200lbs **532.00**

**1576DE-ZB** Inswing mounting bracket for 1576DEU **167.00**



101-DE with DEC-J

## MAGNETIC LOCK FINISH

Add to List

**V** 628 Clear Anodized Aluminum (Standard) **N/C**

**Y** Black Anodized Single **89.00**

### Powder Coat Finishes

(a coating electrostatically applied to form a hard finish, that is tougher than conventional paint)

**X** Dark Bronze Powder Coat Painted (313/613 Equal) Single **89.00**



101-1AK


## OPTIONAL MONITORING

Add to List

**B** Magnetic bond sensor, indicates locked with full holding force, low holding force, unlocked, tampering and obstructions. **(1581DE SPST only)** **67.00**

**D** Door position sensor, indicates door open and door closed. Commonly used to verify egress after alarm and exit delay activation. **45.00**

**(D) Door position sensor not available with 1581, 1575 and 1576**



DEC-J

## OPTIONAL HARDWARE

Add to List

**101-1AK** Outdoor reset with LED and Audible annunciator. 2-gang outdoor box required **355.00**  
(Interior 101-DE and 1575 or 1576 outdoor magnetic lock required)

**DEC-J** 3 Gang Interior surface mount box for 101-DE **100.00**

**SHD-J** Shroud for surface mount box DEC-J outdoor use **67.00**



SHD-J with 101-DE

SHD-J End View

**Mounting Kits & Angle Brackets - See page 10 - 11**



**918** Keyless Reset and Bypass or Momentary Authorized Access 500 User Codes **177.00**  
Keypad tamper lockout; Indoor blue backlit, moisture resistant keypad



**918** **920** Keyless Reset and Bypass or Momentary Authorized Access 500 User Codes **195.00**  
Heavy Cast Vandal Resistant Housing

920



**702R** Separate wall mount reset key switch assembly **122.00**  
MO SPDT dry contact, 6 Amp @ 30VDC max.  
Accepts standard 1-1/8" to 1-1/4" (*Mortise key cylinder not included*)



**702R** **707R** Remote reset key switch with dual function for Bypass (authorized egress) and reset **167.00**  
(2) MO SPDT dry contact, 6Amp @ 30VDC max  
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder. (*Mortise key cylinder not included*)

707R



**708R** Remote reset key switch for bypass (on/off) and reset **167.00**  
(1) Maintain (1) MO, SPDT dry contact, 6Amp @ 30VDC max  
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder. (*Mortise key cylinder not included*)

708R



**order with optional Mortise Cylinder**

- CYL-6KDQ** 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 49.00**
- CYL-6KAQ** 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 49.00**



**101-1A** Remote or local single door annunciator with audible alarm and tricolor LED, 1 Gang **117.00**  
Green - Secure      Amber - Egress initiated      Red - Door unlocked

101-1A



**101-4AM** Remote four door annunciator with audible alarm mute button. Four tricolor LEDs, 2 Gang **355.00**  
Green - Secure      Amber - Egress initiated      Red - Door unlocked

101-4AM



**101-1AK** Remote or local single door annunciator with 2 function key switch for on/off, reset, **355.00**  
audible alarm and tricolor LED, 2 Gang  
Green - Secure      Amber - Egress initiated      Red - Door unlocked  
Accepts standard 1-1/8" to 1-1/4" mortise key cylinder.  
(*Mortise key cylinder not included*)

101-1AK



**order with optional Mortise Cylinder**

- CYL-6KDQ** 6 pin, 1.125" Mortise Cylinder, Keyed Different **add 49.00**
- CYL-6KAQ** 6 pin, 1.125" Mortise Cylinder, Keyed Alike **add 49.00**



101-PAM

**101-PAM** Remote single door annunciator with 3 push button switches for momentary **375.00**  
access. On/off and audible alarm mute button with tricolor LED, 2 Gang  
Green - Secure      Amber - Egress initiated      Red - Door unlocked  
Recommended for remote installation only



101-SP

**101-SP** External 15 watt speaker connects directly to 1511S or 1511T for enhanced decibels **41.00**  
onsite or remote voice message annunciation. Speaker driver may be provided by others  
for extreme decibel requirements.



101-SPSN

**101-SPSN** Remote Single Gang Annunciator with speaker and 80db tone. Duplicates ExitCheck alternat- **107.00**  
ing voice message and tone. Compatible with 101-DE Controller Only.