

NOTE: PRODUCT CLOSEOUT - CONSULT FACTORY FOR AVAILABILITY

1600 Series Electric Strikes

DynaLock 1600 Series Electric Strikes are universally adaptable to suit all door and frame types and accommodate most locking devices with up to a 3/4" latch projection. To simplify ordering and speed installation all 1600 Series models feature 12/24V AC/DC field-selectable operation, dial-selectable fail-safe or fail-secure operating mode, 1/4" horizontal adjustment and modular, plug-in wire connections. All models are also available in a low-profile, 1-1/16" backset version, for narrow-style aluminum frames, which accept up to a 5/8" latch projection. Optional latch/keeper monitor switches are also available.

Current Draw: 375 mA @ 12VDC; 565 mA @ 12VAC
190 mA @ 24VDC; 280 mA @ 24VAC



1604



1607



1614



1608



1605

MODEL	PRODUCT	FINISH	WEIGHT
1604S	Aluminum/Wood Frames, Std. Profile, 1-1/4" x 4-7/8"	US32D	1.5 Lbs.
1604L	Aluminum/Wood Frames, Low Profile, 1-1/4" x 4-7/8"	US32D	1.5 Lbs.
1614S	Steel/Wood Frames, Std. Profile, 1-1/4" x 4-7/8"	US32D	1.5 Lbs.
1614L	Steel/Wood Frames, Low Profile, 1-1/4" x 4-7/8"	US32D	1.5 Lbs.
1605S	Aluminum/Wood Frames, Std. Profile, 1-1/8" x 5-7/8"	US32D	1.6 Lbs.
1605L	Aluminum/Wood Frames, Low Profile, 1-1/8" x 5-7/8"	US32D	1.6 Lbs.
1607S	Aluminum/Wood Frames, Std. Profile, 1-1/4" x 6-7/8"	US32D	1.8 Lbs.
1607L	Aluminum/Wood Frames, Low Profile, 1-1/4" x 6-7/8"	US32D	1.8 Lbs.
1608S	Aluminum/Wood Frames, Std. Profile, 1-7/16" x 7-15/16"	US32D	2 Lbs.
1608L	Aluminum/Wood Frames, Low Profile, 1-7/16" x 7-15/16"	US32D	2 Lbs.