

NOTE: PRODUCT CLOSEOUT - CONSULT FACTORY FOR AVAILABILITY

1900 Series All-in-One Electric Strikes



1921

Versatile DynaLock 1900 Series All-in-One fire-rated (UL 10C, 3 hour) and non-fire-rated Electric Strikes accommodate mortise and cylindrical locksets, as well as mortise exit devices, with offset, or centerline latch entry and up to a 3/4" latch projection. The adjustable deadbolt keeper and deadlatch ramp vertically align to accommodate a wide variety of mortise locks with offset latches. A unique, sliding shim design adjusts vertically on the keeper, to provide up-to 1/8" horizontal adjustment and a "plug-in" latch monitor switch option kit may be added in the field. Field-selectable input voltage 12/24 VDC or 12-24 VAC (1921). Both models fit a HES 1006 (1003) frame cutout (hollow-metal), with no additional modifications.

Current Draw: 375 mA @ 12VDC, Continuous (1921, 1923)
 190 mA @ 24VDC, Continuous (1921, 1923)
 280 - 565 mA @ 12-24VAC, Intermittent (1921 Only)

MODEL	PRODUCT	FINISH	WEIGHT
1921	Fire-Rated All-in-One Strike, Fail-Secure, 12/24 VAC/VDC	US32D	2.5 Lbs.
1923	Non Fire-Rated All-in-One Strike, Fail-Safe, 12/24 VDC	US32D	2.5 Lbs.

1900 SERIES OPTIONS

19-LM Latch Monitor Plug-In Kit, 1900 Series

FEATURES:



DIMENSIONS

ANSI 1-1/4" x 4-7/8" x 1-3/4"



1921 on cylindrical and mortise locks only