

2013 Series 1200 Lb. Gate Lock



2013

Electromagnetic lock, surface mounted for sliding or swinging gates. Face drilled mounting holes, weather resistant, sealed 1/2" conduit fitting with three foot long 22AWG leads.
 Field selectable 12/24 VDC
 Size: 1-1/2"D x 2-3/4"H x 9-1/4"L
 Current Draw: 374 mA @ 12VDC
 210 mA @ 24VDC



NYC MEA
 #23-92-E

MODEL	PRODUCT	FINISH	WEIGHT
2013	Electromagnetic Gate Lock - 12/24 VDC	US28	10 Lbs.

OPTIONS

- DYN** Dynastat Force Sensor - Indicates efficient magnetic bond.
- GLB** Gate Lock Bracket - Fully adjustable "Z" bracket for swinging gate applications.
- GLB2** Gate Lock Bracket - "L" Brackets for sliding gate application.
- RWE** Rear Wire Exit - Coil wiring exits from back of housing in lieu of conduit nipple.
- SF** Special Finish - Standard finish US28. Special anodized finishes see page 56.

Notes: For AC operation order #7088 Pre-wired Rectifier Bridge. See page 48.

2513 Series 650 Lb. Mini-Mag Gate Lock



2513

Compact gate lock, surface mounted for sliding or swinging gates. Face drilled mounting holes, weather resistant, sealed 1/2" conduit fitting with three foot long 22AWG leads.
 Field selectable 12/24 VDC
 Size: 1-1/4"D x 1-13/16"H x 8"L
 Current Draw: 381 mA @ 12VDC
 205 mA @ 24VDC



MODEL	PRODUCT	FINISH	WEIGHT
2513	Mini-Mag Gate Lock - 12/24 VDC	US28	4 Lbs.

OPTIONS

- DYN** Dynastat Force Sensor - Indicates efficient magnetic bond.
- GLBM** Mini-Mag Gate Lock Bracket - Fully adjustable "Z" bracket for gate applications.
- SF** Special Finish - Standard finish US28. Special anodized finishes see page 56.

Notes: For AC operation order #7088 Pre-wired Rectifier Bridge. See page 48.