

Valid Date: February 15, 2017

North America - Access Control - Price List



Table of Contents

Controllers - ExpansE Platform - Distributed Access Control System	Page 2
Controllers - AxTraxNG Platform - Networked Multi-Door Controllers	Page 3
Controllers - Network Controller Accessories	Page 7
Controllers - Wiegand Controllers	Page 8
Controllers - Stand Alone Controllers	Page 9
Readers - Biometric	Page 10
Readers - UHF	Page 12
Readers - 13.56 MHz - Open to Secure - O2S	Page 13
Readers - 13.56 MHz - MIFARE® Classic - CSN and Read Sector	Page 14
Readers - 125 KHz - Rosslare PROX and goPROX™	Page 15
Readers - PIN Only	Page 17
Readers - CSN Smart Card	Page 18
Readers - Modules	Page 19
Credentials - 125 KHz - EM Compatible	Page 20
Credentials - TEMIC Series & 13.56 MHz - MIFARE® Classic	Page 21
Switches - EX - Security Series	Page 22
Switches - PX - Industrial General Purpose	Page 24
Switches - EX & PX - Switch Accessories	Page 25
Locks - Electromagnetic Locks	Page 26
Locks - Electromagnetic Lock Accessories	Page 26
Power Supplies for Access Control	Page 27
Other Access Control Accessories	Page 28
Demo Kits	Page 29
Access Control Kits	Page 30
	_

Version: - Rev 2

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

Page 1 of 34





Valid Date: February 15, 2017

North America - Access Control - Price List

16 Relay Output Unit 16 Form-C relay outputs, ideal for elevator control applications, RS-485 communication port. 1,595.20 Dual Reader Door Unit 2 reader ports supports multiple Wilegand formats, standard and non standard formats, 4 four-state inputs, 4 form-C relay outputs and a sounder output, RS-485 communication port 8 Input/Output Unit 8 four-state inputs and 8 form-C relay outputs, RS-485 communication port 1,443.35 9 Boards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). 417.75 Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	Horm America - Access t		Tana.	Date. I ebi u	u. y . o, _o.
ExpansE Networked Controller Supports 32 doors /64 readers, up to 128 input and outputs per controller and up to 128,000 users per system, 100,000 history event log size, On-board Ethernet, RS-485 and USB 2.0 communication ports 16 Relay Output Unit 16 Form-C relay outputs, ideal for elevator control applications, RS-485 communication port. 1,595.20 1,595.20 1,595.20 1,595.20 1,595.20 1,595.20 1,595.20 1,595.20 2 reader ports — supports multiple Wiegand formats, standard and non standard formats, 4 four-state inputs, 4 form-C relay outputs and a sounder output, RS-485 communication port 1,697.50 1,443.35 1,443.35 1,443.35 2 Bards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one Mul and eight EUs one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE Dourse provided for one 7Ah, 12V lead acid battery (Battery sold separately).		Controllers	- ExpansE Platform - Distributed Access Control System		
Supports 32 doors / 64 readers, up to 128 input and outputs per controller and up to 128,000 users per system, 100,000 history event log size, On-board Ethernet, RS-485 and USB 2.0 communication ports 16 Relay Output Unit 16 Form-C relay outputs, ideal for elevator control applications, RS-485 communication port. 1,595.20 Dual Reader Door Unit 2 reader ports supports multiple Wiegand formats, standard and non standard formats, 4 four-state inputs, 4 form-C relay outputs and a sounder output, RS-485 communication port 8 input/Output Unit 8 four-state inputs and 8 form-C relay outputs, RS-485 communication port 1,443.35 9 Boards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead and battery (Battery sold separately). Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).		Photo	Description	MSRP	
P-2016 Dual Reader Door Unit 2 reader ports — supports multiple Wiegand formats, standard and non standard formats, 4 four-state inputs, 4 form-C relay outputs and a sounder output, RS-485 communication port B input/Output Unit 8 four-state inputs and 8 form-C relay outputs, RS-485 communication port 1,443.35 B Boards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). Single Board Self Powered Metal Enclosure Metal enclosure with lock, filts any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	EXP-1032		Supports 32 doors / 64 readers, up to 128 input and outputs per controller and up to 128,000 users	2,658.65	
2 reader ports supports multiple Wiegand formats, standard and non standard formats, 4 four-state inputs, 4 form-C relay outputs and a sounder output, RS-485 communication port 8 Input/Output Unit 8 four-state inputs and 8 form-C relay outputs, RS-485 communication port 1,443.35 9 Boards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to bards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	EXP-2016		,	1,595.20	
8 four-state inputs and 8 form-C relay outputs, RS-485 communication port 1,443.35 9 Boards Tray Cabinet Housing Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). 417.75 Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	EXP-2024		2 reader ports supports multiple Wiegand formats, standard and non standard formats, 4 four-state inputs, 4	569.75	
Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16 doors. Space provided for one 14Ah, 12V lead acid battery (Battery sold separately). Single Board Self Powered Metal Enclosure Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	EXP-2088	marie Ja.	· · ·	1,443.35	
Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).	ME-00		Metal enclosure with lock, holds up to 9 standard ExpansE boards providing an easy way to set up large systems using the built in interconnect backbone. With one MU and eight EU's one Enclosure can supports up to 16	417.75	
E-01-P14U ME-01-P14, supplied without transformer 151.85	ME-01-P14		Metal enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead		
	ME-01-P14U		ME-01-P14, supplied without transformer	151.85	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

North America - Access C	orth America - Access Control - Price List Valid Date		Date: Febru	ary 15, 2017
	Controlle	ers - ExpansE Platform - Distributed Access Control System		
Part Number	Photo	Description	MSRP	
ME-12-P14		Single Board Self Powered Plastic Enclosure Plastic enclosure with lock, fits any ExpansE End Unit, Main Unit or the AC-215. A built in power supply is provided to provide power to the boards and the battery charging circuit up to 2A. Space provided for one 7Ah, 12V lead acid battery (Battery sold separately).		
ME-12-P14U		ME-12-P14, supplied without transformer	132.90	
ME-14	and the same	Compact Single Board Plastic Enclosure Compact plastic enclosure fits any ExpansE End Unit or Main Unit. Power to be provided by external power supply (Power supply sold separately). Wall and cover tamper switch is provided.	39.90	

Controllers - AxTraxNG Platform - Networked Multi-Door Controllers

Part Number	Photo	Description	MSRP	
AC-215		Advanced Scalable Access Controller One or Two-Door (2-Reader IN/OUT, IN/IN) topology, networked up to 256 panels to one PC. Full online/offline operation. 5000 Users, 20,000 Non-Access Users, 5,000 event history. Access Groups, Holidays, Time-zones and more. Space for 7Ah, 12V lead acid battery (Battery sold separately).		
AC-215-U		AC-215, FCC approved and UL-294 listed, supplied without transformer	571.20	
AC-215-PCBA		AC-215, PCBA only	447.05	
AC-215IP		Advanced Scalable Networked Access Controller One or Two-Door (2-Reader IN/OUT, IN/IN) topology, networked up to 1023 panels to one PC. Full online/offline operation. 30,000 users, 20,000 event history. Advanced event-action logic engine. Space for 7Ah, 12V lead acid battery (Battery sold separately).		
AC-215IP-U		AC-215IP, supplied without transformer	639.60	
AC-215IP-PCBA		AC-215IP, PCBA only	515.85	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

North America - Access Co	ontrol - Price List	Valid	Date: Februa	ary 15, 201
	Controllers -	- AxTraxNG Platform - Networked Multi-Door Controllers		
Part Number	Photo	Description	MSRP	
AC-225		Professional Scalable IP Networked Access Controller One or Two-Door (2-Reader IN/OUT, IN/IN) topology, networked up to 1023 panels to one PC. Full online/offline operation. 30,000 Users, 20,000 event history. Compatible with MD-I084 8 Input / 4 Output Expander and MD-D02 Two Door Expander. Advanced event-action logic engine. Tamper protected, lockable metal enclosure, power supply/charger and Bell/Alarm/Chime sounder. System management performed on the AXTrax PC software platform with client/server operator access. Space for 7Ah, 12V lead acid battery (Battery sold separately).		
AC-225-U		AC-225, no on-board IP, FCC approved and UL-294 listed, supplied without transformer	828.50	
AC-225-PCBA		AC-225, no on-board IP, PCBA only	648.60	
AC-225IP-U		AC-225IP with on-board IP, FCC approved and UL-294 listed, supplied without transformer	927.75	
AC-225IP-PCBA		AC-225IP with on-board IP, PCBA only	747.85	
AC-425		Professional Scalable IP Networked Access Controller Two or Four-Door (4-Reader IN/OUT, IN/IN) topology, networked up to 1023 panels to one PC. Full online/offline operation. 30,000 Users, 20,000 event history. Compatible with MD-I084 8 Input / 4 Output Expander and MD-D04 Four Door Expander. Advanced event-action logic engine. Tamper protected, lockable metal enclosure, power supply/charger and Bell/Alarm/Chime sounder. System management performed on the AXTrax PC software platform with client/server operator access. Space for 7Ah, 12V lead acid battery (Battery sold separately).		
AC-425-U		AC-425, no on-board IP, supplied without transformer	1,201,30	
AC-425-PCBA		AC-425, no on-board IP, PCBA only	940.40	
AC-425IP-U		AC-425IP with on-board IP, supplied without transformer	1,345.25	
AC-425IP-PCBA		AC-425IP with on-board IP, PCBA only	1,084.35	
MD-D02	CC T	2 Door Expander 2-door expander for Professional Scalable Controllers (AC-225, AC-225IP, AC-525). 2 Multi-format reader ports 4 Supervised Inputs each are 4-state/dual EOL inputs 4 form-C 5A relay outputs	256.05	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 4 of 34



Valid Date: February 15, 2017

North America - Access Control - Price List

	Controlle	ers - AxTraxNG Platform - Networked Multi-Door Controllers		
Part Number	Photo	Description	MSRP	
MD-D04	7 Table 1 Tabl	4 Door Expander 4-door expander for Professional Scalable Controllers (AC-425, AC-425IP). 4 Multi-format reader ports 4 Supervised Inputs each are 4-state/dual EOL inputs 4 form-C 5A relay outputs	371.30	
MD-IO84	C C C C C C C C C C C C C C C C C C C	8 Input / 4 Output IO Expander IO expander for Professional Scalable Controllers (AC-225, AC-225IP, AC-425, AC-425IP, AC-525). 8 Supervised Inputs each are 4-state/dual EOL inputs 4 form-C 5A relay outputs	269.15	
AC-825		Professional Scalable IP Networked Access Control Unit The AC-825IP is a state-of-the-art 4-door networked access controller, comes with one onboard expansion slot and can be further expanded by connecting up to 16 expansion boards via OSDP (the AC-825IP could control upto 72 doors). Each AC-825IP access control unit (ACU) supports 300K users, 500K event log entries (FIFO), 4 doors (readers), each with 2 inputs and 1 output, four auxiliary inputs and two auxiliary outputs on board. The AC-825IP includes AES128-bit encrypted communication via TCP/IP, and provides battery charger for 7Ah, 12V lead acid battery. (Battery sold separately) (Image showing the AC-825IP)		
AC-825IP		AC-825IP PCBA installed within ME-1525 enclosure	1.443.35	
AC-825IP-PCBA		AC-825IP PCBA Only	1,090.10	
R-805		R-805 - Relay Output Expansion Board (16 x 5A Form C Relays Outputs)	455.75	
5-805		S-805 - Supervised Input Expansion Board (16 x Supervised Analog Inputs)	455.75	
D-805		D-805 - Door Expansion Board (4 x Wiegand Readers, 4 x 5A Form C Relay Outputs, 8 x Supervised Analog	493.80	
P-805		P-805 - PLC I/O Expansion Board (16 x Supervised Analog Inputs, 8 x 5A Form C Relay Outputs)	569.75	
ME-1505		ME-1505 Enclosure - Fits two Expansion Boards (same internal features as ME-1525 enclosure)	303.85	
AX-NG		AxTraxNG™ - PC Client/Server Management Software for Professional Networked Controllers User-friendly scalable management software for real-time monitoring, configuration and reporting for up to 1023 panels / 4092 doors. SQL database for intensive operation. Advanced event-response logic. Supports AC-215, AC-215IP, AC-225, AC-225IP, AC-425, AC-425IP and AC-525 controllers with their optional expansions and mixed installations. Supports PSTN modem, Serial RS485 and TCP/IP configurations for panels. HASP key required for 65+ panels.		
AX-NG-L0		Level 0 = 1 to 64 panels	FREE	
AX-NG-LU AX-NG-L1		Level 1 = 65 to 256 panels	671.20	
AX-NG-L1 AX-NG-L2		Level 2 = 257 to 512 panels	2.013.65	
AX-NG-L2 AX-NG-L3		Level 3 = Over 512 panels	3,356.10	
IV-IAG-F9	ĺ	Level 3 - Over 312 pariels	3,330.10	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Controllers - AxTraxNG Platform - Networked Multi-Door Controllers			
Part Number	Photo	Description	MSRP
AX-AV	COSMACCH 	ViTrax™ - PC DVR Surveillance Client/Server Suite Management Licenses Advanced digital video recording and remote surveillance Client/Server suite for Microsoft® Windows. It supports our AC-525 panels as well as major Network (IP) Cameras, Frame Grabbers and Directshow compatible devices such as USB cameras. The suite has Clients and Servers capable of viewing multiple local and remote sources, recording video for local or remote playback, enabling exporting recordings to preserve evidence. Can be integrated with Rosslare's AxTrax™ Networked Access Control Software.	
AX-AV-L0		Level 0: 1 camera, 1 local client	FREE
AX-AV-L1		Level 1: 2 cameras, 1 remote client	198.90
AX-AV-L2		Level 2: 4 cameras, 1 remote client	372.00
AX-AV-L3		Level 3: 9 cameras, 3 remote clients	797.10
AX-AV-L4		Level 4: 16 cameras, 4 remote clients	1,328.45
AX-AV-L5		Level 5: unlimited cameras, unlimited remote clients	2,550.65
AX-AVLPR	NEMACON Land Michael Maria Land Michael Mari	Requires ViTrax VMS software license	
AX-AVLPR-L1		Level 1: 2 LPR channels	2,237.00
AX-AVLPR-L2		Level 2: Unlimited LPR channels	3,819.00
АХ-НІК		AxTraxNG™ with Hikvision Video Integration License IP Camera / DVR / PC-NVR support - requires AxTraxNG version 23.04 and higher	
AX-HIK-L1		Level 1: 2 cameras/channels, 1 DVR	198.90
AX-HIK-L2		Level 2: 4 cameras/channels, 2 DVR's	372.00
AX-HIK-L3		Level 3: 9 cameras/channels, 4 DVR's	797.10
AX-HIK-L4		Level 4: 16 cameras/channels, 8 DVR's	1,328.45
AX-HIK-L5		Level 5: Unlimited cameras/channels, 12 DVR's	2.550.65

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Controllers - AxTraxNG Platform - Networked Multi-Door Controllers				
Part Number	Photo	Description	MSRP	
AX-DAH		AxTraxNG™ with Dahua Video Integration License IP Camera / DVR / NVR support - requires AxTraxNG version 24.03 and higher		
AX-DAH-L1		Level 1: 2 cameras/channels, 1 DVR	198.90	
AX-DAH-L2		Level 2: 4 cameras/channels, 2 DVR's	372.00	
AX-DAH-L3		Level 3: 9 cameras/channels, 4 DVR's	797.10	
AX-DAH-L4		Level 4: 16 cameras/channels, 8 DVR's	1,328.45	
AX-DAH-L5		Level 5: Unlimited cameras/channels, 12 DVR's	2,550.65	
АХ-ТМ		AxTime™ Time & Attendance PC software application for AxTrax™ A multiple client software which interacts with the main AxTrax™ server database. Allows advanced Time & Attendance operations such as payroll and specialized reports for multi-shift, multi-activity, and multiple employee payments. The client requires a HASP key to connect to the AxTrax™ server database.	402.30	

Controllers - Network Controller Accessories

Part Number	Photo	Description	MSRP	
MD-W11		Wireless Access Control Door Interface The MD-W11 utilizes bi-directional RF data communication and rolling code protocol to relay Wiegand 26-bit and other formats including PIN code messages, lock, door relay, tamper, door monitor and REX signals between the near and far interface units. (Power supply sold separately).		
MD-W11GR		MD-W11 in GR band – 433 MHz	695.30	
MD-W11BP		Power backup unit for far interface unit, includes BT-05 12 V, 800 mAh Lead Acid Battery	62.25	
AY-F66	30.0540	Outdoor Proximity & PIN Reader with Time/Date LED Display Multi data format output (Wiegand 26-Bit, Clock & Data). Built-in 125 KHz proximity reader, read range of up to 10 cm (4"). Time/Date LED display, RS-485 clock sync input when used with AxTrax and ExpansE platform controllers. Internal buzzer, 3x4 matrix backlit keypad for PIN entry and programming. Optical back tamper. Meets IP54.	239.35	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

	Controllers - Network Controller Accessories			
Part Number	Photo	Description	MSRP	
PS-14	ERETRE ELEC	2A PCB Power Supply Module for AC-215, AC-215IP, ME-01-P14, ME-12-P14 Power supply module for networked controllers	45.20	
PS-33	**************************************	5A PCB Power Supply Module for AC-225, AC-225IP Power supply module for networked controllers	141.00	

Controllers - Wiegand Controllers

Part Number	Photo	Description	MSRP	
AC-115	090 090 700 700	Compact Networked Single Door Controller Connects to two Wiegand 26-bit readers (IN/OUT), 2400 users (Proximity or PIN), 3 security modes, event history of up to 2000 events. Networked up to 8 controllers over RS-485 bus. Built-in sounder for bell, alarm and chime. Integrated power supply/backup battery charger, door monitor and REX inputs, 5A form C lock strike relay and 1A auxiliary relay output. Two bi-color LEDs and 3x4 matrix keypad that can also be used for local programming menu and case is tamper protected. Optional RS-485 connection for PC monitoring using MD-14U (sold separately).	335.60	
AC-020	000 000 700 000	Dual Door, 2-Reader Standalone Controller Connects to two Wiegand 26-Bit readers (2 x IN), 500 users (Proximity or PIN), 3 security modes. Built-in sounder for bell, alarm, and chime, built-in power supply/backup battery charger. Two form C 5A lock strike relays, 2 REX inputs, 2 door monitor inputs. Two bi-color LEDs and 3x4 matrix keypad that can also be used for local programming menu and case is tamper protected.	131.75	
AC-015	000 000 700 500	Single Door, 2-Reader Standalone Controller Connects to two Wiegand 26-bit readers (IN/OUT), 500 users (Proximity or PIN), 3 security modes. Built-in sounder for bell, alarm and chime, built-in power supply/backup battery charger. One form C 5A lock strike relay and 1A auxiliary relay outputs, REX input and door monitor input. Two bi-color LEDs and 3x4 matrix keypad that can also be used for local programming menu and case is tamper protected. RS-232 connection for PC monitoring (cable included), configuration and reporting with AS-015 multi-lingual PC software (CD-ROM included).	112.75	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Controllers - Stand Alone Controllers			
Part Number	Photo	Description	MSRP
AC-QXX Series	123 456 789 ***********************************	Anti-Vandal Standalone Controller 500 dual-code users, two 2A from C relay outputs, two inputs, two bi-color LED indicators, metal 3x4 keypad also used for local programming. 3 user levels and 3 security modes, operation voltage range of 12-24 VAC or 12-24 VDC, optical tamper. Door Bell key function (**' key for BL-D40 sounder). (Image showing the AC-Q42SB)	
AC-Q41H		Keypad Only - Terminal Block Wiring - IP54 - keypad heater	212.45
AC-Q41HB		Keypad Only - Terminal Block Wiring - IP54 - backlit keypad with heater	250.05
AC-Q41HP		Keypad Only - Slim Profile - Terminal Block Wiring - IP65 - backlit keypad with heater	250.05
AC-Q41SB		Keypad Only - Slim Profile - Pigtail Wiring - IP65 - backlit keypad	250.05
AC-Q42H		PROX and Keypad - Terminal Block Wiring - IP54 - keypad heater	308.40
AC-Q42HB		PROX and Keypad - Terminal Block Wiring - IP54 - backlit keypad with heater	345.90
AC-Q42HP		PROX and Keypad - Slim Profile - Terminal Block Wiring - IP65 - backlit keypad with heater	345.90
AC-Q42SB		PROX and Keypad - Slim Profile - Pigtail Wiring - IP65 - backlit keypad	345.90
AC-Q44		PROX and Piezo Keypad - Slim Profile - Pigtail Wiring - IP65	280.25
AC-S43 Series AC-T43 Series	12 24 80 78 90 FB	Anti-Vandal Piezo Standalone Controller 500 dual-code users, two 2A form C relay outputs, two inputs, two bi-color LED indicators, metal piezo keypad also used for local programming. 3 user levels and 3 security modes, operation voltage range of 12-24 VAC or 12- 24 VDC, optical tamper. Door Bell key function ('*' key for BL-D40 Sounder). Fully potted, meets IP68. (Image showing the AC-S43)	
AC-S43		Mullion - Keypad Only - 2x6 Matrix Piezo Keypad	225.55
AC-T43		US Gang Box - Keypad Only - 3x4 Matrix Piezo Keypad	236.50
AC-G4X Series AC-F4X Series	N 2 3 N 5 6 N 7 8 8 N 0 34	Outdoor Backlit Standalone Controller 500 dual-code users, two 2A form C relay outputs, two inputs, two bi-color LED indicators, backlit silicon keypad also used for local programming. 3 user levels and 3 security modes, operation voltage range of 12-24 VAC or 12- 24 VDC, optical tamper. Door Bell key function (**' key for BL-D40 Sounder). Fully potted, meets IP65. (Image showing the AC-F44)	
AC-G43		Mullion - Keypad Only - 2x6 Matrix Keypad	148.05
AC-G44		Mullion - PROX and Keypad - 2x6 Matrix Keypad	223.05
AC-F43		US Gang Box - Keypad Only - 3x4 Matrix Keypad	155.95
AC-F44		US Gang Box - PROX and Keypad - 3x4 Matrix Keypad	232.90

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

North America - Access	Control - Price List	Valid	Date: Februa	ary 15, 2017
		Controllers - Stand Alone Controllers		
Part Number	Photo	Description	MSRP	
AC-X31/32 Series AC-A41/42 Series		Indoor Standalone Controller 500 dual-code users, 3.5A lock strike relay, 1 REX input. 2 Tri-colored LED Indicators. 3 user levels and 3 security modes, operation voltage range of 12-16VDC, case tamper, terminal block interface. (Image showing the AC-B32)		
AC-B31		UK Gang Box - Keypad Only - 1 Output	58.85	
AC-B32		UK Gang Box - PROX and Keypad - 1 Output	74.00	
AC-C31		Mullion - Keypad Only - 1 Output	73.55	
AC-C32		Mullion - PROX and Keypad - 1 Output	156.60	
AC-D31		US Gang Box - Keypad Only - 1 Output	73.55	
AC-D32		US Gang Box - PROX and Keypad - 1 Output	156.60	
AC-A41		US Gang Box - Keypad Only - 2 Output	84.65	
AC-A42		US Gang Box - PROX and Keypad - 2 Outputs	167.80	

Readers - Biometric

Part Number	Photo	Description	MSRP	
AY-Bx663 Series		Fingerprint Swipe Match-on-Card Reader Match On Card Biometric reader with swipe-type fingerprint sensor, built-in ISO-14443A MIFARE® contactless sector reader. The fingerprint reading is matched with the secured data stored on a card. Two fingerprint templates can be stored on a 1K card. No user enrollment required to the readers. Selectable output formats including standard Wiegand 26 bits. Requires CP-R25 Card Programmer / FP Swipe Enrollment Station (sold separately). (Image showing the AY-B1663)		
AY-B1663		Swipe MOC Reader - Design 1	380.35	
AY-B3663		Swipe MOC Reader - Design 3	380.35	
AY-B4663		Swipe MOC Reader - Design 4	380.35	
CP-R25		Card Programmer / FP Swipe Enrollment Station	685.35	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

Page 10 of 34

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

		Readers - Biometric		
Part Number	Photo	Description	MSRP	
AY-Bx660 Series		Full Fingerprint Match-on-Card Reader Match On Card Biometric reader with full fingerprint sensor, built-in ISO-14443A MIFARE® contactless sector reader. The fingerprint reading is matched with the secured data stored on a card. One fingerprint templates can be stored on a 1K card while two templates can be stored on a 4K card. No user enrollment required to the readers. Selectable output formats including standard Wiegand 26 bit. Requires CP-R26 Card Programmer / Full FP Enrollment Station (sold separately). (Image showing the AY-B1660)		
AY-B1660		Full FP MOC - Design 1	445.20	
AY-B2660		Full FP MOC - Design 2	457.10	
CP-R26		Card Programmer / Full FP Enrollment Station	757.55	
AYC-B7661		Full Fingerprint 1:1 / 1:N Convertible Reader 1:1 / 1:N Fingerprint only biometric convertible reader with full fingerprint sensor, built-in ISO-14443A MIFARE® contactless sector reader used for setup only. The fingerprint only reader stores 107 user fingerprint templates and their unique ID, selectable output formats including standard Wiegand 26 bit. Automatically converts into a 107 user controller when operated with Rosslare's intelligent secure power supplies. (PS-x25T series sold separately). Requires CP-R26 Card Programmer / Full FP Enrollment Station (sold separately).	457.10	
AS-B01		Management SW for Biometric readers Master card programming, users card settings and enrollment of biometric data and storing in Mifare smartcards. Compatible with CP-R25 & CP-R26 Card Programmer / FP Enrollment Stations	FREE	
AYC-W6500	Control of the Contro	Fingerprint, PIN & Prox Convertible Reader Built-in backlit keypad and proximity reader. Supports Wiegand 26-bits and standard transmission formats. Stores up to 500 dual fingerprint templates. Built-in 125KHz proximity reader. Automatically converts into a 500 user controller when operated with Rosslare's intelligent secure power supplies. (PS-x25T series sold separately). Includes BioTraxTM configuration and online control software and an interface cable.	1,020.50	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

North America - Access C	ontrol - Price List	Valid	Date: February 1	5, 201
		Readers - UHF		
Part Number	Photo	Description	MSRP	
AY-L23 Advanced Series UHF 433.92 MHz UHF 868.35 MHz		Advanced Extra Long-Range RF Receiver The Advanced Extra Long-Range RF Receiver has an open air read range of 70 m (230 ft), it has single authentication with Rosslare RF, and has two Wiegand format outputs and two open collector outputs (200 mA). The receiver will output the Wiegand format and/or activate the open collector output as per the programmed setting on a 2-button SA-23-B2, or 4-button SA-23-B4 series remote control transmitter. The operating voltage is 7–24 VDC and it is Mullion mounted.		
AY-L23G		Advanced Extra Long-Range RF Receiver in 433.92 MHz	203.05	
SA-23-B2G		2-Channel Advanced Transmitter in 433.92 MHz	36.05	
SA-23-B4G		4-Channel Advanced Transmitter in 433.92 MHz	44.40	
AY-U910 Series UHF 900 MHz	goods.	UHF Integrated Long-Range Reader Series The UHF Integrated Long-Range Reader has an adjustable read range from 1 to 12 meters (3.28 to 40 ft). It has single authentication with Rosslare RF complying with ISO18000-6B and ISO18000-6C (EPC GEN2) and by default outputs Wiegand 26-Bit. The operating voltage is 9–12 VDC and has a standby current of 200 mA and the peak current is 1.2 A. The dimensions are 44 x 44 x 5 cm (17.52 x 17.52 x 2.54*). It is rated IP54.		
AY-U910US		UHF Integrated Long-Range Reader – Frequency: 902–928 MHz	1,181.20	
		AY-U900 Credentials - UHF - Alien Higgs-3		
Part Number	hoto	Description	MSRP	
LT-UVH-26A-7000		Hard Tag - Programmed - 26-Bit (26A - Format) - Price is for Pack of 25	89.50	
LT-UVS-26A-3000		ISO Card (PVC) - Programmed - 26-Bit (26A Format) - Price is for Pack of 25	53.90	

Tamper Proof Label - Programmed - 26-Bit (26A Format) - Price is for Pack of 100

Dual Technology Alien Higgs-3 with MIFARE® Classic 4K - ISO Card (PVC) - Price is for Pack of 25

Tamper Proof Label - Not Programmed - Price is for Pack of 100

www.rosslaresecurity.com

LT-UVT-26A-3000

AT-UVT-000-0000

AT-Z4S-000-0000

A Division of Rosslare Enterprises Ltd.

205.10

151.60

138.80

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

Hard Tag

3. Prices are subject to change without prior notice.

Page 12 of 34



North America - Access Con	ntrol - Price List	Valid [Date: February
		Readers - 13.56 MHz - Open to Secure - O2S	
Part Number	Photo	Description	MSRP
V-H Series Open to Secure	Grand Control of the	Open to Secure™ – MIFARE® DESFire EV1 & PLUS X/S Smart Card Sector Reader Series Rosslare's new Open to Secure™ (O2S) readers are pre-programmed at the factory with Rosslare encryption keys. Secure 128-Bit AES Encryption right out of the box, a true Plug and Play solution. Multi-format output supporting all common Wiegand output formats or Clock & Data output. Select models include OSDP (RS-485) communications. Available in Pigtail or Terminal Block versions. Keypad versions utilize tactile switches and blue backlighting. Large multi-color RGB indicator window. (Image showing the AY-H6380)	
Y-H6270B+P00		O2S – MIFARE® PLUS X/S Smart Card Reader with 18" (46-cm) Pigtail	188.05
Y-H6270B+TR0		O2S – MIFARE® PLUS X/S Smart Card Reader with Terminal Blocks and OSDP Support	188.05
Y-H6370B+P00		O2S – MIFARE® PLUS X/S Smart Card Reader & 3x4 Matrix Keypad with 18" (46-cm) Pigtail	279.10
Y-H6370B+TR0		O2S - MIFARE® PLUS X/S Smart Card Reader & 3x4 Matrix Keypad with Terminal Blocks & OSDP Support	279.10
Y-H6280B+P00		O2S – MIFARE® DESFire EV1 Smart Card Reader with 18" (46-cm) Pigtail	267.80
Y-H6280B+TR0		O2S – MIFARE® DESFire EV1 Smart Card Reader with Terminal Blocks and OSDP Support	267.80
Y-H6380B+P00		O2S – MIFARE® DESFire EV1 Smart Card Reader & 3x4 Matrix Keypad with 18" (46-cm) Pigtail	358.90
Y-H6380B+TR0		O2S - MIFARE® DESFire EV1 Smartcard Reader & 3x4 Matrix Keypad with Terminal Blocks & OSDP Support	358.90
AY-G Series Open to Secure	Canara	Open to Secure™ – MIFARE® DESFire EV1 & PLUS X/S Smart Card Mullion Sector Reader Series Rosslare's new Open to Secure™ (O2S) readers are pre-programmed at the factory with Rosslare encryption keys. Secure 128-Bit AES Encryption right out of the box, a true Plug and Play solution. Multi-format output supporting all common Wiegand output formats or Clock & Data output. Select models include OSDP (RS-485) communications. Available in Pigtail or Terminal Block versions. Keypad versions utilize tactile switches and blue backlighting. Image showing the AY-G6380)	
Y-G6270B+P00		O2S – MIFARE® PLUS X/S Smart Card Reader with 18" (46-cm) Pigtail	188.05
Y-G6270B+TR0		O2S – MIFARE® PLUS X/S Smart Card Reader with Terminal Blocks and OSDP Support	188.05
Y-G6370B+P00		O2S – MIFARE® PLUS X/S Smart Card Reader & 3x4 Matrix Keypad with 18" (46-cm) Pigtail	279.10
Y-G6370B+TR0		O2S – MIFARE® PLUS X/S Smart Card Reader & 3x4 Matrix Keypad with Terminal Blocks & OSDP Support	279.10
Y-G6280B+P00		O2S – MIFARE® DESFire EV1 Smart Card Reader with 18" (46-cm) Pigtail	267.80
Y-G6280B+TR0		O2S – MIFARE® DESFire EV1 Smart Card Reader with Terminal Blocks and OSDP Support	267.80
Y-G6380B+P00		O2S – MIFARE® DESFire EV1 Smart Card Reader & 3x4 Matrix Keypad with 18" (46-cm) Pigtail	358.90

O2S - MIFARE® DESFire EV1 Smartcard Reader & 3x4 Matrix Keypad with Terminal Blocks & OSDP Support

www.rosslaresecurity.com

AY-G6380B+TR0

A Division of Rosslare Enterprises Ltd.

358.90

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

North America - Access to	20	T WITH D	ate. Tebruary 13, 2
	Reader	rs - 13.56 MHz - MIFARE® Classic - CSN and Read Sector	
Part Number	Photo	Description	MSRP
AY-x25 Series AY-x26 Series	•	AY-x25/26 MIFARE® Smart Card Contactless Reader Series 13.56 MHz, ISO-14443A MIFARE® Reader Series. Bi-color LED with read indication and control input, internal buzzer. Waterproof, meets IP65, 18" (46-cm) pigtail cable. For CSN readers, output formats are selectable using the MD-08B programming adapter (sold separately). Read Sector readers are programmed using the CP-R25 or CP-R26. (Image showing the AY-K25)	
AY-K25B		Micro-Mullion MIFARE® CSN Reader	103.75
AY-J25B		Mini-Mullion MIFARE® CSN Reader	108.05
AY-L25B		Mullion MIFARE® CSN Reader	112.45
AY-H25B		US Single Gang MIFARE® CSN Reader	114.60
AY-M25B		UK Gang MIFARE® CSN Reader	114.60
AY-M26		UK Gang MIFARE® Classic Sector Reader	150.05
AY-W6xxx Series		AY-W6xxx MIFARE® Smart Card Contactless US Gang Box Reader Series 13.56 MHz, ISO-14443A MIFARE® Reader Series. Bi-color LED with read indication and control input, internal buzzer. Waterproof, meets IP65, 18" (46-cm) pigtail cable. For CSN Readers, output formats are selectable using MD-08B programming adapter (sold separately). Read Sector readers are programmed using the CP-R25 or CP-R26. (Image showing the AY-W6260)	
AY-W6250		US Gang Box MIFARE® CSN Reader	115.25
AY-W6350		US Gang Box MIFARE® CSN Reader with 3x4 Matrix Backlit Keypad	184.40
AY-W6260		US Gang Box MIFARE® Classic Read Sector Reader	155.85
AY-W6360		US Gang Box MIFARE® Classic Read Sector Reader with 3x4 Matrix Backlit Keypad	249.40
AY-Qxxx Series		AY-Q6xxx Anti-Vandal MIFARE® Smart Card Contactless US Gang Box Reader Series 13.56 MHz, ISO-14443A MIFARE® Reader Series. Bi-color LED with read indication and control input, internal buzzer. waterproof, meets IP65. 18" (46-cm) pigtail cable. For CSN Readers, output formats are selectable using MD-08B programming adapter (sold separately). Read Sector readers is programmed using the CP-R25 or CP-R26. (Image showing the AY-Q6260)	
AY-Q6250		Anti-Vandal US Gang Box MIFARE® CSN Reader	246.80
AY-Q6350		Anti-Vandal US Gang Box MIFARE® CSN Reader with 3x4 Matrix Backlit Keypad	347.45
AY-Q6260		Anti-Vandal US Gang Box MIFARE® Classic Sector Reader	333.80
AY-Q6360		Anti-Vandal US Gang Box MIFARE® Classic Sector Reader with 3x4 Matrix Backlit Keypad	469.85

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Readers - 125 KHz - Rosslare PROX and goPROX™ Part **MSRP** Photo Description Number AY-x12/20 Rosslare Proximity Reader Series 125 KHz, EM Compatible Rosslare Proximity Reader Series. The x12 Series readers only support Wiegand 26-Bit while the x20 Series readers support multiple Wiegand formats, Clock & Data, and RS-232 output formats. All AY-x12 Series readers include green LED control and tamper output while the x20 Series readers have an additional red LED AY-x20 Series control, buzzer control, hold line, and output selection lines. The operating voltage is 5-16 VDC. (Image showing the AY-K12) AY-KR12B Micro-Mullion Rosslare Proximity Reader - UL294 Approved 90.30 AY-K20B Micro-Mullion Rosslare Proximity Reader - 10-Wire Version 101.60 Mini-Mullion Rosslare Proximity Reader - UL294 Approved AY-JR12B 94.00 Mini-Mullion Rosslare Proximity Reader - 10-Wire Version AY-J20B 105.30 Mullion Rosslare Proximity Reader - UL294 Approved 97.75 AY-LR12B AY-L20B Mullion Rosslare Proximity Reader - 10-Wire Version 109.05 US Single Gang Rosslare Proximity Reader - UL294 Approved AY-HR12B 99.65 AY-H20B US Single Gang Rosslare Proximity Reader – 10-Wire Version 110.95 UK Gang Rosslare Proximity Reader - UL294 Approved AY-MR12B 99.65 AY-M20B UK Gang Rosslare Proximity Reader - 10-Wire Version 110.95 AYC-G6x / F6x / M6x Convertible Rosslare Proximity and goPROX with PIN Reader Series 125 KHz, EM Compatible Rosslare Proximity and goPROX with PIN Reader Series. The 64 Series is EM compatible, while the 60 Series is a part of Rosslare's goPROX series supporting both Rosslare Proximity and AYC-G6x Series Genuine HID Technology™ Proximity. The readers output is Wiegand and Clock & Data. The operating voltage is AYC-F6x Series 5-16 VDC. It is rated IP65. Converts to a 500-user secured standalone controller when used with a PS-C25T Series power supply. (Image showing the AYC-M60) Mullion Rosslare Proximity Reader with 2x6 Matrix Backlit Keypad - Convertible - UL294 Approved AYC-G64 209.30 AYC-G60 Mullion Rosslare goPROX Reader with 2x6 Matrix Backlit Keypad - Convertible - UL294 Approved 209.30

US Gang Box Rosslare Proximity Reader with 3x4 Matrix Backlit Keypad - Convertible - UL294 Approved

US Gang Box Rosslare goPROX Reader with 3x4 Matrix Backlit Keypad - Convertible - UL294 Approved

UK Gang Box Rosslare goPROX Reader with 3x4 Matrix Backlit Keypad - Convertible - UL294 Approved

www.rosslaresecurity.com

AYC-F64

AYC-F60

AYC-M60

A Division of Rosslare Enterprises Ltd.

219.10

219.10

210.40

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

	Read	ders - 125 KHz - Rosslare PROX and goPROX™	
Part	Photo	Description	

Part				
Number	Photo	Description	MSRP	
AY-E20 AYC-E6x Series AYC-T6x Series		AY-E20 / AYC-E6x / T6x Ultra-Slim Backlit Piezo Proximity & goPROX Series 125 KHz EM Compatible Ultra-Slim (9 mm) Reader Series. The 20 and 65 Series are EM compatible, while the 60 Series is a part of Rosslare's goPROX product series supporting both Rosslare Proximity and Genuine HID Technology™ Prox. The reader output is Wiegand and Clock & Data. Keypad units are Backlit. The operating voltage is 5–16 VDC. It is rated IP68. The 65 and 60 Series convert to a 500-user secured standalone controller when used with a PS-C25T Series power supply. (Image showing the AYC-E65B)		
AY-E20		Mullion Rosslare Proximity Reader – Natural Housing with Dark Grey Antenna	223.75	
AYC-E65BW		Mullion Rosslare Proximity Reader with 2x6 Matrix Keypad – Convertible – Natural w/ White Antenna - UL294	302.05	
AYC-E65BG		Mullion Rosslare Proximity Reader with 2x6 Matrix Keypad – Convertible – Natural w/ Grey Antenna - UL294	302.05	
AYC-E65BB		Mullion Rosslare Proximity Reader with 2x6 Matrix Keypad – Convertible – Black w/ Grey Antenna - UL294	302.05	
AYC-E60N		Mullion Rosslare goPROX Reader with 2x6 Matrix Keypad – Convertible – Natural w/ Dark Grey Antenna - UL294	302.05	
AYC-E60B		Mullion Rosslare goPROX Reader with 2x6 Matrix Keypad – Convertible – Black w/ Dark Grey Antenna - UL294	302.05	
AYC-T65N		US Gang Box Rosslare goPROX Reader with 3x4 Matrix Keypad – Convertible – Natural w/ Dark Grey Antenna -	262.85	
AYC-T65B		US Gang Box Rosslare goPROX Reader with 3x4 Matrix Keypad – Convertible – Black w/ Dark Grey Antenna -	262.85	
AY-Q12 AYC-Q6x Series		Anti-Vandal US Single Gang Proximity Reader 125 KHz, EM Compatible Rosslare Proximity and goPROX with PIN Reader Series. The 12, 64 and 65 Series are		
AY-Q12		US Gang Box Anti-Vandal Rosslare Proximity Reader - UL294 Approved	195.50	
AYC-Q64B		US Gang Box Anti-Vandal Rosslare Proximity Reader with 3x4 Matrix Backlit Keypad – Convertible - UL294	315.85	
AY-Q65		US Gang Box Anti-Vandal Rosslare Proximity Reader with 3x4 Matrix Backlit Piezoelectric Keypad – Convertible	265.20	
AYC-Q60		US Gang Box Anti-Vandal Rosslare goPROX Reader with 3x4 Matrix Backlit Keypad – Convertible - UL294	301.50	
AY-R Series	general	Multi-Color Illumination Proximity Reader Series The Multi-Color Illumination Proximity Reader Series has seven selectable colors that cycle or the colors can be controlled and instantly changed via four inputs to the reader to adapt to any situation. 125 KHz, EM Compatible Rosslare Proximity and outputs Wiegand 26-Bit. The operating voltage is 12–16 VDC. US Single Gang mounted. It is rated IP54.		
AY-R12		With 18" (46-cm) pigtail	268.50	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

	Readers - 125 KHz - Rosslare PROX and goPROX™			
Part Number	Photo	Description	MSRP	Master Distributor
AY-C1x Series AY-D1x Series	·	Indoor Proximity Readers 125 KHz, EM Compatible Rosslare Proximity Series. Wiegand 26-Bit output, bi-color LED and buzzer indicators. 4-wire terminal block wiring. Bell button for sounder when used with Rosslare's AC-015, AC-020, AC-115, AC-215/IP, AC-225/IP, AC-425/IP, and AC-525 controllers.		
AY-CR11W		Mullion Rosslare Proximity Reader with Bell Button	47.45	
AY-CR12W		Mullion Rosslare Proximity Reader	47.45	
AY-DR11W		US Gang Box Rosslare Proximity Reader	47.45	
AY-DR12W		US Gang Box Rosslare Proximity Reader	47.45	
AY-D19M		US Gang Box Rosslare Proximity Reader with 3x4 Matrix Keypad	68.05	
AY-V Series		Medium Range Proximity Reader The Medium-Range Proximity Reader has a read range of 220 mm (9"). It has single authentication with Rosslare Proximity and outputs Wiegand 26-Bit. The operating voltage is 5–16 VDC. US Single Gang, UK Gang or wall mounted. It is rated IP65.		
AY-V12B		Black Color with 18" (46-cm) pigtail	246.10	
AY-V64B		Black Color with 18" (46-cm) pigtail with 3x4 Matrix Keypad	393.15	
		Long Range Proximity Reader		
		The Long-Range Proximity Reader has a read range of 60 cm (23.6"). It has single authentication with Rosslare Proximity and outputs Wiegand 26-Bit. The operating voltage is 10–16 VDC. The standby current is 280 mA and		

Readers - PIN Only

rated IP65.

Black Color with 18" (46-cm) pigtail

the maximum current is 330 mA. The dimensions are 300 x 300 x 25 mm (11.8 x 11.8 x 1"). Wall mounted. It is

Part Number	Photo	Description	MSRP	
AYC-G54 Series AYC-F54 Series	11 2 S 14 S S 15 S S 16 S S	Convertible Backlit PIN Reader Multi-format Output (Wiegand 26-Bit, Clock & Data). Two bi-colored LED indicators, internal buzzer, LED control. Backlit keypad for PIN entry and programming. The operating voltage is 5–16 VDC. Optical back tamper. Waterproof and rugged, meets IP65. Automatically converts into a 500-user controller when operated with Rosslare's Intelligent Secure power supplies (PS-x25T sold separately). (Image showing the AYC-F54)		
AYC-G54		Mullion PIN Reader with 2x6 Matrix Backlit Keypad – Convertible	130.30	
AYC-F54		US Gang Box PIN Reader with 3x4 Matrix Backlit Keypad – Convertible	144.05	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

732.25

1. All prices are in US Dollars.

AY-Z Series

AY-Z12A

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access C	ontrol - Price List	Valid	Date: February 15,
		Readers - PIN Only	
Part Number	Photo	Description	MSRP
AYC-E55 Series		Convertible 2x6 Ultra-Slim PIN Reader	
AYC-E55		Mullion PIN Reader with 2x6 Matrix Piezo Keypad - Convertible	194.45
AYC-Q54B Series	128 456 789 108	Convertible Anti-Vandal Backlit 3x4 PIN Reader	
AYC-Q54B		US Gang Box Anti-Vandal PIN Reader with 3x4 Matrix Backlit Keypad – Convertible	210.65
AY-S55 Series AY-T55 Series	123 456 789	Anti-Vandal Piezoelectric PIN Reader	
AY-S55		Mullion PIN Reader with 2x6 Matrix Piezo Keypad	196.85
AY-T55		US Gang Box PIN Reader with 3x4 Matrix Piezo Keypad	205.10
AY-T55B		US Gang Box PIN Reader with 3x4 Matrix Piezo Keypad Backlit	249.60
AY-D0X Series	*.000	Indoor Multi-Format PIN Reader Series Multi-format output (Wiegand 26-Bit, Clock & Data). Two bi-colored LED indicator with keypad for PIN entry and programming. The operating voltage is 5–16 VDC. For indoor use with case tamper.	
AY-D09M		US Gang Box Rosslare 3x4 Matrix Keypad Reader	51.30

1. All prices are in US Dollars.

www.rosslaresecurity.com

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.



Page 18 of 34

North America - Access Control - Price List

	CSN Smartcard Readers			
Part Number	Photo	Description	MSRP	
AY-x6255 Series		CSN Select Smartcard Reader Series - Rev A		
AT-X0200 Oction		Multi-credential technology contactless smart card (13.56 MHz) readers for use in access control system		
AY-K6255		Micro-Mullion CSN Select Reader	89.25	
AY-L6255		Mullion CSN Select Reader	89.25	
Y-H6255		US Single Gang CSN Select Reader - OSDP Support	103.50	
AY-M6255		Asia/UK Gang CSN Select Reader - OSDP Support	103.50	
Y-R6255		Illuminated CSN SELECT Smart Card Reader - OSDP Support	123.40	
AYC-x6355 Series		CSN Select Smartcard Reader Series with Keypad - Convertible Multi-credential technology contactless smart card (13.56 MHz) readers with Keypad for use in access control system solutions. CSN SELECT readers can read the Card Serial Number (CSN) from many smart card RFID standards implementations including ISO14443A/B, ISO15693, and ISO18092, see documentation for credential compatibility. OSDP connectivity available on select models. Standard readers output the Wiegand CSN data in Wiegand 26-Bit format, with other Wiegand formats available upon request.		
AYC-H6355		194.75	172.80	
AYC-M6355		Asia/UK Gang CSN Select Reader with Keypad - OSDP Support - Convertible	172.80	
DR-6255	1 11111	CSN Select Desktop Enrollment Reader - Rev A A desktop smart card CSN reader with a USB interface for use when enrolling user credentials to access control software such as Rosslare's AXTraxNg™. CSN SELECT readers can read the Card Serial Number (CSN) from many smart card RFID standards implementations including ISO14443A/B, ISO15693, and ISO18092, see documentation for	173.25	
DR-12C		EM Card Desktop Reader Reads the EM card identification number and transmits it to connected access control software, such as Rosslare's AxTraxNg ^{TM.} With its USB computer interface, it is quick and easy to install and runs without any additional power source.	135.85	
DR-6280	1 (1150)	Open to Secure Desktop Reader Advanced MIFARE Classic® EV1 and MIFARER DESFire® EV1 O2S Desktop Reader, reads the O2S ID Data and CSN and transmits it to connected access control software, such as Rosslare's AxTraxNg [™] . With its USB computer interface, it is quick and easy to install and runs without any additional power source.	374.15	
AT-C1S-000-E000		MIFARE® Classic - 1K - ISO Card (PVC) - 7UID - Not Programmed - Rosslare Branded - CSN Printed in Wiegand 26-Bit Format (FC, ID). Designed for use with CSN Select family of readers, ID printed on card can be used for card enrollment for installations that utilize 26A Wiegand format. (25 pcs per pack)	44.05	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

www.rosslaresecurity.com

^{1.} All prices are in US Dollars.





North America - Access Control - Price List Valid D		Date: Febru	ary 15, 2017	
Readers - Modules				
Part Number	Photo	Description	MSRP	
MD-12 Series 125KHz		OEM Proximity Reader Module 125 KHz Micro sized proximity reader component with built in antenna. Operates using 5 VDC. 5-Pin Connection, Plugs into any Host Board.		
MD-12W		Wiegand 26-Bit Output	43.05	
MD-12C		Clock & Data Output	43.05	

www.rosslaresecurity.com



North America - Access	Control - Price List	V	alid Date: Febru	ary 15, 201
		Credentials - 125 KHz - EM Compatible		
Part Number	Photo	Description	MSRP	Master Distributor
AT-ERS-26A-3001	200 M. A. (200)	ISO Read Only Proximity Card (Was AT-R11) 125KHz, Link ID, EM		
		< 4 Packs	84.25	33.75
		5 - 40 Packs	56.00	22.50
		41 - 80 Packs	53.00	21.25
		81 - 120 Packs	49.75	20.00
		>120 Packs	47.00	18.75
AT-ERC-26A-3001	100 mm 10	Clamshell Read Only Proximity Card (Was AT-R14) 125KHz, Link ID, EM		
		< 4 Packs	49.75	20.00
		5 - 40 Packs	31.00	12.50
		41 - 80 Packs	28.25	11.25
		81 - 120 Packs	24.75	10.00
		>120 Packs	22.00	8.75
AT-ERK-26A-7TB0		Read Only Proximity Tag - Rectangular Black (Was AT-R271BL) 125 KHz, EM4102		
		< 4 Packs	88.75	35.75
		5 - 40 Packs	60.50	24.25
		41 - 80 Packs	57.75	23.25
		81 - 120 Packs	54.25	21.75
		>120 Packs	51.50	20.75
AT-ERK-26A-7RB0	Ô	Read Only Proximity Tag - Circular, Black (Was AT-R261BL) 125 KHz, EM4102		
		< 4 Packs	88.75	35.75
		5 - 40 Packs	60.50	24.25
		41 - 80 Packs	57.75	23.25
		81 - 120 Packs	54.25	21.75
		>120 Packs	51.50	20.75

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

	Credentials - 125 KHz TEMIC and 13.56 MHz Mifare® Classic				
Part Number	Photo	Description		MSRP	Master Distributor
AT-TUS-000-0001		ISO Multiple Read/Write Proximity Card- (Was AT-T11) 125 KHz Temic			
			< 4 Packs	167.75	67.50
			5 - 40 Packs	111.75	45.00
			41 - 80 Packs	105.75	42.50
			81 - 120 Packs	99.50	40.00
			>120 Packs	93.25	37.50
AT-TUC-000-0001		Clamshell Multiple Read/Write Proximity Card - (Was AT-T14) 125 KHz Temic			
			< 4 Packs	99.50	40.00
			5 - 40 Packs	62.25	25.00
			41 - 80 Packs	56.00	22.50
			81 - 120 Packs	49.75	20.00
			>120 Packs	43.50	17.50
AT-D1S-000-0001		Mifare® Contactless 1K Card-ISO Printable Card- (Was AT-T512) Mifare® compatible ISO Read/Write card, 1K Bytes			
			< 4 Packs	70.00	28.25
			5 - 40 Packs	67.75	27.25
			41 - 80 Packs	64.50	26.00
			81 - 120 Packs	61.50	24.75
			>120 Packs	56.00	22.50
AT-D1K-000-0SB0		Mifare® Contactless 1K Tag - Black "Shark"- (Was AT-T551B) Mifare® compatible ISO Read/Write card, 1K Bytes	•		
			< 4 Packs	117.50	52.00
			5 - 40 Packs	78.50	34.75
			41 - 80 Packs	74.00	32.75
			81 - 120 Packs	69.50	30.75
			>120 Packs	27.62	29.00

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

Valid Date: February 15, 2017

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 22 of 34



Valid Date: February 15, 2017

North America - Access Control - Price List

	Switches - EX - Security Series				
Part Number	Photo	Description	MSRP	Master Distributor	
Plastic Push Buttons	12	Plastic Push Buttons Connects to a controller's input, either NO or NC connection.			
EX-01		Plastic Switch with "PUSH TO EXIT" lettering	2.95	1.20	
EX-02		Plastic Switch with "EMERGENCY" lettering	2.95	1.20	
EX-04 Series	PUSH TO EXIT	Plastic Slim Piezoelectric REX Switch with Light Ring Flush Mount multi-purpose Piezoelectric Switch with metal coloured plastic face plate, provides an Open Collector Output (Max 1A @ 30VDC), for indoor use (IP54), two-color light ring (Red / Green). Connection via 5-Wire pigtail cable. Labels with other languages are available upon request. (Image showing the EX-H04E0)			
EX-H0400		US Gang Size - No Label	43.50	17.50	
EX-H04E0		US Gang Size - "PUSH TO EXIT" Label	43.50	17.50	
EX-M0400		UK Gang Size - No Label	43.50	17.50	
EX-M04E0		UK Gang Size - "PUSH TO EXIT" Label	43.50	17.50	
EX-22 Series	EXIT	Plastic Slim Piezoelectric REX Switch with Light Ring Flush Mount multi-purpose Piezoelectric Switch with metal coloured plastic face plate, provides an Open Collector Output (Max 1A @ 30VDC), for indoor use (IP54), two-color light ring (Red / Green). Connection via 5-Wire pigtail cable. Labels with other languages are available upon request. (Image showing the EX-H04E0)			
EX-H2200		US Gang Size - No Label	43.05	17.30	
EX-H22E0		US Gang Size - "PUSH TO EXIT" Label	43.05	17.30	
EX-M2200		UK Gang Size - No Label	43.05	17.30	
EX-M22E0		UK Gang Size - "PUSH TO EXIT" Label	43.05	17.30	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

Page 23 of 34

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

THORIT AMOUNT		vana.	J uto. 1 051 u	a. y . o, _o.	
	Switches - EX - Security Series				
Part Number	Photo	Description	MSRP	Master Distributor	
EX-06/16 Series		Piezo REX Switch with Toggle Option Flush-mount, piezoelectric button with a tri-color light ring (Red / Orange / Green) and with LED control input. Rugged and durable stainless steel face plate with water resistant (IP65) construction can be used outdoors. Provides one 2A relay with two isolated dry contacts N.O. & N.C., Switch duration is adjustable from 0 to 60 seconds or put into toggle switching mode. Connection via terminal blocks on rear side. UL294 approved. Labels with other languages are available upon request. (Image showing the EX-0600)			
EX-0600		US Gang Box - No label	104.40	42.00	
EX-06E0		US Gang Box - "PUSH TO EXIT" label	104.40	42.00	
EX-1600		Mullion - No label	99.45	40.00	
EX-16E0		Mullion - "PUSH TO EXIT" label	99.45	40.00	
EX-07/17 Series		Digital Piezo REX switch with Toggle Option Flush-mount, piezoelectric button with a tri-color light square (Red / Orange / Green), with optional digital colour fading effect and LED Control input. Rugged and durable stainless steel face plate with water resistant (IP65) construction can be used outdoors. Provides one 2A relay with two isolated dry contacts N.O. & N.C., Switch duration is adjustable from 0 to 60 seconds or put into toggle switching mode. Connection via 10 wire pigtail cable. UL294 approved. Labels with other languages are available upon request. (Image showing the EX-0700)			
EX-0700		US Gang Box - No label	114.80	46.20	
EX-07E0		US Gang Box - "PUSH TO EXIT" label	114.80	46.20	
EX-1700		Mullion - No label	109.40	44.00	
EX-17E0		Mullion - "PUSH TO EXIT" label	109.40	44.00	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

	Switches - PX - Industrial General Purpose					
Part Number	Photo	Description		MSRP	Master Distributor	
PX-13 Series		Small Metallic Piezoelectric Push Button Piezoelectric switch with 22mm panel mounting diameter Open collector output (Max 1A @ 30VDC). (Image showing the PX-13N)				
PX-13R		Red Anodized				
PX-13L		Blue Anodized				
PX-13M		Green Anodized				
PX-13N		Natural Anodized				
PX-13B		Black Anodized				
PX-13G		Gold Anodized				
PX-13W		White Anodized				
			200 pcs or less	22.50	9.0	
			Over 200 pcs.	20.10	8.10	
			Over 500 pcs.	17.65	7.10	
			Over 1K pcs.	16.05	6.4	
PX-23 Series		Small Metallic Piezoelectric Push Button with Spot LED Piezoelectric switch with Spot LED with 22mm panel mounting diameter. Two colour LED Control Red/Green Open collector output (Max 1A @ 30VDC). (Image showing the PX-23N)				
PX-23R		Red Anodized				
PX-23L		Blue Anodized				
PX-23M		Green Anodized				
PX-23N		Natural Anodized				
PX-23B		Black Anodized				
PX-23G		Gold Anodized				
PX-23W		White Anodized				
			200 pcs or less	39.10	15.75	
			Over 200 pcs.	34.90	14.05	
			Over 500 pcs.	30.75	12.35	
			Over 1K pcs.	27.90	11.25	

www.rosslaresecurity.com

^{1.} All prices are in US Dollars.

^{2.} Minimum order: USD 100.00, FCA Southlake, Texas.

^{3.} Prices are subject to change without prior notice.



Valid Date: February 15, 2017

North America - Access Control - Price List

Switches - PX - Industrial General Purpose					
Part Number	Photo	Description	MSRP	Master Distributor	
PX-34		Small Metallic Piezoelectric Push Button with Ring LED Piezoelectric switch with Ring LED with 22mm panel mounting diameter. Two colour LED control Red/Green Solid state relay output (Max 100mA @ 30VDC). (Image showing the PX-34N)			
PX-34R		Red Anodized			
PX-34L		Blue Anodized			
PX-34M		Green Anodized			
PX-34N		Natural Anodized			
PX-34B		Black Anodized			
PX-34G		Gold Anodized			
PX-34W		White Anodized			
		200 pcs or less	71.30	28.70	
		Over 200 pcs.	63.60	25.60	
		Over 500 pcs.	55.95	22.50	
		Over 1K pcs.	50.85	20.45	

Switches - EX & PX - Switch Accessories

Part Number	Photo	Description	MSRP	Master Distributor
External Mount Enclosures	PUSH TO EXIT	External Mount Metal Enclosures These rugged die cast metal Enclosures allow Rosslare switch products to be installed and used on hard surfaces where it is difficult for the switch to be flush mounted, such as on a metal surface or reinforced concrete wall. (Metal Enclosure only, switches are sold separately) (Image showing the MP-06 with EX-07E0, the EX-07E0 is sold separately).		
MP-06		External Mount Metal Enclosure for EX-06, EX-07, EX-04, EX-22 Series Buttons and MP-H03.	32.65	13.15
MP-16		External Mount Metal Enclosure for EX-16, EX-17 Piezo Buttons and MP-J03	29.50	11.85
Mounting Plates for PX Buttons		Mounting Plate for PX Series Piezo Push Buttons Made of Stainless Steel these mounting plates are required for installation of PX Series switches on common electrical box. The MP-H03 and MP-J03 are also compatible with MP-06 and MP-16 metal mounting housings respectively. (Mounting Plate only, the PX Switch is sold separately) (Image showing the MP-H03, MP-J03, MP-M03 with switches installed, switches are sold separately)		
MP-H03		Mounting Plate for PX Series Piezo Push Buttons (US Gang Box)	37.05	14.90
MP-J03		Mounting Plate for PX Series Piezo Push Buttons (Mullion Mount)	37.05	14.90
MP-M03		Mounting Plate for PX Series Piezo Push Buttons (UK Gang Box)	37.05	14.90

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Locks - Electromagnetic Locks				
Part Number	Photo	Description	MSRP	Master Distributor
Electromagnetic Locks	8 19	Electromagnetic Locks 1200 lbs, 600 lbs, and 300 lbs Surface mounted Magnetic Locks built from corrosion resistant anodized aluminum. The lock has dual voltage (12/24VDC) operability, has low current consumption and has a built-in voltage spike suppressor and no residual magnetism. Different types of bracket and housing are available to fit various mounting conditions. Compatible with EN55011:1998: Class B, EN60601-1-2:2002, EN61000-4-2:1995, EN61000-4-3:2002 & UL-S5351.		
LK-M12L		MAGLOCK 1200 lbs with Lock Status & Indicator	161.70	65.05
LK-M06L		MAGLOCK 600 lbs with Lock Status & Indicator	100.80	40.55
LK-M03		MAGLOCK 300 lbs	88.25	35.50

Locks - Electromagnetic Lock Accessories

Part Number	Photo	Description	MSRP	Master Distributor
Adjustable L-Brackets		Adjustable L-Bracket for Electromagnetic Locks Adjustable L-Bracket built from corrosion resistant anodized aluminum. It is easy to locate the armature plate and collocate with the Electromagnetic Locks.		
LA-L12		Adjustable L-Bracket for LK-M12L, 1200 lbs electromagnetic locks	40.70	16.35
LA-L06		Adjustable L-Bracket for LK-M06L, 600 lbs electromagnetic locks	21.60	8.70
LA-L03		Adjustable L-Bracket for LK-M03, 300 lbs electromagnetic locks	17.30	6.95
L&Z Brackets		Adjustable L&Z Bracket for Electromagnetic Locks Adjustable L-Z Bracket built from corrossion resistant anodized aluminum and is compatible with the Electromagnetic Locks.		
LA-Z12		L&Z Bracket for LK-M12L, 1200 lbs electromagnetic locks	121.95	49.05
LA-Z06		L&Z Bracket for LK-M06L, 600 lbs electromagnetic locks	62.95	25.30
LA-Z03		L&Z Bracket for LK-M03, 300 lbs electromagnetic locks	48.70	19.60
U Brackets		U-Bracket for glass door for use with LK-M12L & LK-M06L U-Bracket built from corrosion resistant anodized aluminum and is compatible with the Electromagnetic Locks.		
LA-U12		U-Bracket for glass door for use with LK-M12L & LK-M06L, 1200 lbs and 600 lbs electromagnetic locks	44.75	18.00
LA-U03		U-Bracket for glass door for use with LK-M03, 300 lbs electromagnetic locks	34.45	13.85

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



North America - Access Control - Price List

North America - Access Control - Price List Valid I		Date: Febru	ıary 15, 2017	
Locks - Electromagnetic Lock Accessories				
Part Number	Photo	Description	MSRP	Master Distributor
Spacers	Total and in	Maglock Spacers		
LA-S12		6mm Spacer for use with LK-M12L, 1200 lbs electromagnetic locks	15.15	6.10
LA-S06		5mm Spacer for use with LK-M06L, 600 lbs electromagnetic locks	10.50	4.25

Power Supplies for Access Control

Part Number	Photo	Description		Master Distributor
PS-x25T Series		Intelligent Dual-Relay Secured Power Supply Power Supply with two 5 Amp from C relays for convertible reader families. Includes 1.2 Amp / 12VDC output, battery charger for 7Ah lead acid battery (battery not included). Power LED Indicator and sounder output for Bell / Chime / Alarm. Proprietary secure serial communications between power supply and convertible reader. (Image showing the PC-25T)		
PC-25T		PC-25T PCBA Module with 16 VAC Input from transformer	48.60	19.55
PC-25LT		PC-25LT PCBA Module with 16 to 24 VAC Input from transformer	55.80	22.45
PS-C25TU		Large metal enclosure with PC-25T, LED Indicator, Speaker and no transformer, space for 7Ah lead acid battery,	89.85	36.15
PS-16 Series	2	12VDC / 1.2 A Power Supply Unit Input: 16 VAC / 50 Hz from transformer Output: 12 VDC / 1.2A Built-in battery charger, space for 7Ah battery (battery not included) General purpose power supply unit. (Image showing the PC-P16)		
PC-P16		PC-P16 PCBA Module with 16 VAC Input from transformer	24.95	10.05
PS-17 Series		12VDC / 2 A Power Supply Unit Input: 16 VAC / 50 Hz from transformer Output: 12 VDC / 2.0A Built-in battery charger, space for 7Ah battery (battery not included) General purpose power supply unit. (Image showing the PC-P17)		
PC-P17	-	PC-P17 PCBA Module with 16 VAC Input from transformer	32.55	13.10
PS-18 Series		12VDC / 5 A Power Supply Unit Input: 24 VAC / 50 Hz from transformer Output: 12 VDC / 5A Built-in battery charger, space for 7Ah battery (battery not included) General purpose power supply unit. (Image showing the PC-P18)		
PC-P18		PC-P18 PCBA Module with 24 VAC Input from transformer	56.95	22.90

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

		Other Access Control Accessories		
Part Number	Photo	Description	MSRP	Master Distributor
MD-N32		RS-232 to Ethernet Gateway LAN/WAN Gateway to provide TCP/IP communications for serial communications based controllers and other devices. DHCP IP addressing. Fully configurable using dedicated PC software (inCluded), Compatible with all Rosslare equipment with RS-232 communication inCluding AS-525, GS-02, HRP-01, and HRP-02. Supplied with Switch Mode Power Supply. MD-N32 with PS-DC1204US (12VDC @300 mA UL - Two Flat Blades)		
MD-N32-US		MD-N32 with PS-DC1204US (12VDC @300 mA UL - Two Flat Blades)	225.75	90.80
MD-N33	-	RS-232 to PSTN Modem V.34 Modem that provides telephony link for serial communication based controllers and other devices. Operates at 33.6 kbps. Powered with 12VDC adapter. Fully configurable using AS-525 software.		
MD-N33-US		MD-N33 with PS-DC1204US (12VDC @300 mA UL - Two Flat Blades)	271.75	109.30
MD-08	Na.	Wiegand 26-Bit to RS-232 Output converter Converts standard Wiegand 26 bits reader output to RS-232. Suitable for desktop applications and card enrollment. With optional MD-12W unit installed internally or add an external Rosslare proximity reader, acts as a Card Enrollment device for AxTrax and for AS-115 Access Control management software. No power adaptor	47.80	19.25
MD-08B	No.	inCluded. Compatible with Rosslare's PS-DC1512 Switch Mode Power Supply (15VDC / 800mA). Programming Interface for Smartcard Readers Interface form programming Smartcard readers output format and other settings. Works along with the MiProg - Smartcard Programming PC software.		
MD-08B-US		MD-08B with PS-DC1512US (12VDC @800 mA UL - Two Flat Blades)	96.95	39.00
Mounting Spacers For Readers		Mounting Spacers for Readers These mountings spacers have been designed for use when installing readers on a metal surface, the added spacer creates additional distance between the metal surface and the reader and will allow for improved read range. (Image showing the MP-K01)		
MP-K01		Mount spacer for AY-K12 / AY-K20 / AY-K25 Readers	6.35	2.55
MP-J01		Mount spacer for AY-J12 / AY-J20 / AY-J25 Readers	6.35	2.55
MP-Z02		Mount spacer for AY-Z12A Reader	35.05	14.10
Flush Mount Housings		Flush Mount housings for C-Box and G-Box readers and controllers Allows readers or controllers featured in the C-Box or G-Box to be mounted flush on a wall. (Image showing the MP-C02)		
MP-C02		Flush Mount housing for AY-C19M, AY-C09M readers and AC-C31/32 standalone controllers.	5.75	2.30
MP-G02		Flush Mount housing for AC-G43/44 standalone controllers and AYC-G54/64 convertible readers.	10.85	4.35

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

Other Access Control Accessories					
Part Number	Photo	Description	MSRP	Master Distributor	
Converter Cables	9	RS-485 to RS-232 Converter cable Various converter cables used to connect Rosslare devices to USB communication ports. Cable length is approximately 2m (6ft) (Image showing the MD-14U)			
MD-14U		RS-485 to USB Converter Cable	41.00	16.5	
MD-24U		RS-232 to USB Converter Cable	31.75	12.7	
MD-62U		RS-232 TTL to USB Converter Cable	45.10	18.1	
BL-D40		Compact Bell/Strobe Unit for Stand Alone Controllers Emits bell, chime and alarm sounds per programmable events of Rosslare stand-alone controllers. Low power device, uses reader's power input and REX output as control line.	29.05	11.70	

Demo Kits

Part Number	Photo	Description	MSRP	Master Distributor
DMC-AC225IP		AC-225IP - IP Networked Access Control Demo Case 1 x AC-225IP BOARD - Advanced Networked Access Controller 1 x MD-D02 - Two Door Expander 1 x MD-14 - RS-232 to RS-485 Converter 1 x AY-K25 - Micro-Mullion Mifare® Smartcard Contactless Reader 1 x AY-B3663 - Mini Fingerprint SwipeMatch-on-Card Reader 1 x AYC-E65BG - Gray Convertible 2x6 Ultra-Slim Backlit PIN & Prox Reader Controller 1 x EX-17 - Digital Mullion size Piezo REX switch Assortment of Credentials		
DMC-AC225IP-US		DMC-AC225IP with PS-DC1512US (12VDC @800 mA UL - Two Flat Blades)	1,521.20	611.90
DMC-AYC		Convertible Reader/Controller Series Demo Case 1 x AYC-E65BG - Gray Convertible 2x6 Ultra-Slim Backlit PIN & Prox Reader / Controller 1 x AYC-W6500 - Fingerprint, Backlit PIN & Prox Convertible Reader / Controller 1 x AYC-Q64B - Convertible Anti-Vandal Backlit 3x4 PIN & Prox Reader Controller 1 x AYC-G64 - Convertible 2x6 Backlit PIN & Prox Reader / Controller 1 x PC-25T - Secured power supply unit - PCB Module, 16 VAC Input Assortment of Credentials		
DMC-AYC-US		DMC-AYC with PS-DC1512US (12VDC @800 mA UL - Two Flat Blades)	1,811.75	728.75

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 30 of 34



North America - Access Control - Price List Valid Da			Date: Febru	ary 15, 2017		
Access Control Kits						
Part Number	Photo	Description		MSRP	Master Distributor	
АС-К03		Single Door Networked Controller Kit Perfect for a basic access control system where control of one door is necessary to maintain tight access control over your workspace, with the flexibility of networking and management software. 1 x AC-115 modular 1- to 8-door Networked Controller including AS-115 PC software 1 x AY-K12 Micro-Mullion Reader 1 x MP-K01 Mounting Spacer for AY-K12 Reader 25 Credentials				
AC-K03C		AC-K03 with 1 pack of AT-ERS-26A-3001 , ISO Card (was AT-R11C)	1 to 19 Kits	459.80	184.95	
			20 to 49 Kits	445.45	179.20	
			50 Kits or above	435.85	175.30	
AC-K03S		AC-K03 with 1 pack of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	435.95	175.35	
			20 to 49 Kits	422.40	169.90	
			50 Kits or above	413.25	166.25	
AC-K03F		AC-K03 with 1 pack of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	464.20	186.75	
			20 to 49 Kits	449.65	180.85	
			50 Kits or above	440.00	177.00	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

Page 31 of 34

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.



Valid Date: February 15, 2017

North America - Access Control - Price List

					•
Access Control Kits					
Part Number	Photo	Description		MSRP	Master Distributo
AC-K01U		AC-215-U Single Door Kit - 1 Reader - 25 Credentials Basic access control solution for one door, with upgradeability options and flexibility of networking and real-time management software. 1 x AC-215-U Networked Controller - FCC approved and UL-294 listed 1 x AY-K12 Micro Mullion Reader 1 x MP-K01 Mounting spacer for AY-K12 reader 25 Credentials 1 x AX-NG Management Software (Level 0)			
AC-K01UC		AC-K01U with 1 pack of AT-ERS-26A-3001 , ISO Card (was AT-R11C)	1 to 19 Kits	667.05	268.3
			20 to 49 Kits	646.25	259.9
			50 Kits or above	632.35	254.3
AC-K01US		AC-K01U with 1 pack of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	643.20	258.
			20 to 49 Kits	623.10	250.
			50 Kits or above	609.65	245.
AC-K01UF		AC-K01U with 1 pack of AT-ERK-26A-7TB0 EM Key FOB (was AT-R271BL)	1 to 19 Kits	671.35	270.
			20 to 49 Kits	650.45	261.6
			50 Kits or above	636.40	256.0
AC-K02U		AC-215-U Two Door Kit - 2 Readers - 50 Credentials The ACK02 Kit is perfect for the basic access control system where two doors or tw maintain tight access control to your workspace, with the flexibility of networking and software. 1 x AC-215-U Networked Controller - FCC approved and UL-294 listed 2 x AY-K12 Micro Mullion Reader 2 x MP-K01 Mounting Spacer for AY-K12 reader 50 Credentials 1 x AX-NG Management Software (Level 0)			
AC-K02UC		AC-K02U with 2 packs of AT-ERS-26A-3001, ISO Card (was AT-R11C)	1 to 19 Kits	785.70	316.0
			20 to 49 Kits	761.15	306.2
			50 Kits or above	744.80	299.0
AC-K02US		AC-K02U with 2 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	738.00	296.
			20 to 49 Kits	714.95	287.0
			50 Kits or above	699.60	281.4
AC-K02UF		AC-K02U with 2 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	794.40	319.
			20 to 49 Kits	769.55	309.
			50 Kits or above	753.05	302.9

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 32 of 34



North America - Access	Control - Price List		Valid I	Date: Febru	ary 15, 201	
Access Control Kits						
Part Number	Photo	Description		MSRP	Master Distributor	
AC-K04U		AC-215IP-U Two Door Kit - 2 Readers - 50 Credentials 1 x AC-215IP-U Professional Scalable Networked Controller with On-board TCP/IP-listed 2 x AY-K12 Micro Mullion Readers 2 x MP-K01 Mounting Spacer for AY-K12 reader 50 Credentials 1 x AX-NG AxTrax Management Software (Level 0)	FCC approved and UL-294			
AC-K04UC		AC-K04U with 2 packs of AT-ERS-26A-3001 , ISO Card (was AT-R11C)	1 to 19 Kits	851.35	342.45	
			20 to 49 Kits	824.80	331.75	
			50 Kits or above	807.05	324.65	
AC-K04US		AC-K04U with 2 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	803.65	323.25	
			20 to 49 Kits	778.45	313.15	
			50 Kits or above	761.75	306.40	
AC-K04UF		AC-K04U with 2 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	860.05	345.95	
			20 to 49 Kits	833.15	335.15	
			50 Kits or above	815.20	327.90	
AC-K06U		AC-225-U Two Door Kit - 2 Readers - 50 Credentials 1 x AC-225-U Professional Scalable Networked Controller - FCC approved and UL-2 2 x AY-K12 Micro Mullion Reader 2 x MP-K01 Mounting Spacer for AY-K12 reader 50 Credentials 1 x AX-NG AxTrax Management Software (Level 0)	294 listed			
AC-K06UC		AC-K06U with 2 packs of AT-ERS-26A-3001 , ISO Card (was AT-R11C)	1 to 19 Kits	1,070.65	430.70	
			20 to 49 Kits	1,037.25	417.25	
			50 Kits or above	1,014.95	408.25	
AC-K06US		AC-K06U with 2 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	1,023.00	411.50	
			20 to 49 Kits	991.00	398.65	
			50 Kits or above	969.65	390.05	
AC-K06UF		AC-K06U with 2 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	1,079.40	434.20	
-			20 to 49 Kits	1,045.60	420.60	
			50 Kits or above	1,023.20	411.60	

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 33 of 34



		Access Control Kits			
Part Number	Description Description			MSRP	Master Distributor
AC-K07U		AC-225IP-U Two Door Kit - 2 Readers - 50 Credentials 1 x AC-225IP-U Professional Scalable Networked Controller with On-board TCP/IP - listed 2 x AY-K12 Micro Mullion Readers 2 x MP-K01 Mounting Spacer for AY-K12 reader 50 Credentials 1 x AX-NG AxTrax Management Software (Level 0)	FCC approved and UL-294		
AC-K07UC		AC-K07U with 2 packs of AT-ERS-26A-3001, ISO Card (was AT-R11C)	1 to 19 Kits	1,165.95	469.00
			20 to 49 Kits	1,129.55	454.35
			50 Kits or above	1,105.25	444.60
AC-K07US		AC-K07U with 2 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	1,118.25	449.80
			20 to 49 Kits	1,083.20	435.75
			50 Kits or above	1,059.95	426.35
AC-K07UF		AC-K07U with 2 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	1,174.65	472.50
			20 to 49 Kits	1,137.90	457.75
			50 Kits or above	1,113.40	447.85
AC-K14U		AC-425-U Two Door Kit - 4 Readers - 100 Credentials 1 x AC-425-U Professional Scalable Networked Controller 4 x AY-K12 Micro Mullion Reader 4 x MP-K01 Mounting Spacer for AY-K12 reader 100 Credentials 1 x AX-NG AxTrax Management Software (Level 0)			
AC-K14UC		AC-K14U with 4 packs of AT-ERS-26A-3001, ISO Card (was AT-R11C)	1 to 19 Kits	1,703.95	685.40
			20 to 49 Kits	1,650.70	664.00
			50 Kits or above	1,615.10	649.70
AC-K14US		AC-K14U with 4 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	1,608.45	647.00
			20 to 49 Kits	1,558.15	626.75
			50 Kits or above	1,524.70	613.30
AC-K14UF		AC-K14U with 4 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	1,721.20	692.35
			20 to 49 Kits	1,667.45	670.75
			50 Kits or above	1,631.60	656.30

www.rosslaresecurity.com

A Division of Rosslare Enterprises Ltd.

1. All prices are in US Dollars.

2. Minimum order: USD 100.00, FCA Southlake, Texas.

3. Prices are subject to change without prior notice.

Page 34 of 34



Valid Date: February 15, 2017

North America - Access Control - Price List

				Date: 1 coru	, ,
		Access Control Kits			
Part Number	Photo	Description		MSRP	Master Distributor
AC-K15U		AC-425IP-U Two Door Kit - 4 Readers - 100 Credentials 1 x AC-425IP-U Professional Scalable Networked Controller with On-board TCP/IP 4 x AY-K12 Micro Mullion Readers 4 x MP-K01 Mounting Spacer for AY-K12 reader 100 Credentials 1 x AX-NG AxTrax Management Software (Level 0)			
AC-K15UC		AC-K15U with 4 packs of AT-ERS-26A-3001, ISO Card (was AT-R11C)	1 to 19 Kits	1.842.15	741.00
			20 to 49 Kits	1,784.50	717.80
			50 Kits or above	1,746.20	702.40
AC-K15US		AC-K15U with 4 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	1,746.65	702.60
			20 to 49 Kits	1,692.05	680.65
			50 Kits or above	1,655.70	666.00
AC-K15UF		AC-K15U with 4 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	1,859.40	747.95
			20 to 49 Kits	1,801.35	724.60
			50 Kits or above	1,762.55	709.00
AC-K16		AC-825IP Four Door Kit - 4 Readers - 100 Credentials - 110 VAC Transformer 1 x AC-825IP Professional Scalable Networked Controller with On-board TCP/IP - 5 Power Supply 4 x AY-K12 Micro Mullion Readers 4 x MP-K01 Mounting spacer for AY-K12 reader 100 Credentials 1 x AX-NG AxTrax Management Software (Level 0)	Supplied with Switch-Mode		
AC-K16C		AC-K16 with 4 packs of AT-ERS-26A-3001, ISO Card (was AT-R11C)	1 to 19 Kits	1,939.10	780.00
			20 to 49 Kits	1,878.45	755.60
			50 Kits or above	1,838.05	739.35
AC-K16S		AC-K16 with 4 packs of AT-ERC-26A-3001 Clamshell Card (was AT-R14C)	1 to 19 Kits	1,931.90	777.10
			20 to 49 Kits	1,871.60	752.85
			50 Kits or above	1,831.35	736.65
AC-K16F		AC-K16 with 4 packs of AT-ERK-26A-7TB0 Key FOB (was AT-R271BL)	1 to 19 Kits	2,009.60	808.35
			20 to 49 Kits	1,946.70	783.05
			50 Kits or above	1,904.95	766.25

www.rosslaresecurity.com

Access Control Turn-Key Kits					
Part Number	L Photo L Description L MSRP				
		AC-825IP Turn-Key Kit - AxTraxNG Ultralight & CSN Select Reader Edition			

MS-K825IP Series	AC-825IP Transp. Accord of plant	Rosslare's new Turn-Key Kits contain a Mini-PC pre-installed with the AxTraxNG Ultralight server and client, SQL Express, TeamViewer, and a managed Windows 10 operating system. This Ultralight version is optimized for the Z64W Mini-PC and its activated license is limited to 16 readers. This kit provides a Plug & Play solution with Rosslare's AC-825IP network control panel, an ME-1515 enclosure, CSN SELECT readers, credentials, and a set of accessories. 1 x PC-Z64W Mini-PC and accessories 1 x AC-825IP intelligent IP networked access control unit 4 x AY-K6255 micro-mullion CSN SELECT reader (5-meter pigtail) 2 x AT-C1S-000-E000 (25-card pack) MIFARE® Classic - 1K - ISO cards (50 cards total)		
MS-K825IP-U	Min-PC C	AC-825IP powered by switcher with Type B plug cable. Mini PC powered by switcher with Type A plug cable.	2,734.95	1,100.15
MS-K225IP Series	AG-225IP	AC-225IP Turn-Key Kit - AxTraxNG Ultralight & CSN Select Reader Edition Rosslare's new Turn-Key Kits contain a Mini-PC pre-installed with the AxTraxNG Ultralight server and client, SQL Express, TeamViewer, and a managed Windows 10 operating system. This Ultralight version is optimized for the Z64W Mini-PC and its activated license is limited to 16 readers. This kit provides a Plug & Play solution with Rosslare's AC-225IP network control panel, CSN SELECT readers, credentials, and a set of accessories. 1 x PC-Z64W Mini-PC and accessories 1 x AC-225IP intelligent IP networked access control unit 2 x AY-K6255 micro-mullion CSN SELECT reader (5-meter pigtail) 1 x AT-C1S-000-E000 (25-card pack) MIFARE® Classic - 1K - ISO cards		
MS-K225IP-U	Mini-PC II	AC-225IP without transformer or cable (UL 294 and FCC certified) Mini PC powered by switcher with Type A plug cable.	2,019.10	812.20

www.rosslaresecurity.com