

## 2280 Series 1200 Lb. SlimLine



2280



2282



2280-TJ80



2282-TJ82



New "upscale" low profile electromagnetic locks, surface mounted for single and double outswing or inswing doors. Seamless one-piece lock housings mount with an adjustable baseplate for quicker installations. Armatures utilize high-impact plastic housings, with incorporated foam pads to reduce noise. When ordered with DSM, concealed disc magnets are included at each end of the armature housings.

Size: 1-1/2"D x 2-1/16"H x 12-3/4"L Single or 25-1/2"L Double

Multi-voltage field selectable 12/24 VDC/VAC

Current Draw: 583 mA @ 12VDC Single / 1166 mA Double

335 mA @ 24VDC Single / 670 mA Double

Adjustable Relock Time Delay (Former TD Option) is standard on all models.

MODEL	PRODUCT	FINISH	WEIGHT
<b>2280</b>	Single Electromagnetic Lock Outswing	US28	9 Lbs.
<b>2282</b>	Double Electromagnetic Lock Pair Outswing	US28	18 Lbs.
<b>2280-TJ80</b>	Single Electromagnetic Lock Inswing	US28	12 Lbs.
<b>2282-TJ82</b>	Double Electromagnetic Lock Pair Inswing	US28	24 Lbs.

### OPTIONS

<b>DSM</b>	Door Status Switch - Signals door closed or ajar.
<b>DSM2</b>	Door Status Switch - For the 2282 Series.
<b>HSM</b>	High Security Monitor. Includes the following: Door Status Switch - Signals door closed or ajar. Dynastat Force Sensor - Indicates efficient magnetic bond.
<b>HSM2</b>	High Security Monitor - For the 2282 Series.
<b>LCB</b>	Basic Lock Less Circuit Board
<b>LED</b>	Bi-Color LED - For local signaling of lock status. (Requires HSM or VOP Option.)
<b>LED2</b>	Bi-Color LED's (2) - For the 2282 Series. (Requires HSM2 or VOP2 Option.)
<b>SF</b>	Special Finish - Standard finish US28. Special anodized finishes see page 56.

Notes: \* DSM, HSM, VOP and LED options not available with the LCB option.