



25 SERIES ELECTRIC DOOR STRIKE

25 SERIES

ELECTRIC STRIKES

25 Series Electric Door Strike

- **Low Profile - 1.25" Backset**
- **Reversible Failsafe - Failsecure**
- **Latch Status Output Standard**

The IDC 25 Series electric strike is designed for use with cylindrical and mortise locksets with up to 5/8" (15mm) throw latchbolt. The compact low profile design with an internally mounted solenoid and factory supplied mounting tabs enable quick and easy installation where jamb space is limited. The heavy duty construction makes the 25 Series ideal for high traffic installations.

Features

- Fail-Secure
- Field reversible for failsafe operation
- For 1/2" latch or 5/8" latch with 1/8" door gap
- Latch status output, 3Amp - SPDT
- Non-handed, reversible
- All stainless steel parts with durable die cast body for corrosion resistance
- 630 Stainless steel standard finish
- ANSI A156.31 compliant

Model

25-4U: 4-7/8" (124mm) faceplate for aluminum, wood and hollow metal frames.



Options

- RMB** Buzzer 12/24V AC/DC operation
- BR64XL** Rectifier for AC operation

Specifications

Input: 300/150 mA @ 12/24VDC
Latch Status: SPDT, 3 Amp @ 30VDC
Dimensions: 1-1/4" W x 4-7/8" H x 1-1/4" D
(31.8W x 124H x 31.8D mm)