



2511



2522



2511TJ



2522TJ2



2585



2585-TJ85

## 2500 Series 650 Lb. "Mini"

Mini electromagnetic locks, surface mounted for single and double outswing or inswing doors.  
 Size: 1-1/4"D x 1-3/4"H x 10-1/2"L Single or 21"L Double  
 Multi-voltage field selectable 12/24 VAC/VDC  
 Current Draw: 381 mA @ 12V Single / 762 mA Double  
 205 mA @ 24V Single / 410 mA Double

MODEL	PRODUCT	FINISH	WEIGHT
<b>2511</b>	Single Electromagnetic Lock Outswing	US28	4.5 Lbs.
<b>2522</b>	Double Electromagnetic Lock Pair Outswing	US28	9 Lbs.
<b>2511TJ</b>	Single Electromagnetic Lock Inswing	US28	7.5 Lbs.
<b>2522TJ2</b>	Double Electromagnetic Lock Pair Inswing	US28	15 Lbs.

## 2585 Series 650 Lb. "Bantam"

"Bantam" electromagnetic lock, surface mounted for single outswing or inswing doors.  
 Size: 1-1/4"D x 1-3/4"H x 8-1/2"L  
 Field Selectable 12/24 VDC.  
 Current Draw: 500 mA @ 12VDC  
 250 mA @ 24VDC

MODEL	PRODUCT	FINISH	WEIGHT
<b>2585</b>	Single Lock Outswing	US28	4 Lbs.
<b>2585-TJ85</b>	Single Lock Inswing	US28	8 Lbs.

## OPTIONS

- **ATS** Anti-Tamper Switch - Signals removal of the housing cover.
- **CLH** Custom Length Housing - See page 24.
- DSM** Door Status Switch - Signals door closed or ajar.
- DSM2** Door Status Switch - For the 2522 Series only.
- DYN** Dynastat Force Sensor - Indicates efficient magnetic bond.
- DYN2** Dynastat Force Sensor - For the 2522 Series only.
- LED** Bi-Color LED - For local signaling of lock status.  
(Requires DYN Option. Not available on TJ models.)
- LED2** Bi-Color LED's (2) - For the 2522 Series only.  
(Requires DYN2 Option. Not available on TJ models.)
- SF** Special Finish - Standard finish US28. Special anodized finishes see page 56.

Notes: • ATS and CLH options not available on the 2585 Series.

Note: For AC operation order #7088 Pre-wired Rectifier Bridge. See page 48.

