



NOTES:

- ① USE 7 GAUGE REINFORCEMENT FOR HOLLOW METAL FRAMES AND 12 GAUGE REINFORCEMENT FOR HOLLOW METAL DOORS.
- ② MINIMUM OPENING REQUIRED FOR CLOSER BODY. A 15 1/2" X 2" CUTOUT IS REQUIRED IN THE FRAME.
- ③ A SECTION OF THE STOP BELOW CLOSER MUST BE REMOVABLE, SEE TEMPLATE A7778 FOR AN ALTERNATE FRAME CONFIGURATION FOR A 2" DOOR THAT DOES NOT REQUIRE A REMOVABLE STOP.
- ④ MAXIMUM DEGREE OF OPENING 90°.
- ⑤ LEFT HAND DOOR AND CLOSER SHOWN, RIGHT HAND OPPOSITE.
- ⑥ A SECTION OF THE REMOVABLE STOP MUST BE LEFT OPEN FOR ARM CLEARANCE.

<b>SARGENT</b> ® Manufacturing Company 100 Sargent Drive New Haven, CT 06511	
DATA SHEET: 268 OR 267 OVERHEAD CONCEALED CLOSER WITH POCKET HINGES 2" FACE FRAME	RELEASE DATE <b>APRIL 09</b> TEMPLATE NO. A7782 B