Delayed Egress Systems







Delay egress electromagnetic locks, surface mounted for outswing single or double doors and inswing single doors. Non-handed.

Sizes: 3"D x 2-3/4"H x 11"L (3101C) 3"D x 2-3/4"H x 22"L (3121C) 3"D x 2-3/4"H x 11"L ea. (3121C2) 2-3/4"D x 4"H x 11"L (3101C-TJ101)

Multi-voltage auto-sensing 12/24 VAC/VDC

Current Draw: 456 mA @ 12VDC / 263 mA @ 24VDC (3101C, 3101C-TJ101)

849 mA @ 12VDC / 480 mA @ 24VDC (3121C, 3121C2)



MODEL	PRODUCT	FINISH	WEIGHT
3101C-G2 3121C-G2	Single Delay Egress Lock Outswing Double Delay Egress Lock Pair Outswing	US28 US28	12 Lbs. 24 Lbs.
3121C2-G2	Double Delay Egress Lock Pair Outswing	US28	24 Lbs.
3101C-TJ101-G2	Tandem Unit To Accommodate Center Mullion Single-Inswing Delay Egress Lock Kit Includes "Z" Bracket, Shim Plate, Door Sign,	US28	15 Lbs.
	Wall-Mount Keyswitch (#7054)		

3121C2 (Gen II) LISTED

OPTIONS

AAO Auxiliary Alarm Output - Redundant 2nd delay egress output, SPDT.

ATS Anti-Tamper Switch - Signals removal of the housing cover.

ATS2 Anti-Tamper Switch - For the 3121C and 3121C2

BPM Bypass Monitor - Signals bypass keyswitch activation

DSM Door Status Switch - Signals door closed or ajar.

DSM2 Door Status Switch - For the 3121C and 3121C2.

Dynastat Force Sensor - Indicates efficient magnetic bond.

DYN2 Dynastat Force Sensor - Indicates entrent magnetic bond.

DYN2 Dynastat Force Sensor - For the 3121C and 3121C2.

ETR Egress Sensor Omitted - For externally triggered egress.

KSO Keyswitch Omitted - In favor of separate remote keyswitch.

(Suggested for door heights over 8 ft.) See page 47.

LP Low Power Consumption Coil - 12V only (Single Lock)
Low Power Consumption Coils - 12V only (Double lock)
SF Special Finish - Standard finish US28. Special anodized

finishes see page 56.



3101C-TJ101 (Gen II)

BUILDING CODE SOFTWARE OPTIONS (FACTORY INSTALLED)

BOCA	For operation in compliance with BOCA Code.
UBC	For operation in compliance with UBC Code.
CHGO	For operation in compliance with Chicago Building Code.

Notes: • BPM option not available with the KSO option.

* LP option may not be combined with DYN option.

3101C SERIES COMMON REPLACEMENT PARTS

300477	Door Sign only, 15 second delay verbiage.	
300478	Door Sign only, 30 second delay verbiage.	
301393	Egress Sensor Adjustment Wheel Kit.	
301424	"PULL" Door Sign, 3101C-TJ101-G2.	
301556	Mounting Hardware Kit, 3101C-G2.	
301047	Ribbon Interconnect Cable, 12" Length, 3121C-G2.	
301048	Ribbon Interconnect Cable, 36" Length, 3121C2-G2.	