

# 413MN and 423M Exit Switches

## Code Compliant Manual Release

**Code Compliant Manual Releasing Devices and Sensors**  
 423M and 413MN exit switches used together with the MD31D PIR sensor comply with manual releasing device and sensor device requirements for **Access-Controlled Egress Doors** per the following codes:

- IBC International Code 1008.1.3.4
- IFC International Fire Code 1008.1.3.4
- NFPA 101 Life Safety Code 7.2.1.6.2
- NFPA 1.15.5.3.2
- BOCA National Building Code 1017.4.5
- SBCCI Standard Building Code 1012.7
- **UL 294 LISTED**



423M



413MN

### FEATURES

- Fixed 30 Sec. Timer, Re-Triggerable
- Failsafe-Lock Releases when Power to Switch is Interrupted
- Green Illuminated Switch Button
- Push-to-Exit Sign
- CSFM Listed



### SPECIFICATIONS

<b>Timer Contacts</b>	DPDT 2 Amp @ 12/24VDC
<b>Wire Leads</b>	6", 20 Gauge
<b>1 Gang</b>	2 7/8" x 4 1/2" x 20 Ga.
<b>Narrow</b>	1 3/4" x 4 1/2" x 20 Ga.
<b>Weight</b>	0.4 lbs

PRODUCT SKU SAMPLE: 413MN U LT

### HOW TO ORDER

#### 1| SPECIFY MODEL

 <b>413MN</b>	Narrow, Integrated Electronic Timer, Fixed 30 Sec. Timer, 1 3/4"x1" Green Illuminated Button	<b>PUSH TO EXIT</b>
 <b>423M</b>	1 Gang, Integrated Electronic Timer, Fixed 30 Sec. Timer, 2" Green Illuminated Button	<b>PUSH TO EXIT</b>

#### 2| SPECIFY FINISHES

<b>U</b> 630 Stainless Steel - STANDARD	<b>D</b> 606 Dull Brass
<b>C</b> 605 Bright Brass	<b>P</b> 625 Bright Chrome
<b>H</b> 613 Oil Rubbed Bronze	

#### 3| SPECIFY LED OPTIONS

<b>L1G</b> 1 Green LED	<b>LT</b> Tri-color LED - Red, Green, Amber
<b>L1R</b> 1 Red LED	
<b>L2</b> 1 Red, 1 Green LED	



