


6000 Series Monitor Panels



6010



6020

6000 Monitor Panels provide bi-color LED's, red/green, operating on 12 or 24 VDC. Mounted on brushed stainless steel US32D switch plate.

MODEL	PRODUCT	WEIGHT
6010	One Bi-Color LED, Red/Green, 12/24VDC	.2 Lbs.
6020	Two Bi-Color LED's, Red/Green, 12/24VDC	.3 Lbs.

OPTIONS

DBL-AUD	Two Gang Plate with Audible Sounder - 1-28VDC.
NR	Narrow Plate - 1-3/4" wide, substitute.
SF	Special Finishes - Standard finish US32D. See page 52.

6000 Series Pushbuttons



6115



6125

6000 Series controls provide a popular selection of request to exit (REX) controls in multiple switching configurations. Monitoring is accomplished with optional illuminated or audible indicators. Standard finish - Brushed Stainless Steel US32D. Standard button color - Green. All switches SPDT contacts.



6135



6145

MODEL	PRODUCT	WEIGHT
6115M	One Pushbutton, 1 Gang, Momentary	.3 Lbs.
6115A	One Pushbutton, 1 Gang, Alternate Action	.3 Lbs.
6125M	Two Pushbuttons, 1 Gang, Momentary	.4 Lbs.
6125A	Two Pushbuttons, 1 Gang, Alternate Action	.4 Lbs.
6135M	Three Pushbuttons, 1 Gang, Momentary	.5 Lbs.
6135A	Three Pushbuttons, 1 Gang, Alternate Action	.5 Lbs.
6145M	Four Pushbuttons, 2 Gang, Momentary	.6 Lbs.
6145A	Four Pushbuttons, 2 Gang, Alternate Action	.6 Lbs.

OPTIONS

AUD	Audible Sounder - 1-28VDC (Requires DBL option).
DBL	Two Gang Plate - 4-9/16" wide, for options.
ILM	Illuminated Pushbutton - Specify 12 or 24VDC (per button).
LED	Bi-Color LED - Red/Green, 12/24VDC.
NR	Narrow Plate - 1-3/4" wide, substitute.
P2	Additional set of SPDT contacts (per button).
SF	Special Finishes - See page 56.
WPC	Weather Proof Cover - For single gang 6115 only.
ATS	Anti-Tamper Switch