## Access/Egress Controls





6171



6172



6173



6174



6175



6176

## **6170 Series Weatherproof Pushbutton**

Commercial grade weatherproof pushbutton. Button is 3/4" diameter white thermoplastic raised dome, rated IP68 water-tight (up to 1 meter), IP64 moisture-proof, and IP64 dust-tight. Single gang plate, includes weatherproof faceplate gasket and tamper-resistant faceplate screws. Green LED backlit button on all models, field selectable 12/24 VDC. All models are momentary-action SPDT-Double Break (FORM Z)

Contact Rating: 3 A @ 115VAC

Operating temperature rating: -67°F to +185°F

MODEL	PRODUCT	WEIGHT
6171 6172 6173 6174 6175 6176	Blank Faceplate Faceplate Silkscreened "EXIT" Faceplate Silkscreened "EXIT/SALIDA" Faceplate Silkscreened "EXIT/SORTIE" Faceplate Silkscreened "PUSH TO UNLOCK" Faceplate Silkscreened "PUSH TO OPEN"	.3 Lbs. .3 Lbs. .3 Lbs. .3 Lbs. .3 Lbs. .3 Lbs.

OP.	TIC	)NS
-----	-----	-----

BBX CSF	Weatherproof Surface Back Box - 2 <sup>5</sup> / <sub>8</sub> " deep Custom Silkscreened Faceplate - Consult
SF	factory for price and delivery Special Finish Faceplate - US32D standard,
ATS	see page 56 for other finishes Anti-Tamper Switch