

# 6200R - PANIC & 6200F - FIRE LABELED RIM EXIT DEVICE MODELS FOR 2-1/4" BACKSET FROM STOP

6200 SERIES EXIT DEVICES WITH STRIKE 629036

TEMPLATE: 629310

REV. 4 2/6/18

<b>MACHINE SCREWS:</b> USE #7 OR 13/64" [5.1] DRILL AND 1/4-20 TAP
<b>WOOD DOOR/FRAME SCREWS:</b> USE 5/32" [4.0] DRILL
<b>SEX NUTS:</b> USE 3/8" [9.5] DRILL

**NOTES:**

1. VERIFY PRINTED TO SCALE.
2. DIMENSIONS IN **INCHES** [MM].
3. CAUTION: SEX NUTS MAY BE REQUIRED FOR UNREINFORCED DOORS OR COMPOSITE FIRE DOORS. CONSULT DOOR MANUFACTURER'S RECOMMENDATIONS.
4. SEE TRIM TEMPLATE (IF APPLICABLE) FOR RELATED MACHINING DETAILS.
5. DIMENSION "X" MEASURES 31-1/4" [793.8] UNCUT FOR 36" [914.4] DOORS.  
  
DIMENSION "X" MEASURES 43-1/4" [1098.6] UNCUT FOR 48" [1219.2] DOORS.
6. RECOMMENDED DIMENSION FROM FINISHED FLOOR MAY VARY BY APPLICATION, CODES OR BUILDING SPECIFICATIONS.
7. ALWAYS CHECK PDQ WEBSITE FOR MOST RECENT REVISION AT WWW.PDQLOCKS.COM

