

# 6202R/RA/RF/RFA - NARROW STILE PANIC & FIRE RATED RIM EXIT DEVICE MODELS

TEMPLATE: 629328

REV. 0 4/9/18

## 6202 SERIES EXIT DEVICES WITH 629036 STRIKE

<b>MACHINE SCREWS:</b> USE #7 OR 13/64" [5.1] DRILL AND 1/4-20 TAP
<b>WOOD DOOR/FRAME SCREWS:</b> USE 5/32" [4.0] DRILL
<b>SEX NUTS:</b> USE 3/8" [9.5] DRILL

**NOTES:**

1. VERIFY PRINTED TO SCALE.
2. DIMENSIONS IN **INCHES** [MM].
3. CAUTION: SEX NUTS MAY BE REQUIRED FOR UNREINFORCED DOORS OR COMPOSITE FIRE DOORS. CONSULT DOOR MANUFACTURER'S RECOMMENDATIONS.
4. SEE TRIM TEMPLATE (IF APPLICABLE) FOR RELATED MACHINING DETAILS.
5. DIMENSION "X" MEASURES 31-1/4" [793.8] UNCUT FOR 36" [914.4] DOORS.  
  
DIMENSION "X" MEASURES 43-1/4" [1098.6] UNCUT FOR 48" [1219.2] DOORS.
6. RECOMMENDED DIMENSION FROM FINISHED FLOOR MAY VARY BY APPLICATION, CODES OR BUILDING SPECIFICATIONS.
7. ALWAYS CHECK PDQ WEBSITE FOR MOST RECENT REVISION AT WWW.PDQLOCKS.COM

