



**Single Gang**



**Single Gang Recessed**



**Narrow**



**Narrow Recessed**

## 6700/6800 Series Pushplates

6700 & 6800 Series Pushplates are heavy duty egress controls machined from solid aluminum with engraved "PUSH TO EXIT" signage. Multiple switching configurations and finishes are available. Narrow recessed models are specifically designed for installation in aluminum store front frames, requiring minimal cut-out/preparation. All momentary models feature "all active" operation. Consult factory for special engraving.

Standard finish - Satin Aluminum US28

PTD Contact Rating: 10 A @ 125VAC

All Others: 6 A @ 125VAC

MODEL	PRODUCT	WEIGHT
<b>6700</b>	Single Gang 1-60 Sec. PTD, FORM Z	.7 Lbs.
<b>6710</b>	Single Gang A-A, SPDT	.7 Lbs.
<b>6720</b>	Single Gang A-A, DPDT	.8 Lbs.
<b>6730</b>	Single Gang MOM, SPDT	.7 Lbs.
<b>6740</b>	Single Gang MOM, DPDT	.8 Lbs.
<b>6750</b>	Single Gang, Recessed 1-60 Sec. PTD, FORM Z	.8 Lbs.
<b>6751</b>	Single Gang, Recessed A-A, SPDT	.8 Lbs.
<b>6752</b>	Single Gang, Recessed A-A, DPDT	.9 Lbs.
<b>6753</b>	Single Gang, Recessed MOM, SPDT	.8 Lbs.
<b>6754</b>	Single Gang, Recessed MOM, DPDT	.9 Lbs.
<b>6800</b>	Narrow 1-60 Sec. PTD, FORM Z	.6 Lbs.
<b>6810</b>	Narrow A-A, SPDT	.6 Lbs.
<b>6820</b>	Narrow A-A, DPDT	.7 Lbs.
<b>6830</b>	Narrow MOM, SPDT	.6 Lbs.
<b>6840</b>	Narrow MOM, DPDT	.7 Lbs.
<b>6850</b>	Narrow, Recessed 1-60 Sec. PTD, FORM Z	.7 Lbs.
<b>6851</b>	Narrow, Recessed A-A, SPDT	.7 Lbs.
<b>6852</b>	Narrow, Recessed A-A, DPDT	.8 Lbs.
<b>6853</b>	Narrow, Recessed MOM, SPDT	.7 Lbs.
<b>6854</b>	Narrow, Recessed MOM, DPDT	.8 Lbs.

## OPTIONS

**SF** Special Finishes - US28 standard. US3, US4, US10, US13, US10B, US19, US26 available.

## NOTES:

- A-A** Alternate Action (Maintained)
- MOM** Momentary Action
- SPDT** Single Pole Double Throw
- DPDT** Double Pole Double Throw
- PTD** Pneumatic Time Delay
- FORM Z** Single Pole Double Throw, Double Break

