Keyswitches





7001xCYL



7001xNRxCYL



7050

7000 Series Keyswitches

Keyswitches may be used to control electric locks, shunt or activate security panels, consoles or any similar requirements. The assembly is supplied with face plate, bracketry, cylinder locknut and one or two switches depending on model ordered. The user typically supplies the mortise cylinder and cam when master keying a system. Models 7050 & 7051 do not require a cylinder.

Switch contacts rated 6 Amps @ 125VAC and are available momentary or maintained, SPDT or DPDT. Switch assembly requires 1-1/2" depth clearance and is shipped on single, double or narrow gang plates.

Standard Finish: US32D

Cylinder Requirements: 1-1/8" or 1-1/4" Mortise Cylinder with "bat" type cam.

MODEL	PRODUCT	WEIGHT
7001	Maintained, (1) SPDT	.5 Lbs.
7002	Momentary, (1) SPDT	.5 Lbs.
7003	Maintained, (2) SPDT	.5 Lbs.
7004	Momentary, (2) SPDT	.5 Lbs.
7005	Momentary/Maintained, 1 Each SPDT	.5 Lbs.
7021	Maintained, (1) DPDT	.6 Lbs.
7022	Momentary, (1) DPDT	.6 Lbs.
7023	Maintained, (2) DPDT	.6 Lbs.
7024	Momentary, (2) DPDT	.6 Lbs.
7025	Momentary/Maintained, 1 Each DPDT	.7 Lbs.
7035	Elec. Time Delay, 0-60 Sec. SPDT, 2 Gang	1 Lbs.
7050	3101C Type, Momentary/Maintained	.5 Lbs.
7051	3101C Type, Momentary/Momentary	.5 Lbs.
7054	For Use With 3101C-TJ101-G2 and 3101C-G2 Series Locks Only	.5 Lbs.

Anti-Tamper Switch	
Audible Sounder - 1-28VDC (Requires DBL	
option).	
Mortise Cylinder - 1-1/4" long w/cam, 2 keys.	
Two Gang Plate - 4-9/16" wide, for options.	
Key, Extra (Order with CYL option)	
Bi-Color LED - Red/Green, 12/24VDC.	
Narrow Plate - 1-3/4" wide, substitute.	
Pushbutton - 6115A type (Requires DBL option).	
Pushbutton - 6115M type (Requires DBL option).	

Notes: * Not available with NR or WPC Options.

• Not available with NR or WPC Options, or on Model 7035.

Special Finishes - Standard finish US32D. See

Weatherproof Cover - Single Gang Only.

All cylinders keyed alike.

page 56.

~ Not available with WPC Option.

OPTIONS

~SF

WPC