





7075



7080



7086



7088

7075 Series Break Glass Exit Stations

Break glass assembly provides auxiliary method of releasing egress doors in an emergency situation. The assembly may be ordered in three versions: standard, standard with LED indicator or standard with audible.

Size: 6-3/4" x 4-1/2"

Contacts: SPDT-DB (FORM Z), MOM rated 6 Amps @ 125VAC

Furnished with 5 spare glass lenses.



MODEL	PRODUCT	WEIGHT
7075	Break Glass, Standard	.9 Lbs.
7076	Break Glass, with Bi-Color LED, Red/Green, 12/24VDC	.9 Lbs.
7077	Break Glass, with Audible Sounder, 1-28VDC, 1-28VDC	1.1 Lbs.
7078	Spare Contact Block, SPDT	.3 Lbs.
7079	Spare Lenses, 5 Pk.	.1 Lbs.

7080 Series Adjustable Time Delay Module

Compact, in-line time delay module provides an adjustable relock delay for an electric lock controlled by a momentary normally-closed access/egress device.

Size: 5/8"W x 2"L x 9/16"D

Input Power: 12-30 VAC/VDC, Contacts: SPDT rated 1 Amp @ 30VDC

Delay Adjustment Range: 0-60 Seconds

MODEL	PRODUCT	WEIGHT
7080	Adjustable Time Delay Module	.3 Lbs.

7086 Series Programmable Digital Timer

365 day/24 hour digital timer provides automated control of electric locks. Programmable for up to 50 weekly/daily events and 10 holidays. Operates on 12 or 24 VAC/VDC @ 0.05A.

Size: 3"W x 5.25"L x 1"D

Contacts: SPDT rated 10 Amps @ 120VAC

MODEL	PRODUCT	WEIGHT
7086	Programmable Digital Timer	.4 Lbs.

7088 Prewired Rectifier

MODEL	PRODUCT	WEIGHT
7088	1 Amp Prewired Rectifier Module	.2 Lbs.