# 7500 Series HiTower®

# Distributor LK Discount Code

#### HiTower® - Electric Frame Actuator Controlled Locksets

The HiTower utilizes SDC's original concept of utilizing an electric frame actuator to control a mechanical lock in the door, eliminating the cost and labor associated with a power transfer hinge and wires through the door.







#### HiTower® Z7500

- · SDC brand Grade 1 Heavy Duty lockset
- Field selectable function, Locked outside only or both sides

## HiTower® CONVERSIONS

Distributors provide a new mechanical lock brand of choice to the factory for conversion to LISTED

**Electrically Controlled Single** US Point Locks or Latches 3 Hr A Label Fire Rated Doors

an electric frame actuator controlled lockset



#### SPECIFY SOURCE OF MORTISE LOCK

HiTower® Pro - SDC supplied mortise lock and electric frame actuator, complete with lever trim (Cylinder not included)

**Z** SDC lockset

**ZR** SDC Retrofit lockset, replaces discontinued 5000/6000 series

**ZY** SDC retrofit lockset replaces SDC modifications of discontinued manufacturer models: Falcon-LM581; Sargent-7704/7705; Corbin-9557L/2257; Russwin- 7059L; Arrow-1600EW; Yale-8705; Almet-5007; Best-35HEW

### HiTower® Mod - SDC supplied Schlage mortise lock and electric frame actuator, less lever trim

ZS Schlage L9080

HiTower® Mod - Distributors supply SDC with the mortise lock body and armored front (less trim) for modification. SDC returns the modified lock body with an electric actuator. Upon installation, two lever return spring cages (supplied by distributor) are required for proper operation.



Α	Falcon*	MA581	P	Yale	8805
D	Sargent	8204	R	Schlage Retro	L9080 (replaces 5000 series)
Н	Hager	3880	s	Schlage	L9080
ı	Corbin/Russwin	2057	Т	Best	35 HEW and 45H
N	Arrow	B12	U	Dorma	Consult Factory
0	Yale	7130F-L5 Exit device	٧	Marks	5EW



# SPECIFY FUNCTION

7530 Locked both sides. Unlocked by access control, remote control and key from either side, failsafe

Locked outside only. Unlocked by access control, remote control, outside key and inside lever, failsafe 7550

7560 Locked both sides. Unlocked by access control, remote control and key from either side, failsecure

7570 Locked outside only. Unlocked by access control, remote control, outside key and inside lever, failsecure







GF



**SPECIFY HAND** 





B 24VAC 0.5 Amps

C 24VDC 0.5 Amps

**OPTIONS** 

Extra Narrow failsafe actuator +Failsecure actuator for 1-1/4" to 1-1/2" face frames

for 2" face frames G 115VAC 0.2 Amps H 24VAC 0.5 Amps J 24VDC 0.5 Amps

see page 39 for pricing

add to list

add to list

+ Fail Secure Actuator Available with Z or S lockset only. Special strike preparation required for S7560/7570.

115VAC 0.2 Amps

24VAC 0.5 Amps

24VDC 0.5 Amps

	0
The state of the s	4
E	EE





NE	
0	

	0			
6	8			9
	N	ΙE	0	

6		
2	-	
0	7E	

SPECIFY	FINISH	FUR Z,	∠K, .	∠Y, ∠	<u> </u>	JNL	١
<b>Q</b> 626 Dull	Chrome	(standa	rd)				

C 605 Bright Brass	56.00	<b>G</b> 612 Dull Bronze	56.00	<b>S</b> 629 Bright Stainless Steel <b>56.00</b>
<b>D</b> 606 Dull Brass	56.00	H 613 Oil Rubbed Bronze	56.00	U 630 Dull Stainless Steel <b>56.00</b>
F 611 Bright Bronze	56.00	P 625 Bright Chrome	56.00	

Ε

Lock	status	and	wire	harness

L Latch status switch, SPDT, 5 Amps @ 30VDC 67.00 S Latch and deadlock status, 3 Amps @ 30VDC 112.00

	•				
SP	ECIFY LEVER TRIM FOR Z, ZR & ZY		工		add to list
G	Galaxy with rose	N/C	GE	Galaxy with escutcheon	108.00
E	Eclipse with rose	N/C	EE	Eclipse with escutcheon	108.00
N	Nova with rose	N/C	NE	Nova with escutcheon	108.00
07	Schlage style with SDC B rose	N/C	07E	Schlage style with SDC escutcheor	108.00

HiTower® PRO			AND FUNC		stributor nt Code LK LIS
	Sources Z,	ZR, ZY: SD	C supplied - S	SDC lever trim, mortise lock and electric frame actuator.	
	SOURCE/FU	NCTION			
	<b>Z</b> 7530	SDC	Failsafe, lock	ked both sides with rose trim	782.00
	<b>Z</b> 7550	SDC	Failsafe, lock	ked outside only with rose trim	771.00
	<b>Z</b> 7560	SDC	Failsecure, Ic	ocked Both sides with rose trim	948.00
	<b>Z</b> 7570	SDC	Failsecure, Ic	ocked outside only with rose trim	938.00
	ZY7530		· ·	scontinued lock models, see page 39 for details) ked both sides with rose trim	782.00
	<b>ZY</b> 7550		· ·	scontinued lock models, see page 39 for details) ked outside only with rose trim	771.00
	ZR7530	SDC	(Replaces 50	2000 series) Failsafe, locked both sides with rose trim	894.00
	ZR7550	SDC	(Replaces 50	2000 series) Failsafe, locked outside only with rose trim	881.00
	ZR7560	SDC	(Replaces 60	000 series) Failsecure, locked both sides with rose trim	948.00
	ZR7570	SDC	(Replaces 60	000 series) Failsecure, locked outside only with rose trim	938.00
	(Actuator typ	oe D, E, F, on	, , ,	aator for 1-1/4" to 1-1/2" frames. able with ZR or failsecure 7560 and 7570	Add 134.00
	Rose Trim				N/C
	Escutcheor	n trim			Add 112.00
HiTower® MOD		d - Schlage L	-	der, no returns, no cancellation	
	ZS7530	Schlage F	-ailsafe, locke	ed both sides	1,924.00
	ZS7550	Schlage F	ailsafe, locke	ed outside only	1,924.00
	SOURCE/FUN A, D, H, I, N,	NCTION		chanical lock for modification, SDC supplied Electric frame a  Failsafe, locked both sides	532.00
	A, D, H, I, N,			Failsafe, locked outside only	494.00
	S7560	, 0, P, 3, 1,	U, V 1550	Failsecure . locked both sides (5.75" Strike plate)	693.00
				, , , , , , , , , , , , , , , , , , , ,	093.00
	S7570			Failsecure, locked outside only (5.75" Strike plate)	000.00
	Extra Narro				683.00 134.00
		e D, E, F only	y page 39) Fo	or 1-1/4" to 1-1/2" frames. Special strike prep required.	
HiTower <sup>®</sup> MOD	(Actuator type Not available <b>Source R</b> (se	e D, E, F only with failsecu ee page 38)	y page 39) Fo ire 7560 and	or 1-1/4" to 1-1/2" frames. Special strike prep required.	134.00
HiTower <sup>®</sup> MOD	(Actuator type Not available <b>Source R</b> (se	e D, E, F only with failsecu ee page 38) upplied - Sch	y page 39) Fo ire 7560 and	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570	134.00
HiTower <sup>®</sup> MOD	(Actuator type Not available Source R (se Distributor su	e D, E, F only with failsecu ee page 38) upplied - Sch	y page 39) Fo ire 7560 and lage L9080 n	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570	134.00
HiTower <sup>®</sup> MOD	(Actuator type Not available Source R (se Distributor su SOURCE/FUN	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces	y page 39) Fo ire 7560 and lage L9080 n 5000 series)	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram	134.00
HiTower® MOD	(Actuator type Not available Source R (see Distributor su SOURCE/FUN R7530	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces	y page 39) Fo ire 7560 and lage L9080 n 5000 series)	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides	134.00 ne actuator 588.00 555.00
CCESSORIES	(Actuator type Not available Source R (se Distributor su SOURCE/FUN R7530 R7550	e D, E, F only with failsecu ee page 38) applied - Sch NCTION (Replaces (Replaces	y page 39) Fo ire 7560 and lage L9080 n 5000 series) 5000 series)	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00
CCESSORIES C-10 Socket connec	(Actuator type Not available  Source R (see Distributor su  SOURCE/FUN  R7530  R7550  ctors with 10 ft.	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces (Replaces)	y page 39) Four page 39) Four 7560 and page L9080 in 5000 series) four series only	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00 t
CCESSORIES C-10 Socket connect C-10-5 Socket connect	(Actuator type Not available Source R (se Distributor su SOURCE/FUN R7530 R7550  ctors with 10 ft.	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces and Cable, power cable for po	y page 39) Four page 39) Four 7560 and page L9080 in 5000 series) for wiring only ower and optical page 39) Four page 39	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00
C-10 Socket connect C-10-5 Socket connect lectrical back boxes for	(Actuator type Not available Source R (se Distributor su SOURCE/FUN R7530 R7550  ctors with 10 ft.	e D, E, F only with failsecu ee page 38) applied - Sch NCTION (Replaces (Replaces) cable, power cable for po	y page 39) Four 7560 and lage L9080 n 5000 series) er wiring only ower and optionduit knoc	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00 t
CCESSORIES  C-10 Socket connect C-10-5 Socket connect lectrical back boxes for 7500EB-S For standar	(Actuator type Not available  Source R (se Distributor su SOURCE/FUN R7530 R7550  Cotors with 10 ft. Cotors with 10 ft. Cotors with 10 ft. Cotors make actual or actuator in 1	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces and Cable, power cable for positors with co-3/4" or 2" fa	y page 39) Four page 39) Four 7560 and series) 5000 series) Four wiring only ower and optionduit knocace frame	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00 t
CCESSORIES  C-10 Socket connect C-10-5 Socket connect lectrical back boxes for 7500EB-S For standar	(Actuator type Not available Source R (se Distributor su SOURCE/FUN R7530 R7550  ctors with 10 ft. ctors with 10 ft. or frame actual	e D, E, F only with failsecu ee page 38) upplied - Sch NCTION (Replaces and Cable, power cable for positors with co-3/4" or 2" fa	y page 39) Four page 39) Four 7560 and series) 5000 series) Four wiring only ower and optionduit knocace frame	or 1-1/4" to 1-1/2" frames. Special strike prep required. 7570  mechanical lock for modification. SDC supplied Electric fram Failsafe, locked both sides Failsafe, locked outside only  Add to Lis	134.00 ne actuator 588.00 555.00 t 67.00 86.00