



918



500 user codes, 1 to 6 digits in length, 4 outputs, 2 relay and 2 solid state outputs timed or latching (on/off). Assign entry PIN's to relays 1 and/or 2. Tactile keys with selectable audible volume for key depression or output activation. LED Status: Access, lockout. Timed anti-passback. Keypad tamper lockout. Request-to-Exit/Enter input. Indoor blue backlit, moisture resistant keypad. Thick S.S. faceplate 3/32" (2mm).

ELECTRICAL SPECIFICATIONS

Voltage	12/24 VAC/DC — 5-16 VDC for Wiegand
Current	30mA typical, 150mA maximum - 60mA max for Wiegand
Outputs (918)	Relay 1 - SPDT 5 Amps @ 30VDC, Relay 2 - SPDT 2 Amps @ 30VDC, Switch to Common Outputs 3 & 4 - 100mA @ 30VDC
Dimensions	3"W x 4-3/4"H x 1-1/2"D (1/4" Wall projection)



918W



- 918** Stand alone digital indoor keypad **174.00**
- 918W** Indoor digital keypad, Wiegand output **174.00**

SPECIFY FINISH Add to List

U	630 Brushed Stainless Steel (standard)	N/C	H	613 Oil Rubbed Bronze	67.00
C	605 Bright Brass	67.00	P	625 Bright Chrome	67.00
D	606 Dull Brass	67.00			

OPTIONS Add to List

- TR12** Plug in power supply (optional) **81.00**
120 VAC primary, Output: 12VDC @ 1Amp, Secondary screw terminals



900-PS with 918 Keypad

ACCESSORIES Add to List

- 900-PS** Privacy Shroud for stand alone digital keypads 918. Ensure security from spying eyes. **107.00**