



Closer Sizing Chart	
Door Width	Closer
Up to 42" - (1.07 mm.)	406STP
43" to 48" - (1.09 mm to 1.22 mm)	406EP-STP

Preparation for Fasteners		
Fasteners	Door or Frame	Drill
#14 type "A" Sheet Metal Screw	Wood	7/32" (5.5 mm.)
1/4-20 machine screw	Metal	#7 (.201" dia.) or 5.10 mm. drill: tap: 1/4-20
SNB (optional)	Hollow Metal	9/32" (7.00 mm.) thru; 3/8" (9.50 mm.) door face opposite to closer
	Aluminum or Wood	3/8" (9.50 mm.) thru
TBGN (optional)	All	9/32" (7.00 mm.) thru; 3/8" (9.50 mm.) dia. x 3/8" (10 mm.) deep, door face opposite to closer

Notes:

1. Do not scale drawing
2. Right hand door shown.
3. Dimensions shown in inches (mm.).

Experience a safer
and more open world

406STP or 406EP-STP Series Closer
Slide Track Closer for 90° Wall Pocket Installation
For Pocket Depths 2-1/4" to 4-1/4" (57mm to 108mm)

Template Number:
80-7344-0505-010
Sheet: 1 of 1
Date: 01/24

ASSA ABLOY
1-800-438-1951
www.assaabloy.com