


nexTouch®

Sectional Mortise Keypad Lock



Yale® nexTouch®

Sectional Mortise Keypad Lock



Technical Specifications

Door Specifications: Fits into the standard mortise door prep

Backset: 2-3/4" (70mm) standard backset

Door Thickness: 1-3/4" (44mm) door thickness standard; please specify for other

door thicknesses

Handing: Field reversible

Latchbolt: 3/4" spring latchbolt standard, 1" throw deadlocking latchbolt optional

Strike: Curved lip strike with 1-1/4" (32 mm) lip length standard

Cylinder: Accepts conventional, interchangeable core, security and high security

cylinders, and other manufacturers' keyway cylinders

ANSI/BHMA: Certified ANSI/BHMA Grade 1

UL/cUL: Functions are UL - cUL Fire Listed for use on fire doors having a rating up to

and including 3-hours

Warranty: 3-year electronic and mechanical, 1-year finish

Environmental Specifications: Operating temperature: -40°F to +140°F (-40°C to

 $+60\ensuremath{^{\circ}\text{C}})$ at 95% relative humidity when used with an external power supply

 $\textbf{Power Source:} \ 4 \ \text{AA alkaline batteries (included) with optional hardwire input for}$

9VDC external power; 9V battery power backup on keypad

Interface: Capacitive touchscreen or pushbutton keypad

User Codes: Up to 500 unique user codes

Finishes

ANSI/BHMA Code	Finish Description
605 (US3)	Bright Brass, Clear Coated
613E (US10BE)	Dark Oxidized Satin Bronze - equivalent
626 (US26D)	Satin Chrome Plated
BSP	Black Suede Powder Coat



Levers

ARCADIA ARR



AUGUSTA AUR



CARMEL CRR



JEFFERSON JNR



MONROE MOR



PACIFIC BEACH PBR



PINEHURST PNR



VIRGINIA VNR



Contact your local ASSA ABLOY Door Security Solutions team or **visit yalecommercial.com** Yale Locks & Hardware • 225 Episcopal Road, Berlin, CT 06037-4004 Tel: 1-800-438-1951 • Fax: 1-800-338-0965 • yalecommercial.com

Yale Commercial is a business associated with ASSA ABLOY Access and Egress Hardware Group, Inc., an ASSA ABLOY Group company. Copyright © 2018-2023, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.