

This product is now proudly being offered under the ASSA ABLOY ACCENTRA® brand, effective June 20, 2023. Visit YaleCommercial.com/en/Today for support and information.





Opening					
Stop	Dim. A	Dim. B	Dim. C		
90°	11-1/4	9-1/8	10-1/8		
95°	10-1/2	8-3/8	9-3/8		
100°	9-3/4	7-5/8	8-5/8		
105°	9-1/8	7	8		
110°	8-1/2	6-3/8	7-3/8		
115°	7-7/8	5-3/4	6-3/4		
	90° 95° 100° 105° 110°	Stop Dim. A 90° 11-1/4 95° 10-1/2 100° 9-3/4 105° 9-1/8 110° 8-1/2	Stop Dim. A Dim. B 90° 11-1/4 9-1/8 95° 10-1/2 8-3/8 100° 9-3/4 7-5/8 105° 9-1/8 7 110° 8-1/2 6-3/8		

Notes:

- Do not scale drawing
- 2. Left hand door shown.
- 3. Dimensions shown in inches. See conversion chart for metric dimensions.
- 4. Units with a "T" suffix have a hold-open arm and cannot be installed on fire doors.
- Door swing may be limited by door, frame, wall or hardware conditions.
- Hollow metal doors require channel or box type reinforcement when thru-bolt mount is specified for closers.
- Sex bolts and bolts required to mount closer on steel covered composite type, sheet metal type or hollow metal type fire doors provided without reinforcements.
- Minimum thickness recommended for reinforcements is hollow metal doors and frame: .1046" (2.66 mm.) unless otherwise noted.

Metric Conversion							
inches	mm.	inches	mm.	inches	mm.	inches	mm.
1/2"	12.7	4"	101.6	7-7/8"	200	9-3/8"	238
3/4"	19.1	5-3/4"	146	8"	203	9-3/4"	248
1-1/2"	38.1	6-3/8"	162	8-3/8"	213	10-1/8"	257
1-5/8"	41	6-3/4"	171	8-1/2"	216	10-1/2"	267
1-3/4"	44	7"	177.8	8-5/8"	219	11-1/4"	286
2-1/2"	63.5	7-3/8"	187	9-1/16"	230.2		
2-3/4"	69.9	7-5/8"	194	9-1/8"	232		

op view lypical installati	ion
Left Door Right Door	
∠ Stop	Stop \(\)
— "S" and "L" — Valves	
Pinion Flat Hold Open Installation Sho	Pinion Flat

Tam Minus Trustani Imakalinki am

Preparation for Fasteners				
Fasteners	Frame	Door	Drill	
#14 type "A" Sheet Metal Screw	Wood	None	7/32" (5.5 mm.)	
1/4-20 machine screw	Metal	None	#7 (.201" dia.) or 5.10 mm. drill 1/4-20 tap	
SNB No	None	Hollow Metal	9/32" (7.00 mm.) thru; 3/8" (9.50 mm.) door face opposite to closer	
	none	Aluminum or Wood	3/8" (9.50 mm.) thru	

Experience a safer and more open world

Copyright © 2001, 2023, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

5120 or 5120T Series HolderStop Door Closers Parallel Arm Application with 293L Flush Transom Bracket and with or without 214 Drop Plate Stop Only or Stop with Hold Open (Hold Open Indicated by a "T" Suffix) Closer sizes 1, 1BF, 2, 3, 4, 5, or 6

Template Number: 7350-1306 Sheet: 1 of 1

Date: 12/23

ASSA ABLOY

1-800-438-1951 www.assaabloy.com