
Opening	Dim. "A"
To 100°	7-5/8 (194)
100° to 120°	6-5/8 (168)
120° to 150°	4-5/8 (117)
150° to 180°	4-1/8 (105)

This template covers the following series of door closers:

400	4400
TJ400	TJ4400
TJĹ400	TJĹ4400
TJS400	TJS4400

**Caution:** Door swing may be limited by door, frame, wall or hardware conditions.



## **Q** Hinge or Pivot

## Notes:

- 1. Do not scale drawing.
- 2. Left hand door shown.
- 3. Dimensions are in inches (mm).
- 4. Hollow metal doors require channel or box type reinforcement when thru bolt mount is specified.
- 5. Sex bolts may be required for wood or plastic faced fire door mounting.
- 6. Minimum thickness recommended for reinforcements in hollow metal doors and frames: 0.1046" (2.66mm) unless otherwise noted.
- \* Always use frame or transom rabbet as reference plane, not bottom of stop.

	Preparation for Fasteners			
	Fasteners	Door or Frame	Drill Sizes	
7	#14 type "A" S.M. Screw	Wood	7/32" (5.5mm)	
	Arm: 1-1/4" (32mm) Closer: 2-3/4" (70mm)	Aluminum		
5	1/4-20 machine screw	Metal	drill: #7 (.201") tap: 1/4-20	
-	Sex nuts and bolts	Hollow Metal	9/32" (7.00mm) thru; 3/8" (9.50mm) on door or transom face opposite to closer	
1 :		Aluminum or Wood	3/8" (9.50mm) thru	
Optiona	Thru bolts and grommet nuts	All	9/32" (7.00mm) thru; 3/8" (9.50mm) dia. x 3/8" (10mm) deep on door or transom face opposite to closer	

Experience a safer and more open world

Copyright @ 2004, 2023, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

(TJ), (TJL), (TJS) 400 Series Door Closers - Sized 2 thru 6 (TJ), (TJL), (TJS) 4400 Series Door Closers -Multi-Size 1 to 6

Top Jamb Non-Hold Open Arm with 487 Drop Plate Drop Application for 2" (51) Ceiling Clearance or O.H. Holder Clearance

Template Number: 7344-0152

Sheet: 1 of 1 Date: 12/23 **ASSA ABLOY** 

1-855-557-5078 www.assaabloy.com