



Notes:

- Do not scale drawing.
- Left hand door shown.
- Dimensions are in inches (mm).
- Caution: Hollow-metal doors require channel or box-type reinforcement.
- UNI-1910 Series closers have a hold open arm feature and are not permitted to be used on fire door assemblies.

Preparation for Fasteners			
Fasteners	Application	Door or Frame	Drill Sizes
Sex nuts and bolts	Closer Drop Plate 2022 Bracket	Hollow Metal	9/32" (7.00mm) through 3/8" (9.50mm) door face opposite to closer
		Aluminum or Wood	3/8" (9.50mm) through

Door Opening Angle		Dimensions★			
Hold Open★★	Dead Stop	Butts and Offset Pivots		Center Pivots	
		A	B	A	B
85°	90°	16-3/8 (416)	15-3/8 (391)	17-1/8 (435)	16-1/8 (410)
90°	95°	15-1/2 (394)	14-1/2 (368)	16-1/4 (413)	15-1/4 (387)
95°	100°	14-3/4 (375)	13-3/4 (349)	15-1/2 (394)	14-1/2 (368)
100°	105°	14-1/8 (359)	13-1/8 (333)	14-7/8 (378)	13-7/8 (352)
105°	110°	13-5/8 (346)	12-5/8 (321)	14-3/8 (365)	13-3/8 (340)
110°	115°	13-1/8 (333)	12-1/8 (308)	13-7/8 (352)	12-7/8 (327)

★ "A" and "B" dimensions measured from centerline of hinge or pivot.
★★ Door must be free to swing 5° beyond hold-open position.

UNI-1900 Series Closer - Non Hold Open/Stop Arm
UNI-1910 Series Closer - Hold Open/Stop Arm
Flush Transom Parallel Arm with 589L Bracket
Doors 42" – 48" (1.05-1.20m) Wide

Parallel Arm Installation Template –
Flush Partitions
Stop Only or Hold Open Unitrol
Door Closer
With or Without 1988 Drop Plate

Yale®
 Yale Commercial Locks and Hardware
 www.yalecommercial.com
 TEMPLATE NUMBER **7319-1356** DATE **8-99**