



Notes:

- Do not scale drawing.
- All dimensions shown in inches (mm).
- Left hand door shown.
- Caution: Hollow metal doors require channel or box type reinforcement.
- UNI-1400 and UNI-4410 Series door closers have a hold open arm feature and are not permitted to be used on fire door assemblies.

| Preparation for Fasteners | | | |
|--------------------------------|---------------------------------|------------------|---|
| Fasteners | Application | Door or Frame | Drill Sizes |
| Sex nuts and bolts | Closer, drop plate 2022 bracket | Hollow metal | 9/32" (7.00mm) through 3/8" (9.50mm) door face opposite to closer |
| | | Aluminum or Wood | 3/8" (9.50mm) through |
| Through bolts and grommet nuts | Optional | All | 9/32" (7.00mm) through 3/8" (9.50mm) dia. x 3/8" (10mm) deep door face opposite to closer |

| Door Opening Angle | | Dimensions ★ | | | | | | | |
|--------------------|-----------|-------------------------|-----|-------------|-----|---------------|-----|-------------|-----|
| Hold Open ★★ | Dead Stop | Butts and Offset Pivots | | | | Center Pivots | | | |
| | | Dimension A | | Dimension B | | Dimension A | | Dimension B | |
| | | Inches | mm | Inches | mm | Inches | mm | Inches | mm |
| 85° | 90° | 10-1/4 | 260 | 10-5/8 | 270 | 11-1/4 | 286 | 11-5/8 | 295 |
| 90° | 95° | 9-5/8 | 244 | 10 | 254 | 10-1/2 | 267 | 10-7/8 | 276 |
| 95° | 100° | 9-1/8 | 232 | 9-1/2 | 241 | 10 | 254 | 10-3/8 | 264 |
| 100° | 105° | 8-3/4 | 222 | 9-1/8 | 232 | 9-1/2 | 241 | 9-7/8 | 251 |
| 105° | 110° | 8-3/8 | 213 | 8-3/4 | 222 | 9-1/8 | 232 | 9-1/2 | 241 |
| 110° | 115° | 8 | 203 | 8-3/8 | 213 | 8-3/4 | 222 | 9-1/8 | 232 |

★ "A" and "B" dimensions measured from centerline of hinge or pivot.
 ★★ Door must be free to swing up to 5° beyond hold open position.

Experience a safer and more open world

Copyright © 2004, 2024 ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

UNI-400,UNI-4400 Series Non Hold Open/Stop Arm
UNI-1400,UNI-4410 Series Hold Open/Stop Arm

Closer Sizes 0 Multi-size 1-6 or Sizes 2, 3, 4, 5, or 6
 Flush Transom Parallel Arm with 589L Bracket for Door 28"-32" (0.70-0.80m) Wide
 Parallel Arm Installation Template — Flush Partitions
 Stop Only or Hold Open Nitrol
 Backcheck or Delayed Action Door Closer

Template Number:
7344-1354
 Sheet: 1 of 1
 Date: 01/24

ASSA ABLOY

1-855-557-5078
 www.assaabloy.com