



# YPL Series

## Cylindrical Indicator Lock



**ACCENTRA**

---

**ASSA ABLOY**

ASSA ABLOY is transitioning the Yale Commercial brand to ACCENTRA. This affects only the brand name; the products and product numbers will remain unchanged. Prior to May 20, 2024, products may be shipped either as Yale Commercial brand or ACCENTRA brand. Products shipping after May 20, 2024, will be branded ACCENTRA.



## Contents

Features .....	3
How to Order, Finishes, Lever Trim .....	4
Function .....	5
Indicator Options .....	5
Latchbolts .....	6
Strikes .....	6
Technical Specifications and Listings .....	7

## Increased Privacy

The cylindrical lock indicator visually displays door status; whether the door is locked or unlocked, thus eliminating potentially embarrassing situations and providing a peace of mind.

Using a standard bored lock door prep, this indicator lock is ideal for new construction or retrofit applications.



# Features

## Features

- Red or Green window display with padlock icon for visual door status
- Cylindrical lock construction for durability and longevity in high use applications
- Patent pending design
- Privacy function (F76A) with push button lock and for automatic unlock when inside lever is pushed down
- One motion for egress
- Coin turn for emergency access
- Through-bolted for robust operation
- Ideal for retrofit
- Lever returns to within 1/2" of door face

## Applications

- Office buildings
- Restaurants
- Schools
- Hospitals
- Warehouses
- Airports
- Places of Worship
- Convenience Stores
- Gas Stations
- Travel Centers



## Specifications

<b>Door Prep</b>	ANSI/BHMA A156.115
<b>Door Thickness</b>	1-3/4" (44mm) standard, accommodates 1-3/8" (35mm) with adapter plate kit (ordered separately, specify APK-2)
<b>Backset</b>	2-3/4" (70mm) standard, 2-3/8" (60mm) optional
<b>Handing</b>	Non-handed
<b>Latchbolt</b>	Plain, 2-3/4" (70mm) backset x 1-1/8" (29mm) square corner front with 1/2" (13mm) throw standard, 2-3/8" (60mm) x 1" (25mm) optional
<b>Strike</b>	ANSI strike 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center
<b>ANSI/BHMA</b>	2-3/4" Backset: Certified Grade 1, ANSI/BHMA A156.2, Series 4000 2-3/8" Backset: Certified Grade 2, ANSI/BHMA A156.2, Series 4000
<b>UL/cUL</b>	Listed for 3 hour fire doors
<b>Warranty</b>	3 years







# How To Order, Finishes, Lever Trim



## How To Order

Trim Design	Function	Finish
AU	YPL02	626


## Finishes

ANSI/BHMA Code Finish Description			
<b>605</b> Bright Brass, Clear Coated	<b>613E</b> Dark Oxidized Satin Bronze - equivalent	<b>626</b> Satin Chrome Plated	<b>BSP</b> Black Suede Powder Coat
			

## Lever Trim

### Augusta - AU

Lever: Cast Zinc  
Rose: Wrought Brass






# Functions

## YPL02 (F76A)

### Privacy Lock with Indicator

- Either lever operates latchbolt unless outside lever is locked by pushbutton inside.
- Pushbutton inside changes indicator display status outside.
- Rotating inside lever and/or closing door unlocks outside lever and changes indicator display status outside.
- Coin turn in outside lever for emergency access.
- Inside lever always active.
- Outside lever rigid when in locked position.




Outside

Inside

## Indicator Display

YPL02 locks are provided standard with a visual display that shows red with a closed shackle padlock for locked and green with an open shackle padlock for unlocked. The padlock icons are positioned in a manner that allows for the locks to be non-handed.



Other options may be available by special application, contact Customer Service for more information.


# Latchbolts



Model No. 693A supplied standard with all YPL02 locksets. Standard latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) beveled square front with a 2-3/4" (70mm) backset and a 1/2" (13mm) throw bolt. Optional 2-3/8" latchbolt available to order.

Model	Front	Backset	Throw	"W" Front Width	Latch Diameter
693A	Square	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
378PL	Square	2-3/8" (60mm)	1/2" (13mm)	1" (25mm)	7/8" (22mm)*

\*1/8" sleeve supplied to accommodate 1" preps.



# Strikes

<p><b>Model No. 497 ANSI Strike (Standard)</b></p> <p>For door and frames with ANSI/ BHMA A156.115 preparations 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center supplied standard. Other lip lengths available by special order. Available with optional 202 Strike Box. Specify 497 x 202.</p>	<p><b>Model No. 371 T-Strike</b></p> <p>2-3/4" x 1-1/8" x 1-1/4" (70mm x 29mm x 32mm) lip to center supplied standard. Other lip lengths available by special order. Wrought strike box supplied.</p>	<p><b>Model No. 70S Full Lip</b></p> <p>2-1/4" x 1-3/4" x 1-1/4" (57mm x 44mm x 32mm) lip to center with full lip anti-rattle tab.</p>	<p><b>Model No. 202 Strike Box</b></p> <p>Available to special order. Specify x 202.</p>

# Technical Specifications and Listings



## ADA

The YPL02 meets accessibility guidelines of the Americans with Disabilities Act and the requirements of the Uniform Federal Accessibility Standards and ANSI 117.1, all requiring ease of accessibility for the handicapped.



## ANSI/BHMA


2-3/4" Backset: Certified ANSI/BHMA A156.2, Series 4000 Grade 1.

2-3/8" Backset: Certified ANSI/BHMA A156.2, Series 4000 Grade 2.



## Door Thickness

The YPL02 installs on 1-3/4" thick doors standard. It can also be used on 1-3/8" thick doors by adding adapter plates. To order specify adapter plate kit model number APK-2.



APK-2

## Fire Listings



UL/cUL Listed for up to 3 hours

Note: Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Yale Locks and Hardware makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

## Installation

YPL02 Cylindrical locks conform to ANSI/BHMA Specifications A156.115 which cover hardware preparations for steel doors and steel frames and A156.115-W which cover hardware preparations for wood doors with wood or steel frames.

## Warranty

The YPL02 cylindrical lever lock carries a three-year warranty.



**Trusted every day**

**Phone**

1-855-557-5078

**Customer Service Email**

customerservice.yale@assaabloy.com

**Technical Product Support Email**

techsupport.yale@assaabloy.com

**Order Entry Email**

orders.yaleus@assaabloy.com

**Fax**

1-800-338-0965

**Website**

www.yalecommercial.com

## Contact Us

**U.S.A.**

**Yale Locks & Hardware**

Address: 225 Episcopal Road

Berlin, CT 06037-4004

Tel: 1-800-438-1951

Fax: 1-800-338-0965

yalecommercial.com

**Canada:**

**ASSA ABLOY Door Security Solutions Canada**

Address: 160 Four Valley Drive

Vaughan, Ontario L4K 4T9

Tel: 1-800-461-3007

Fax: 1-800-461-8989

assaabloydss.ca

**International:**

**ASSA ABLOY Americas International**

Tel: 1-905-821-7775

Fax: 1-905-821-1429

assaabloyai.com

**THE YALE BRAND**, with its unparalleled global reach and range of products, reassures more people in more countries than any other consumer locking solution.

**THE ASSA ABLOY GROUP** is the world's leading manufacturer and supplier of locking solutions, dedicated to satisfying end-user needs for security, safety and convenience.

Yale Commercial is a business associated with ASSA ABLOY Access and Egress Hardware Group, Inc., an ASSA ABLOY Group company. Copyright © 2022, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited. Patent pending and/or patent [www.assaabloydss.com/patents](http://www.assaabloydss.com/patents).