



NOTE 1: FOR SELF-TAPPING SCREWS:  
DRILL 1/8 DIA HOLE (4 PLCS)

FOR SEX BOLTS:  
REFER TO NOTE 2 FOR DRILL HOLE SIZES.

NOTE 2: UNLESS OTHERWISE SPECIFIED,  
FOR HOLLOW METAL DOOR: 4 HOLES  
ON OUTSIDE OF DOOR ARE 3/8 INCH  
DIAMETER AND INSIDE OF DOOR ARE  
7/32 INCH DIAMETER. FOR WOOD DOOR:  
4 HOLES 3/8 INCH DIAMETER THRU.

NOTE 3: WHEN BAR HEIGHT IS 36" OR MORE,  
DIVIDE BAR HEIGHT BY 2. OTHERWISE,  
USE 18" AS THE DIMENSION.

NOTE 4: FOR 3100T AND 3100W OMIT THE 4 LOWER  
MOUNTING HOLES FROM DOOR  
PREPARATION.

NOTE: IT IS RECOMMENDED THE MOUNTING  
HOLES BE PREPARED IN THE FIELD.

NOTE: REQUIRED DOOR UNDERCUT  
IS 1/4 FROM FINISHED  
FLOOR OR 1/8 FROM  
THRESHOLD

DIM A	DOOR OPENING WIDTH			
	30"	36"	42"	48"
	24 1/4	30 1/4	36 1/4	42 1/4

LHR PREPARATION SHOWN.  
SEE 10010 FOR RHR.

ADAMS RITE MANUFACTURING COMPANY  
POMONA, CA 91767

3100 SVR FIRE RATED LHR  
EXIT DEVICE  
WOOD OR HOLLOW METAL DOOR

ECN NO. 10189

NOTE: SEE MASTER SHEET 10001 FOR  
SUGGESTED REINFORCEMENT

TEMPLATE NO.:

10011-3

DATE:

06-15-01