

Model 600D



600 lbs Double Magnetic Lock

Specifications

- 600 lbs holding force per leaf
- Magnet size: 19-3/4" L x 1-7/8" H x 1" W
- Armature size: 7-1/4" L x 1-1/2" H x 5/8" W
- Operates on 12 or 24 VDC, selectable
- Low current draw: 400 mA at 12 VDC, 200 mA at 24 VDC
- Operating Temperature: +14 to +131F [-10 to +55C]

Features

- Instant release, no hysteresis
- Non-aluminum parts are plated to resist corrosion
- Built-in arc suppression
- Can be used with any access control system
- E-Z mount system, no special tools required
- Self drilling TEC screws
- Limited lifetime warranty

Options

- Clear anodized (US28) finish standard
- Duranodic (US40) finish available
- Dress covers in polished chrome and brass are available

Certifications & Listings

- UL 294 listed
- UL 10C fire rated
- CAN/ULC-S104 fire door conformant

Models

600D
600 lbs Double Door Magnetic Lock, 12 or 24 VDC, UL 10C and Canadian UL Listed

600DDURO
600 lbs Double Door Magnetic Lock, 12 or 24 VDC, US 40 Duranodic Finish, UL 10C and Canadian UL Listed

ALARMCONTROLS



ASSA ABLOY

Experience a safer
and more open world