



# Model 6131

## Single Zone Burglary Control with Entry/Exit Delay

### Specifications

- Regulated voltage output, 13.8 VDC and 300 mA
- Power input 12 VAC, Class 2 plug-in transformer (transformer supplied)
- 12 VDC, 4 Ah rechargeable battery (battery not supplied)
- Bell/siren output 12 VDC, 2.5A
- Dry contacts SPST normally-open rated 5A at 28 VDC
- Pre-alarm output 12 VDC for SC628 sonalert or equal
- Cabinet size: 11" H x 9" W x 3" D
- Closed circuit instant loop: Instant and Delay maximum loop resistance 1000 ohms
- Adjustable bell cut-off, auto restore time 2 to 15 minutes
- Latching panic circuit
- Built-in battery charger
- Built-in pulse stretcher
- Open circuit instant loop
- 24 hour latching panic circuit
- Remote instant/delay switch: single pole, single throw (Delay active when open)
- Full static and lightning protection
- Remote LEDs: Armed LED: Red, Secure LED: Green, Control will accept up to three LED remote stations
- Key switch momentary type, round or flat key, key switch not supplied
- Cabinet beige finish, knockout for optional camlock, knockout for cabinet mounted key switch, secure and armed LEDs, five additional knockouts

### Models

#### 6131NT

*Burglary Only, Entry/Exit Delay, Remote Arming, Battery and Transformer not included*

### Features

- Adjustable entry/exit delay, independently adjustable from 2 to 60 seconds

# ALARM CONTROLS



**ASSA ABLOY**

ASSA ABLOY, the global leader in door opening solutions