# IMPORTANT

Templates must be printed without size modifications and verified for dimensional accuracy.

- Before printing, select the printing options necessary to ensure that copies are produced without size adjustments.

- After printing, measure the dimensions indicated on the template to ensure correct scale.

1"
(SEE NOTE)

1-5/8"

3-3/8"

NOTE: 1" = DISTANCE FROM DOOR SURFACE TO CENTERS OF KEEPER MOUNTING HOLES (INCLUDES SMOKE GASKETS, RUBBER STOPS, ETC. THICK GASKETS MAY CAUSE KEEPER TO OVERHANG DOOR JAMB SLIGHTLY.

DRILL #22 OR 5/32" HOLES (7) FOR #10 SCREWS.

SURFACE-MOUNTED KEEPER -- DO NOT MORTISE.

FOLD UP 90 DEGREES ON DASHED LINE AND TAPE ONTO DOOR AND JAMB.

3-3/8"

1-1/4" DIA. DRILL ONLY FOR OUTSIDE RIM CYLINDER (CUT TAILPIECE TO PROJECT 3/8" BEYOND DOOR.)

7-5/8"

CENTERLINE OF LOCK TO BE 38" ABOVE FINISHED FLOOR.

FOR LOCKING SCREW. DO NOT DRILL UNTIL INSTALLATION IS COMPLETE AND ALL ADJUSTMENTS HAVE BEEN MADE. (SEE TEXT.)

3/8" WIRE-ENTRY HOLE

LOCK & KEEPER MOUNTING TEMPLATE, MODELS 265 & 715
ALARM LOCK SYSTEMS, INC., 345 BAYVIEW AVE., AMITYVILLE, NY 11701

P5709A
11/93