# **E Series Deadbolts**

#### **Classic Product**

Arrow E Series deadlocks are unsurpassed for value, quality and durability. Our tamper resistant rotating wrench-proof collar, steel deadbolt with hardened steel pin insert and concealed screws are security features that have made the E Series the most specified deadlock in its class.



## **Certification & Compliance:**

- ANSI A156.5, Auxiliary Locks, Grade 2
- Underwriters Laboratories (UL and CUL) listed for use on 3 hour fire doors when used in conjunction with a rated primary latching device.



## **General Specifications:**

**Housing** – Two-piece housing, with free spinning outer ring to prevent wrenching. Concealed mounting screws standard on double cylinder functions.

**Thru-bolting** – supplied with two 1/4" (6.35mm) steel thru-bolts.

**Deadbolt** – 1" (25.40mm) throw, solid steel deadbolt with hardened, free spinning, steel pin insert.

Backset - 2-3/8" (60.32mm), 2-3/4" (69.85mm)

**Deadbolt Fronts** – 2-1/4" (57.15mm) x 1" (25.40mm) standard for 2-3/8" (60.32mm) backset, 2-1/4" (57.15mm) x 1-1/8" (28.57mm) standard for 2-3/4" (69.85mm) backset. Drive-in deadbolts are available.

**Doors** – 1-3/8" (34.925mm) to 1-3/4" (44.45mm) thick standard. **Strikes** – Supplied standard with the #346 wood frame strike. The #345 metal frame strike is optional.

**Handing** – All functions are reversible.

**Cylinder, Standard** – Solid brass, Arrow "A" keyway, drilled for 6 pins, pinned to 5. E41 and E42 low profile deadbolts are supplied with 5-pin cylinders. Supplied with two brass keys. Available in Schlage CS keyway and other competitive keyways.

**Cylinder Options** – Accepts 6 or 7 pin, small format, interchangeable cores. Supplied less cores. Will accept Best<sup>™</sup> or Falcon<sup>™</sup> type cores.

#### **Finishes:**



	ВНМА	U.S. Equivalent	Arrow Equivalent	Finish
1	605	US3	03	Bright Brass
2	606	US4	04	Satin Brass
3	609	US5	05A	Antique Brass
4	612	US10	10	Satin Bronze
5	613	US10B	10B	Dark Oxide Bronze, Oil Rubbed
6	619	US15	15	Nickel Plated
7	625	US26	26	Bright Chromium Plated
8	626	US26D	26D	Satin Chromium Plated

