

HK Series Cylindrical Locksets

Professional Replacement Products



The HK series Grade 1 Cylindrical Knob lock is designed and tested for the most robust applications for Grade 1 knob locksets. Backed by the Arrow 10 year warranty and Certified to BHMA Grade 1 it is the worry free solution when a Grade 1 knob lock is needed.

A great choice for a variety of commercial applications when a Grade 1 knob is needed.

Features:

Lock Chassis – Cold rolled steel with zinc dichromate finish for corrosion resistance. Latch retractor is precision cast steel. Requires standard 2-1/8" (54mm) bore through door.

Backset – 2-3/4" (70mm) backset standard.

Door Thickness – 1-3/8" (35mm) to 2" (51mm).

Latch – Brass with 1/2" (13mm) throw. Latch housing is steel, zinc dichromate finish for corrosion resistance. 1" (25mm) bore in edge of door required.

Latch Front – Brass or stainless steel, 2-1/4" (57mm) x 1-1/8" (29mm), beveled 1/8" (3mm) in 2" (51mm).

Handing – Reversible.

Strike – Brass or stainless steel. ANSI A115.2, 4-7/8" (124mm) x 1-1/4" (32mm) curved lip standard. Optional 2-3/4" (70mm) x 1-1/8" (29mm) available.

All strikes have 1-1/4" (32mm) lip to center dimension.

Cylinder, Standard – Solid brass, 6 pin cylinder with Arrow "A" keyway. Supplied with two 6 pin nickel silver keys. Optional Schlage C keyway available.

Cylinder Options – Interchangeable core-lockset prepared for use with 6 or 7 pin interchangeable core. Supplied less core, but packed with 6 and 7 pin tailpieces. Will accept Best™ and Falcon™ type cores. Suffix "IC" to design.

Finishes:

BHMA	U.S. Code	Arrow Code	Finish
605	US3	605	Bright Brass
613E	US10BE	613E	Dark Oxide Bronze Equivalent
630	US32D	630	Satin Stainless Steel

Certification & Compliance:



- ANSI/BHMA A156.2, Series 4000, Grade 1.
- Underwriters Laboratories (UL and CUL) listed for use on 3 hour, A label single swinging doors.
- Federal Specification FF-H-106C.

Design:

