

MLX Series Cylindrical Lever Locks

Professional Replacement Products



The MLX Series is a robust Grade 2 lockset featuring a Freewheeling Lever for abuse resistance, two screw lockset install for quick installation and a 10 Year Mechanical Warranty. The perfect solution for replacing or upgrading locksets in commercial applications.

Features:

- Door Preparation** – Requires standard 2-1/8" (54mm) bore through door.
- Backset** – 2-3/4" (70mm) standard. 2-3/8" (60mm) backset latch available separately.
- Door Thickness** – Fits 1-3/8" (35mm) to 1-3/4" (44mm) doors standard.
- Latch** – Stainless Steel 1/2" (13mm) throw, UL Listed, guarded latchbolt on all locking functions.
- Latch Front** – 1-1/8" x 2-1/4" for 2-3/4" (70mm) backset.
- Exposed Trim** – MLX Levers are pressure cast zinc measuring 4-3/4" (121mm) in length. MLX Roses are wrought brass 3-11/32" (85mm) diameter. Total projection from face of door is 2-17/32" (65mm).

- Freewheeling Lever**
- Warranty** – Ten Year Warranty
- Handing** – Non-handed
- Packaging** – 6 per case
- Strike** – 4-7/8" ANSI (124mm)
- Cylinder** – Standard: solid brass, 6-pin, keyed different, Arrow A or Schlage C keyway. Optional: prep for small or large format interchangeable core cylinder (cylinder not included).
- Keys** – 2 brass keys

Finishes:

	BHMA	U.S. Equiv.	Arrow Equiv.	Finish
1	605	US3	03	Bright Brass
3	613E	US10BE	613E	Dark Oxide Satin Bronze Equivalent
5	626	US26D	26D	Satin Chromium Plated

Design:



Certification & Compliance:



- Arrow MLX Series Cylindrical Lever Locks are BHMA Grade 2 Certified, ANSI/BHMA A156.2, Series 4000
- All Arrow MLX Series Locks are U.L. and c.U.L. list for use on 3 hour, A label or lesser doors
- Meets American with Disabilities Act Requirements

Experience a safer and more open world