

QL Series Cylindrical Lever Locks

Professional Replacement Products



The QL Series is a robust Grade 1 lockset featuring a Freewheeling Lever for abuse resistance, two screw lockset install for quick installation and a 10 Year Mechanical Warranty. The perfect solution for replacing or upgrading locksets in commercial applications.

Features:

Door Preparation – Requires standard 2-1/8" (54mm) bore through door.

Backset – 2-3/4" (70mm)

Door Thickness – Fits 1-3/8" (35mm) to 1-3/4" (44mm) doors standard.

Latch – Stainless Steel 1/2" (13mm) throw, UL Listed, guarded latchbolt on all locking functions

Latch Front – 1-1/8" x 2-1/4" for 2-3/4" (70mm) backset.

Exposed Trim – QL Levers are pressure cast zinc measuring 4-3/4" (121mm) in length. QL Roses are wrought brass 3-11/32" (85mm) diameter. Total projection from face of door is 2-17/32" (65mm).

Freewheeling Lever

Warranty – Ten Year Warranty

Finishes:

	BHMA	U.S. Equiv.	Arrow Equiv.	Finish
1	605	US3	03	Bright Brass
3	613E	US10BE	613E	Dark Oxide Satin Bronze Equivalent
5	626	US26D	26D	Satin Chromium Plated

Handing – Non-handed

Packaging – 6 per case

Strike – 4-7/8" ANSI (124mm)

Cylinder – Standard: solid brass, 6-pin, keyed different, Arrow A or Schlage C keyway. Optional: prep for small or large format interchangeable core cylinder (cylinder not included).

Keys – 2 brass keys



Certification & Compliance:

- Arrow QL Series Cylindrical Lever Locks are BHMA Grade 1 Certified, ANSI/BHMA A156.2, Series 4000
- All Arrow QL Series Locks are U.L. and c.U.L. list for use on 3 hour, A label or lesser doors
- Meets American with Disabilities Act Requirements

Design:



Experience a safer and more open world

