

# RK Series Cylindrical Locksets

## Value Product

The RK Series has been enhanced to offer a wide variety of finishes and functions. The RK Series cylindrical locksets are an economical value for a variety of application. Perfect for multi-family housing markets, as well as light commercial applications.



### Certification:

The RK Series has been designed to meet the requirements of ANSI, A156.2, Series 4000, Grade 2 UL Listed for use on 3 hour, A label single swinging doors.



### Features:

**Construction** – Cold rolled steel with zinc dichromate finish for corrosion resistance. Requires standard 2-1/8" (54mm) bore through door.

**Backset** – 2-3/8" (60mm) or 2-3/4" (70mm).

**Door Thickness** – Fits 1-3/8" (35mm) to 1-3/4" (44mm) doors standard.

**Latch** – Brass 1/2" (13mm) throw, UL Listed, guarded latchbolt on all locking functions.

**Latch Front** – 1" x 2-1/4" (25mm x 57mm) for 2-3/8" backset (60mm) or 1-1/8" x 2-1/4" for 2-3/4" (70mm) backset.

**Exposed Trim** – Brass or stainless steel. Roses are 2-1/2" (64mm) diameter. Total projection from face of door is 2-3/4" (70mm).

**Strike** – 4-7/8" ANSI (124mm), 2-3/4" (70mm) T strike, or 2-1/4" (57mm) full lip strike.

**Cylinder** – Standard: solid brass, 6-pin, keyed different, Arrow A or Schlage C keyway. Optional: prep for small format interchangeable.

**Keys** – 2 brass keys.

**Handing** – Non-handed.

**Thru-bolts** – Removable thru-bolts standard on RL Series.

**Packaging** – 10 per case.

**Warranty** – Five Year Mechanical Warranty.

### Finishes:



	BHMA	U.S. Equivalent	Arrow Equivalent	Finish
<b>1</b>	605	US3	03	Bright Brass
<b>2</b>	606	US4	04	Satin Brass
<b>3</b>	612	US10	10	Satin Bronze
<b>4</b>	613	US10B	10B	Dark Oxide Bronze, Oil Rubbed
<b>5</b>	629	US32	32	Bright Stainless Steel
<b>6</b>	630	US32D	32D	Satin Stainless Steel