

For Handicap Access, Automatic Door Activation & Request-to-Exit Applications

- Door Opener Activation
- Automatic Door Activation
- Access Control Request-to-Exit (RTE)
- Door Sequencer Activation



can be used with wireless transmitter and receiver

SPECIFICATIONS

Mounting Plate	Heavy Duty 1/8" (3.2mm) mounting plate
Faceplate	Heavy 18 Gauge (1.02mm), 630/US32D Satin Stainless Steel Standard
Legends	Bold debossing or engraving with black, blue or white infill
Contacts	SPDT or DPDT, 15 Amps @ 125/250VAC; UL 1054, CSA Listed
Depth	[Narrow & (1) Gang] SPDT-7/8" deep, DPDT-1-3/8" deep, [4 1/2", & 6" square/ round] SPDT-3/4" deep, DPDT-1-5/32



1-11/16" Narrow Mullion Push Plate Switch – Recessed, Surface Box or Bollard Mount


SPDT Model	Description	Price	DPDT Model	Description	Price
48201U	Push to Open, black infill	69.00	48401U	Push to Open, black infill	96.00
482A1U	Push to Open, blue infill	69.00	484A1U	Push to Open, blue infill	96.00
400-1B	Narrow Mullion Surface Box, 1-3/4" x 4-9/16" x 1-3/4" O.D.				30.00



2 3/4" x 4 1/2" Single (1) Gang Push Plate Switch

- Pressing any part of the push plate (2 3/4" x 4 1/2") causes switch actuation
- Recessed, Surface Box or Bollard Mount
- Depth: SPDT - 7/8" deep; DPDT - 1 1/2" deep


SPDT Model	Description	Price	DPDT Model	Description	Price
48202U	Push to Open, black infill	83.00	48402U	Push to Open, black infill	110.00
482A2U	Push to Open, blue infill	83.00	484A2U	Push to Open, blue infill	110.00
480-2SB	Surface mount box, 2 3/4" x 4 1/2" x 1 5/8" O.D.				31.00



4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the push plates 4" 1/2" x 4 1/2" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	Price	DPDT Model	Description	Price
48204U	Push to Open, black infill	89.00	48404U	Push to Open, black infill	116.00
482A4U	Push to Open, blue infill	89.00	484A4U	Push to Open, blue infill	116.00
480-4FB	Square Flush Recessed box, 6 3/4" x 6 3/4" x 2-1/8" O.D.				67.00
480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless				42.00
480-4SB	Surface mount box, tmper resistant, 5-1/2" x 5-1/2" x 2-1/8" O.D.				67.00
480-4SE	3-sided stainless shroud for exterior applications, 4-11/16" x 4-7/8" x 12"				41.00



6" x 6" Square Push Plate Switch

- Pressing any part of the push plates 6" x 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount
- Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	Price	DPDT Model	Description	Price
48206U	Push to Open, black infill	96.00	48406U	Push to Open, black infill	122.00
482A6U	Push to Open, blue infill	96.00	484A6U	Push to Open, blue infill	122.00
480-6SBB	Surface mount box, 2-gang Battery Compartment, 4 1/2" x 4 1/2" x 1 3/4" O.D.				42.00

480 Series Push Plate Switches - Wireless and Hardwired (continued)

Distributor Discount Code **CK LIST**



4 1/2" Round Push Plate Switch

- Pressing any part of the push plates 4" 1/2 active area causes switch actuation
- 1 Gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
482O4RU	Push to Open, black infill	91.00	484O4RU Push to Open, black infill 118.00
482A4RU	Push to Open, blue infill	91.00	484A4RU Push to Open, blue infill 118.00
480-4RSB	Surface box, 5" Dia., 2 1/8" O.D.	60.00	480-4RFB Black Flush Escutcheon, 6 3/8" overall diameter with trim ring 67.00
480-4RG	4" round gasket for 4RSB or 4RFB box	17.00	



6" Round Push Plate Switch

- Pressing any part of the push plates 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1 1/2" deep

SPDT Model	Description	DPDT Model	Description
482O6RU	Push to Open, black infill	96.00	484O6RU Push to Open, black infill 122.00
482A6RU	Push to Open, blue infill	96.00	484A6RU Push to Open, blue infill 122.00
480-6RSB	Surface box Round, 6 7/16" Dia., 2 1/8" Depth	60.00	480-6RFB Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring 67.00
480-6RG	6" round gasket for 6RSB or 6RFB	18.00	

480 Series Push Plate Switches - HDPE (High Density Polyethylene)

Distributor Discount Code **CK LIST**



4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the push plates 4" 1/2" x 4 1/2" active area causes switch actuation
- 1 Gang recessed or Surface Box Mount • Depth: SPDT 3/4" min; DPDT 1-5/32" min

SPDT Model	Description	DPDT Model	Description
482A4SPH	Push to Open, white infill on blue HDPE, SPDT		156.00
484A4SPH	Push to Open, white infill on blue HDPE, DPDT		156.00
480-4FB	Square Flush Recessed box, 1-gang, 6 3/4" x 6 3/4" x 1 7/8" O.D.		67.00
480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless		35.00
480-4SB	Surface mount box, tamper resistant, 5-1/2" x 5-1/2" x 2-1/8" O.D.		67.00



6" Round Push Plate Switch

- Pressing any part of the push plates 6" active area causes switch actuation
- 1 Gang or 2 gang recessed or Surface Box Mount • Depth: SPDT 7/8" deep; DPDT 1-5/32"


SPDT Model	Description	DPDT Model	Description
482A6RPH	Push to Open, white infill on blue HDPE, SPDT		187.00
484A6RPH	Push to Open, white infill on blue HDPE, DPDT		187.00
480-6RSB	Surface box Round, 6 7/16" Dia., 2 1/8" Depth (not shown)		60.00
480-6RFB	Recessed Flush Escutcheon, 7 3/4" overall diameter with trim ring		67.00
480-6RG	6" round gasket for 6RSB or 6RFB		18.00



482A4VWU



482A4VWPU



482A4VPU



482A4VWPB



4 1/2" x 4 1/2" Square Push Plate Switches

- Pressing any part of the split push plates active area causes switch actuation
- 2 Gang Wall-mount or Surface Box Mount • Depth: 2x SPDT 7/8" deep

SPDT Model	Description	
482A4VWU	♿ Arrow (left/right), blue infill	405.00
482A4VWPU	♿ Arrow (left/right) Push to Open, blue infill	405.00
482A4VPU	Arrow (left/right) Push to Open, black infill	405.00
482A4VWPB	♿ Arrow (left/right) Push to Open, white infill on blue	468.00



480-4SBB	Surface mount box, 4-1/2" x 4-1/2" x 1 3/4" O.D. with Battery compartment for wireless	35.00
-----------------	--	--------------

Applications

- Wireless & Hardwire
- ADA Ingress/R.E.X/Egress Door Opener Activation
- Access Control Request-to-Exit (REX)
- Door Opener Activation
- Automatic Door Activation or Lock Release
- Automatic Door & Exit Device Sequencer Activation



can be used with wireless transmitter and receiver

Features

- Surface wall mount or bollard mount
- Sleek Architectural profile
- No square edges to snag, wide sloping sides deflects impact movement naturally to activate column
- Deflects impact from wheeled carts and conveyances
- Impact & Vandal resistant design, inhibits prying, tampering
- Weather Resistant, no gaps for water or ice penetration
- Choice of SPDT or DPDT, 15 Amps @ 125/250VAC



9" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

List

Fully Active 22-1/2 Sq. Inch Actuation Area
Recommended Centerline mounting height 34" to 48"

Material: Sturdy 1/8" extrusion with architectural finish
Overall Size: 9" h x 6" w x 1-1/2" d (229 x 152 x 38mm)
Active Area: 9" h x 2-1/2" w (229 x 63.5mm)

SPDT Model	Description	DPDT Model	Description
482AA9	♿ Push to Open	484AA9	♿ Push to Open
		309.00	336.00

SPECIFY FINISH Add to List

V 628 Aluminum (standard), blue infill	N/C	X 613 Dark Bronze, white infill	26.00
--	-----	---------------------------------	-------

36" X 6" INGRESS-R.E.X TOUCH PANEL COLUMN

List

Fully Active 90 Sq. Inch Actuation Area
Recommended mounting height is 3" from floor

Material: Sturdy 1/8" extrusion with architectural finish
Overall Size: 36" h x 6" w x 1-1/2" d (914 x 152 x 38mm)
Active Area: 36" h x 2-1/2" w (914 x 63.5mm)

SPDT Model	Description	DPDT Model	Description
482AA36	♿ Push to Open	484AA36	♿ Push to Open
		433.00	460.00

SPECIFY FINISH Add to List

V 628 Aluminum (standard), blue infill	X 613 Dark Bronze, white infill	26.00
--	---------------------------------	-------



400 Series Wireless Transmitter and Receiver



For Remote Control Versatility for Touch Panel Column and Push Plate Switches

433MHz Micro Transmitter

- Requires a non-metallic surface box or standard bollard cap (non-metallic). Works with 400RC433
- Pre-Wired for quick installation
- Antenna magnifies signal

Voltage Input: 9V Battery (included)
Trigger Input: Momentary, N.O.Dry Contact
Temperature: -20F — 100F
Dimensions: 1-9/64" x 15/16" x 7/32" (29 x 49 x 6mm)

Model	Description	
400W1-433	433MHz Micro Transmitter	141.00

433MHz 1 Channel Nano Receiver

- Designed to control automatic closing and anti-burglar systems. Works with 400W1-433.

Carrier Frequency: 433.92 MHz **Power Supply:** 12/24 VAC/DC
Relay Numbers: 1 **Contacts:** C-NO
Temperature: -4F — 158F **Dimensions:** 1-1/4" x 2" x 3/4" Deep (32 x 51 x 19mm)

Model	Description	
400RC433	433MHz 1 Channel Receiver	174.00

