

All-in-One Strikes

All-in-One Strikes BES-F2164 (Fire-Rated/Fail-Secure) BES-2364 (Fail-Safe)

These versatile All-in-One Strikes are designed for offset and centerline latch entry.

With 1500 pounds of holding force, BEST All-in-One Strikes combine strength and convenience in a versatile, easy to install design.

With the sawtooth adjustment locator, installers can adjust the strike to align with a wide variety of mortise locks with offset latches eliminating the need to order special faceplates making BEST All-in-One Strikes versatile and easy to install.







Plug-in Accessory Available

Endurance 50 500,000 Cycles



Five-year (Limited)

Mode Fail-Secure and Fail-Safe

All-in-One Strikes

Versatile, convenient and easy to install.

These electric strikes—featuring an adjustable deadbolt keeper and deadlatch ramp-combine strength and convenience in an attractive, sleek and easy-to-install design.

Product specifications

Faceplate	1-1/4" (32mm) W x 4-7/8"H (124mm)				
Insert depth	1-3/4 "D (45mm)				
Door lock type	Mortise, cylindrical and mortise exit device				
Frame type	Hollow metal, aluminum and wood				
Latch projection	1/2" (12.7mm) to 3/4" (19mm)				
Connectors	Plug-in wire				
Handing	Non-handed				
Optional accessories	BES-F2LM Latch monitor plug-in kit (2A @ 24VDC)				
Finishes	32D Brushed Stainless Steel				
Warranty	Five-year limited				
Certifications	UL 294 Listed for Access Control Unit Accessory (6th Edition) UL 1034 burglary-resistant Listed UL 10C, 3-hour fire-rating Listed ³ CAN/ULC S104, 3-hour fire-rating Listed ³ Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles				

Model	Mode	Volts	Duty	Sound	Amps	Ohms [*]
BES-F2164	Fail Secure	12VDC	Continuous	Silent	0.375	37
		24VDC			0.190	148
		12-24VDC	Intermittent	Buzz	0.280-0.565	37
BES-2364	Fail Safe	12VDC	Continuous	Silent	0.375	37
		24VDC			0.190	148

Intermittent Duty: Energized less than one minute with duty ratio 1:5 Continuous Duty: Energized one minute or more *Nominal resistance at +25°C ± 7% tolerance



¹ Max at 12VDC ² 12-24VAC not available with 2364 model

³ Fire-rated (F) model only. 3-hour for single swing, 90 minutes for standard pair of doors.

bestaccess.com





Adjustment Locator

Features

BEST All-in-One Strikes

- Modular design: compatible with most locks; no special faceplates required; non-handed
- Adjustable: deadbolt keeper and deadlatch ramp—up to 5/16" of strike for precise alignment with lockset; keeper shims for horizontal adjustment[±]—1/16" (1.5mm) and 1/8" (3mm)—for up to 1/8" (3mm)
- Run cool operation: solenoid design prevents keeper from heating up
- Heavy-duty construction: stainless steel with brushed stainless steel finish (32D)
- Holding force: up to 1500lbf (680kgf)
- Easy installation: non-handed; fits HES 1006 (1003) frame cutout (hollow metal)
- Secure: accommodates up to 3/4" latch projection; up to 1 " deadbolt (night-latch function only, bolt will not release)
- Included: faceplate, trim plate and anti-tamper security screws for centerline latch entry; star and security driver bit; and, adhesive paper template
- Field selectable voltage input: accommodates 12 or 24VDC and 12 to 24VAC
- Low current draw: 0.19 Amps @24VDC; plug-in wire connector
- Patents: US patent 9,580,935 and Canadian patent 2,850,072
- Warranty: five-year limited

Frame Type





Door Lock Type



Exit Device

Choose BEST All-in-One Strikes for a solution that you can trust.

Cylindrical

Aluminum



BA-0336 @ 2018 dormakaba USA Inc.

dormakaba 🚧 BEST is a trademark of dormakaba USA Inc. All rights reserved.

