

POWER TRANSFER



CONCEALED POWER TRANSFER UNIT SPECIFICATIONS

CAT EPT-2 -(2) 18AWG WIRES

MAX. RATING: UP TO 2 AMPS @24VDC

CAT EPT-10 -(10) 24 AWG WIRES

MAX. RATING: UP TO 1 AMP @ 24VDC



STANDARD FINISHES: AL - Aluminum, DU – DURO

PRODUCT DETAILS:

Housing Dimensions: 9”x 1.25”x 1.625”

Minimum door thickness - 1.75”

Box: 10.5” x 3.75”: x 2.5”

WEIGHT: 2.25 Lbs

15 MASTER PACK:

Box: 12.75” x 11.75” x 11”

WEIGHT: 34 ILbs

CAN BE USED IN COMBINATION WITH THE FOLLOWING HINGES	
HINGE TYPE	MAX DOOR SWING
BUTT HINGES UP TO 5”	180°
5 1/2” BUTT HINGES	130°
6” BUTT HINGES	110°
UP TO 3/4” OFFSET PIVOTS	180°
WILL WORK WITH CONTINUOUS HINGES - PLEASE CHECK WITH CONTINUOUS HINGE MANUFACTURER AS TO THEIR CUTOUT AVAILABILITY AND CHARGE FOR THIS CUTOUT	

FEATURES



- CAT EPT-2, CAT EPT-10 and CAT EPT-10C are designed to transfer electrical power from the frame to the door in a very secure manner.
- UL 10C-Listed for up to 3 hours for Fire Rated doors and frames Standard 7-2, “Fire Test of Door Assemblies”
- UL-Listed as Miscellaneous Fire Door Accessories
- Classified according to Uniform Building Code (UBC)
- Unit is mortised into the edges of the door and frame and is completely concealed when door is in the close position
- Designed for use in high traffic openings
- Packaged individually with fasteners for wood, steel or aluminum doors and frames
- All parts are made of metal including back boxes - no plastic parts
- Crimp connectors are supplied for a more secure and clean connection.

NOT FOR USE WITH

- Swing-clear hinges
- Pocket pivots
- Butt hinges larger than 6”
- 1 1/2” offset pivots
- Center hung doors

ACCESSORIES

- Add Molex Connector’s compatible with Allegion Connect or Assa Abloy Electrolynx system



MANUFACTURER CROSS REFERENCE

COMMAND ACCESS	CAL-ROYAL	VON DUPRIN	SECURITON	ABH	SDC
CAT-EPT2	CRPT-2	EPT2	CEPT-2	PT200	PTM-2
CAT-EPT10	CRPT-10	EPT10	CEPT-10	PT1000	PTM-10
CAT-EPT10C	CRPT-10C	EPT-10C	EL-CPT-10C		
*Brand names are trademarks or registered trademarks of their respective companies					

U.S. Customer Support
1-888-622-2377

Visit our website for more details
www.commandaccess.com

Canada Customer Support
1-855-823-3002

Command Access is not a licensee, or affiliated, associated or connected with Allegion, Assa Abloy, Stanley, Schlage, Falcon, Von Duprin, Dorma, Sargent, Corbin Russwin, Yale, Emtek, Adams Rite, Best, Precision, Arrow, Design Hardware, Cal Royal, Jackson, AHT, Marshall Best, Marks, Accurate, Baldwin, FSB, PDQ, Lawrence, Trans Atlantic, Hager, LSDA, General Lock, or Omnia or any of their subsidiaries or affiliates.

#20454_A