

How to Order CLS-XLS Interconnected Lock

QTY	SERIES	FAMILY	FUNCTION	LEVER	FINISH	TRIM	HANDING	BACKSET	STRIKE	CYLINDER	KEYWAY	KEYING	OPTIONS
	CLS	XLS	126	PHL	605	—	RH	Deadbolt	T	D	SCC	KD	—
				BSN	613	Round Rose (de- fault) SR - Square Rose	LH	234 - 2-3/4"	T - "T" Strike ASA - ANSI/ASA (default) FL - Full Lip	D - Default L - Less Cylinder SF6 - SFIC w/Core, 6 Pin SF7 - SFIC w/Core, 7 Pin	AR1	KD - Keyed Different	SF - Split Finishes DB - Dust Box
			MIA	622	238 - 2-3/8"		CO59A1	KO - Zero Bitted					
			ORL	626	Cylindrical		234 - 2-3/4"	CL4	KA - Keyed Alike				
			MEM*		238 - 2-3/8"		234R	RUD	KE - Keyed to Existing				
						238R	SCE	MK - Master Key					
							SCC	CMK - Construc- tion Master Key					
							SCC-K						
							SAL						
							RA-RC						
							YA8						
							GA						
							FAL						
							KW						
							TA						
							A (BEST Keyways)						
							PDQ1						
							PDQ2						
							PDQ3						



*MEM Specify Handing

Headquarters: 2230 Embassy Drive, Lancaster, PA 17603
 Phone: 866.874.3662 | Email: smartsupport@pdqlocks.com
www.pdqsmart.com