

















MAGNETIC LOCKS

FEATURES

- COMPATIBLE WITH ALL ACCESS/EGRESS SYSTEMS
- ALUMINUM / STAINLESS CASINGS ARE WEATHER AND VANDAL RESISTANT
- SELECTABLE 12V/24V DC OPERATION
- ON BOARD MOV'S PROVIDE PROTECTION AGAINST VOLTAGE SPIKES AND SURGES
- ASSORTED MOUNTING BRACKETS AND FILLER PLATES AVAILABLE

ITEM	MODEL	DESCRIPTION	CURRENT DRAW	DIMENSIONS
1200 LBS. SURFACE MOUNT SINGLE DOOR  	CX-915-12	Basic	500 mA @12V 250 mA @24V	Body: 2 7/8"H x 10 1/2"W x 1 9/16"D (73mm x 266mm x 40mm) Armature Plate: 2 13/32"H x 7 9/16"W x 7/16"D (61mm x 192mm x 16mm)
	CX-915-12TDS	c/w Adjustable Timer, Lock Sensor, Door Status Switch, Relay & LED		
1200 LBS. SURFACE MOUNT DOUBLE DOORS  	CX-925-12	Basic	2 x 500 mA @12V 2 x 250 mA @24V	Body: 2 7/8"H x 21"W x 1 9/16"D (73mm x 533mm x 40mm) Armature Plate: 2 x 3"H x 7 15/16"W x 5/8"D 2 x (76mm x 202mm x 16mm)
	CX-925-12TDS	c/w Adjustable Timer, Lock Sensor, Door Status Switch, Relay & LED		
600 LBS. SURFACE MOUNT SINGLE DOOR  	CX-915-06	Basic	500 mA @12V 250 mA @24V	Body: 1 7/8"H x 9 5/32"W x 1"D (48mm x 250mm x 25mm) Armature Plate: 1 1/2"H x 9"W x 1/8"D (38mm x 229mm x 11mm)
	CX-915-06TDS	c/w Adjustable Timer, Lock Sensor, Door Status Switch, Relay & LED		
600 LBS. SURFACE MOUNT DOUBLE DOORS  	CX-925-06	Basic	2 x 500 mA @12V 2 x 250 mA @24V	Body: 1 7/8"H x 19 11/16"W x 1"D (48mm x 500mm x 25mm) Armature Plate: 2 x 1 1/2"H x 7 13/32"W x 7/16"D 2 x (38mm x 188mm x 11mm)
	CX-925-06TDS	c/w Adjustable Timer, Lock Sensor, Door Status Switch, Relay & LED		
600 LBS. MORTISE MOUNT SINGLE DOOR  	CX-91M-06	Basic	480 mA @12V 240 mA @24V	1 1/2"H x 9"W x 1/8"D (38mm x 229mm x 11mm)
	CX-91M-06TLS	c/w Adjustable Timer & Lock Sensor/Relay		
300 LBS. SURFACE MOUNT SINGLE DOOR 	CX-905-03	Basic	360 mA @12V 180 mA @24V	1 3/8"H x 6 1/2"W x 13/16"D (35mm x 165mm x 21mm)
300 LBS. MORTISE MOUNT SINGLE DOOR 	CX-90M-03	Basic	360 mA @12V 180 mA @24V	1 3/8"H x 8"W x 13/16"D (35mm x 203mm x 21mm)
1200 LBS. SURFACE MOUNT GATE LOCK 	CX-945-12LS	c/w Lock Sensor/Relay	500 mA @12V 250 mA @24V	2 1/2"H x 8"W x 1 5/8"D (63mm x 203mm x 41.5mm)
1200 LBS. MORTISE MOUNT SHEAR LOCK 	CX-93M-12LS	With Bond Sensor	310 mA @12VDC 180 mA @24VDC	Lock: 1 3/8"H x 7 1/4" W x 1"D (35mm x 184mm x 25mm) Control Board: 2 1/2"H x 8" W (63mm x 203mm)

ELECTRIC STRIKES
MAGNETIC LOCKS
DOOR ALARMS
RELAYS & TIMERS
POWER SUPPLIES
TRANSFORMERS
ANNUNCIATORS
RESTROOM CONTROL KITS