



CX-ED1259L
SURFACE MOUNT
RIM ELECTRIC STRIKE

STANDARD FEATURES	CAMDEN CX-ED1259L	RCI-0162	HES-9600	HES-9500	HES-9400	TRINE 4800F	SECO LARM SD-998C-NUQ	SECO LARM SD-998C-NUAQ	VON DUPRIN 6300
Heavy Duty Stainless Steel construction	√	√	√	√	√	√	X	X	√
Fire label 10C 3 Hr.	√	√	X	√	X	√	X	X	√
UL1034 Burglary Resistant	√	√	√	√	√	√	√	√	√
Tested to ANSI-Grade 1	√	√	√	√	√	√	√	√	√
Plug in wire connectors	√	X	√	√	√	√	√	√	X
Dual voltage	√	√	√	√	√	√	√	√	√
Monitor switch standard	√	X	X	X	X	X	X	X	X
Non Handed	√	√	√	√	√	√	√	√	√
Adjustable for different latch/frame spacing	√	X	X	X	√	X	X	X	X
Standard cover plate	√	X	√	√	√	X	X	X	X
Easy Installation	√	√	√	√	√	√	√	√	√
Endurance cycles	2,000,000	2,000,000	1,000,000	1,000,000	500,000	1,500,000	250,000	250,000	2,000,000

Note: Specifications are subject to change without notice.