

MOUNTING INFORMATION

Sex nuts or through bolts are required for wood and plastic covered composite doors, and any type of door without reinforcements and recommended for wood core and metal clad (Kalamein) type doors.

RH SHOWN
LH OPPOSITE


CAUTION: Closer To Be Installed In A True Horizontal Position To Ensure Proper Closer Performance.

NOTES:

1. Dimensions given in inches and (mm).
2. Minimum Top Rail:
Standard Header Width: 1-7/8 (48)
Narrow Header Width: 2-1/4 (57)
3. Auxiliary door stop required, by others.
4. Center hung doors must be single acting.
5. Maximum Opening is based on a 3-1/4 (83) reveal. Deeper reveals will limit the degree of opening.


MOUNTING SCREW SPECIFICATIONS
ARM AND QUIK-INSTALL™ BRACKET

#12-14 self-drilling screw.
1/8 (3) diameter pilot hole } or { Sex nuts, furnished when ordered
Applications.



OPENING MAXIMUM	A	B	HINGE CONDITION
110°	6-7/8 (175)	14 (356)	Butts, Offset Pivots, and Swing Clear Hinges
140°	5-1/8 (130)	12-1/2 (318)	
180°	3-3/8 (86)	10-1/2 (267)	
140°	5-1/8 (130)	12-3/8 (314)	CENTER HUNG

HEADER WIDTH	C	D	E _{MIN}	F _{MIN}
STANDARD	1-1/2 (38)	3/4 (19)	2-1/8 (54)	4 (102)
NARROW	1-7/8 (48)	3/8 (10)	1-3/4 (45)	3-5/8 (92)



RESPONSIBILITY

Door and Frame Manufacturers are responsible for providing adequate construction or reinforcements for proper installation of hardware shown. All architectural builders hardware must be installed on properly reinforced doors and frames, regardless of the type, material, or method of construction.

DC8220 Series

Top Jamb Arm Mounted
Surface Door Closer
(with or without A1/A6/A8)



ASSA ABLOY

www.corbinrusswin.com

Do Not Scale Drawing

Supersedes	Dr.	App.
Date 04-08	Template Number	T31103