



Notes:

1. Do not scale drawing.
2. Dimensions are in inches (mm).
3. LHR door shown. Preparation is typical for both door hands.
4. Minimum door stile width: 4-1/2(114).
5. Prepare mounting holes when installing the device.
6. Unreinforced frames require blind rivet nuts (by others) to mount the strike.
7. Dimension from door face.
8. For recommended door reinforcements see template T30800. Unreinforced doors require SNB option to mount the device components.
9. Holes for optional SNB: 9/32 (7) dia. inside door face; 3/8 (9.5) dia. outside door face.
10. Provide door stiffeners as needed to prevent door collapse due to installation with power tools, door use, or abuse.
11. Device mount to hinge stile (not shown) requires hole location and preparation during device installation.
12. For outside trim preparation see appropriate trim template.
13. For electrical devices (suffixes M91, M92, M93, M94, M97) also see template T30890.
14. Doors greater than 3'0" (914) in width and greater than 60 psf require 14 gauge horizontal stiffener.



FRAME TEMPLATE	MULLION		
	SERIES	SIZE	ILLUSTRATION
T30882	700 Series	1-1/2" x 3" (38 x 76)	<p>Doors 1-1/2" Mullion Width</p>
T31074	900 Series	2" x 3" (51 x 76)	<p>Doors 2" Mullion Width</p>
T31075	FE700 Series WS700 Series		

CAUTION: Width of mullion used with exit device will affect device backset. Determine Mullion Series and Width before prepping doors for exit devices.

WINDSTORM CERTIFIED
ED5202S X M107 Series Double Cylinder
SecureBolt™ Panic Exit Device with 710F458 Strike
Application for Metal Door and Frame or Mullion



ASSA ABLOY

www.corbinrusswin.com

SUPERSEDES T30997-1	DO NOT SCALE DRAWING
TEMPLATE NUMBER T30997-2	DATE 03-08