



TO BE USED FOR:
 AD-FE8400
 FED4800 AD

NOTES:

1. DOOR PREPARATION SHOWN FOR INSIDE DOOR ONLY.
2. IF OUTSIDE PULL AND/OR OUTSIDE CONTROL IS USED, SEE APPROPRIATE DOOR TEMPLATE FOR OUTSIDE DOOR PREP.
3. *MIN BACKSET FOR SINGLE DOOR IS BASED ON 1/2" FRAME STOP. LARGER FRAME STOPS REQUIRE LARGER BACKSET.
4. SURFACE OF DOOR WHERE EXIT DEVICE IS TO BE APPLIED, MUST BE FLUSH.
5. WE RECOMMENDED THAT ALL TAPPED HOLES BE DRILLED AND TAPPED IN FIELD.
6. TOLERANCE ALL FRACTIONAL DIMENSIONS $\pm 1/64"$.
7. BOTTOM AND TOP STRIKES MUST BE USED. SEE STRIKE TEMPLATE NO. MEDT6.
8. SEE TEMPLATE NO. MEDT7 FOR AUX CONTROL IF REQ'D.
9. FOR DEVICES WITH NO BOTTOM ROD, HOLES FOR BOTTOM CASE ARE NOT REQUIRED.

ASSA ABLOY

Locking Solutions
 ASSA ABLOY
 10000 W. 10th Ave. Suite 100
 Denver, CO 80202

DOOR MANUFACTURE TEMPLATE:
 NARROW CONCEALED VERTICAL ROD
 FOR ALUM DOORS (INSIDE FACE ONLY)
 EXIT DEVICES

RELEASE DATE

05/02/22

TEMPLATE NO.

MEDT1