



- NOTES:
- FOR LOCATION OF VERTICAL AND HORIZONTAL  $\bar{C}$ , AND ADDITIONAL EXIT DEVICE PREP, REFER TO APPROPRIATE EXIT DEVICE TEMPLATE.
  - HARNESSES ROUTES MAY DIFFER BY DOOR, CONSULT DOOR MANUFACTURER'S SPECS FOR ROUTES USED.
  - FOR ELECTROLYNX™ APPLICATIONS REFER TO MCKINNEY TRANSFER DEVICE CATALOG.
  - 3/8" RACEWAY FOR ELECTROLYNX™ APPLICATIONS REFER TO MCKINNEY TRANSFER DEVICE CATALOG.
  - CONSULT WITH POWER TRANSFER DEVICE MANUFACTURER AND DOOR MANUFACTURER FOR DOOR AND FRAME TEMPLATE DETAILS.
  - FOR MODIFIED RAIL LENGTHS; POSITION HOLE .250" BEYOND END OF RAIL.
  - DOOR MFG TO PROVIDE CLEARANCE IN REINFORCEMENT TO ALLOW INSERTION OF ELECTRICAL WIRES RUNNING BETWEEN RAIL AND ELECTRIC HINGE. MAKE PROVISIONS TO PROTECT WIRES FROM ABRASION.

ELECTRIFIED EXIT DEVICE RAIL  
PREP LOCATION

DIMENSION "X" CROSS-  
REFERENCE CHART

DOOR WIDTH	DIM "X" FOR WIDE STYLE CHASSIS
48"	41.912"
47"	40.912"
46"	39.912"
45"	38.912"
44"	37.912"
43"	36.912"
42"	35.912"
41"	34.912"
40"	33.912"
39"	32.912"
38"	31.912"
37"	30.912"
36"	29.912"
35"	28.912"
34"	27.912"
33"	26.912"
32"	25.912"
31"	24.912"
30"	23.912"
29"	22.912"
28"	21.912"
27"	20.912"
26"	19.912"
25"	18.912"
24"	17.912"

AUTHORIZED PREMIUM EXIT DEVICE  
PREFIX TEMPLATE AND INSTRUCTION SHEET

DESCRIPTION	OPTION	INSTALLATION INSTRUCTIONS	OPTION	INSTALLATION INSTRUCTION
LATCH MONITOR SWITCH	53-	A8299	M91	FMS75
SIGNAL SWITCH RAIL	55-	A8299	M92	FMS75
ELECTRIFIED LATCH RETRACTION	56-	A8297	MELR	FMS73
ELECTRIC DOGGING	58-	A8299	M97	FMS75
DELAYED EGRESS	59-	A8298	D	FMS74
ALARMED	AL-	A8325	M61	FM618

ASSA ABLOY

ASSA ABLOY

DOOR MANUFACTURER TEMPLATE:  
ELECTRO-MECHANICAL  
EXIT DEVICE RAILS(WIDE DESIGN)

RELEASE DATE  
04/07/22  
TEMPLATE NO.  
MEDT17