



FOR USE WITH TRIMS:
P704
P744
847PT
857PT
947PT
957PT

- NOTES:
1. TOLERANCE ON ALL DIMENSIONS  $\pm 1/64"$ .
  2. WE RECOMMEND THAT ALL TAPPED HOLES BE DRILLED & TAPPED IN FIELD.
  3. FOR MOUNTING LOCATION SEE STRIKE TEMPLATE MEDT39 (649 STANDARD STRIKE) FOR HC RIM EXIT DEVICES.
  4. SEE MASTER SHEET No. MEDT23 FOR AREAS REQUIRING REINFORCEMENTS.
  5. SURFACE OF DOOR WHERE EXIT DEVICE IS TO BE APPLIED MUST BE FLUSH.
  6. FOR OUTSIDE TRIM SEE TEMPLATE MEDT20.
  7. FOR GLASS BEADED DOORS, IF GLASS BEAD CANNOT BE REMOVED, USE GLASS BEAD SHIM KIT (AVAILABLE ON ORDER).

<b>ASSA ABLOY</b> Opening Solutions <small>Experience a safer and more open world.</small> <small>1-800-881-1111 • www.assaabloy.com</small>	TEMPLATE: HC RIM EXIT DEVICE FOR USE WITH KEY LATCH-RETRACT TRIM FUNCTIONS	RELEASE DATE <b>5/24/23</b>
		TEMPLATE NO. <b>MEDT76</b>